


MultiSync® X464UNS-2 LCD 46" Video Wall Display

Datasheet



Video Walls you can rely on

The ultra slim MultiSync® X464UNS-2 sets the standard for video wall technology. Featuring a minimal 3.5 mm bezel these display modules create impressive high resolution video walls with barely visible image gaps. With perfect picture quality and high product reliability, these displays are designed for the rigors of 24/7 operation. At a high brightness level of 700 cd/m² your message will be well received with effortless readability even in the brightest ambient light conditions. The panel size of 46" makes these video wall displays ideal for narrow spaces, for mobile use or frequent set-up and take-down in rental installations. An advanced set of intelligent features make the displays easy to install and operate and support significantly reduced maintenance requirements.

NEC's vast experience in the video wall market is evident in the design of the X464UNS-2 with features that reduce costs, ease installation and improve the visual impact of content in control rooms, broadcast studios, transport installations, retail signage and the rental market.

Benefits

Compelling Image Presentation - the display can be hardware colour and brightness calibrated to secure a consistent image presentation over the entire video wall.

Continous Workflow - reliable and secure for mission critical applications with 24/7 operational performance.

Reduced Installation and Operating Costs - highly energy efficient LED backlit display ensures low power consumption, longer backlight lifetime and lighter design for easy transportation, mounting and integration.

Smart Way to Large Scale perfectly detailed Imagery - native UHD Daisy Chaining enables the user to create UHD video walls with either a single UHD image or 4 different Full HD sources.

Easy Setup - Auto TileMatrix offers time and cost savings during installation. Configure just one display in order to complete the set up for the entire wall.

Perfect Visual Experience - FrameComp supports a seamless appearance, crucial for fast moving content, creating one stunning image by synchronising the content across the entire video wall.

Secure Reliability and Longevity of Video Walls - unique NEC heat management system enables the user to monitor and control the heat inside the display.

Future Ready with OPS Cable Free Expansion - upgrade the power of your display at any time while seamlessly integrating

one of our various Slot-in PCs, signal interfaces and other OPS compatible products without the need for external cables or devices.

Free Download of Multi-Display Management Software – with NaViSet Administrator 2 you can manage all your connected display devices from a centralised location.

Product Information

Product Name	MultiSync® X464UNS-2
Product Group	LCD 46" Video Wall Display
Order Code	60004172

Display

Panel Technology	S-PVA with direct LED backlight
Active Screen Area (W x H) [mm]	1,018.1 x 572.7
Screen Size [inch/cm]	46 / 116.8
Aspect Ratio	16:9
Brightness [cd/m ²]	700, 420 Eco (shipment setting)
Contrast Ratio (typ.)	3500:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	8
Panel Refresh Rate [Hz]	60
Haze Level [%]	25
Supported Orientation	Face Up; Landscape; Portrait

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 91.1
Vertical Frequency [Hz]	50 - 85

Resolution

Native Resolution	1920 x 1080 at 60 Hz			
Supported on DisplayPort and HDMI	3840 x 2160 (24/30 Hz); 1920 x 1080; 1600 x 1200; 1360 x 768;	1280 x 1024; 1280 x 768; 1080i; 1080p;	1024 x 768; 800 x 600; 720p (50/60 Hz); 640 x 480;	576p (50 Hz); 480p (60 Hz)
Supported on HDMI only	4096 x 2160 (24 Hz); 3840 x 2160 (25 Hz);	1360 x 768; 576i (50 Hz);	480i (60 Hz)	

Connectivity

Input Video Analogue	1 x D-sub 15 pin
Input Video Digital	1 x DisplayPort (with HDCP); 1 x DVI-D (with HDCP); 1 x HDMI (with HDCP)
Input Audio Analogue	2 x 3,5 mm jack
Input Audio Digital	1 x DisplayPort; 1 x HDMI
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
Output Video Digital	1 x DisplayPort out (loop through: DisplayPort, DVI-D, HDMI, Interface Extension Slot, OPS)
Output Audio Analogue	1 x 3,5 mm jack
Output Control	1 x LAN 100Mbit

Open Modular Intelligence

OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)
----------	--

OPS Max. Current / Power 10 / 61
Consumption [A / W]

Interface Extension Slot

Slot Technology analogue and digital interface extension (NEC standard)

Sensors

Ambient Light Sensor Optional, triggered actions programmable
Human Sensor Optional, external, 4-5m range, triggered actions programmable
Temperature Sensor Integrated, 3 sensors, triggered actions programmable
NFC Sensor Integrated, 2cm range, free NEC Android App required

Electrical

Power Consumption [W] 120 Eco (shipment setting), 150
Power Savings Mode [W] < 0.5 (ECO Standby); < 1
Power Management VESA DPMS

Environmental Conditions

Operating Temperature [°C] +0 to +40
Operating Humidity [%] 20 to 80

Mechanical

Dimensions (W x H x D) [mm] Without stand: 1,022 x 576.6 x 101.7
Weight [kg] Without stand: 19.9
Bezel Width [mm] 1.2 bottom/right; 2.3 top/left; 3.5; Content to content 3.7
VESA Mounting [mm] 300 x 300 (FDMI); 4 holes; M6
Ingress Protection IP40 (front); IP20 (back)

Additional Features

Special Characteristics Auto ID assignment; Auto tiling function; Automatic Alarm E-Mails; DICOM Simulation; Frame Comp; HTTP Server; Image flip; Intelligent Wireless Data (based on NFC); NaViSet Administrator 2; Point Zoom Function; Programmable 10-bit LUT with 3 memory banks; Sticky Note Function in OSD; Super slim bezel with 3.7 mm between contents and 3.5 mm bezel width; TileMatrix; User readable log function
Colour Versions Black Front Bezel, Black Back Cabinet
Safety and Ergonomics C-tick; CE; FCC Class A; PSB; RoHS; TÜV GS; UL/C-UL or CSA; VCCI
Audio Optional Speakers (15 W + 15 W)
Shipping Content CD-ROM (User Guides/Manuals); Display; DisplayPort Cable; Free LAN control software (download); Power Cable
Signal Cable: LAN cable
Warranty 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension
Operating Hours 24/7

Available Options

Accessories Calibration kit (KT-LFD-CC2); Feet (ST-322); Overframe kit (KT-46UN-OF5); Remote control kit (KT-RC2); Speaker (SP-RM1); Trolley (PD02VWM 2x2 46 55 L, PD02VWM 3x3 46 55 L); Wall mount (PD02VW MFS 46 55 L/P, easyFrame02 X46UN, PD03VWXUN 46L, PD02VWXUN 46P)
Interface Extension SB3-AB1 analogue: Audio; Component; Composite; S-Video
SB3-AB2 analogue: Audio; RGBHV

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 199 kWh (based on 4 operating hours per day); Carbon savings meter; ECOMode; Energy efficiency class: C; Human Sensor
Ecological Materials	Manuals on CD; Optional feet



CE



C-tick



FCC Class A



RoHS



TÜV GS



VCCI

This document is © 2018 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 09.08.2018