

UHD7510/PC BK/WH

75" 4K Ultra High Definition
Interactive Flat Panel Display



Multi Point
Touch Screen



This smart new 75" Hitachi Interactive Flat Panel Display has been designed for a variety of uses from boardrooms, classrooms, lecture theatres, foyers and consultation rooms.

Within its sleek contemporary bezel frame the UHD7510BK/WH incorporates a host of clever features, which includes 10 point multi-touch interactivity, edge LED backlighting, anti-glare tempered screen, wide viewing angle, superb contrast ratio and two powerful 12W speakers.

Features:

UHD 4K Resolution

Black/White Bezel Design

Anti-Glare Tempered Glass

Wide Viewing Angle Screen

10 Point Multi-Touch

Windows 10 Compatible

Built-in PC Option Available

VESA Mount



UHD7510BK/WH Interactive Flat Panel

Technical Specifications

Models available		UHD7510WH (White colour) UHD7510WHPC (White colour with PC) UHD7510BK (Black colour) UHD7510BKPC (Black colour with PC) (White and Black models available depending on your region - please check with your sales representative).
LCD Component		75" (1650 x 928 mm) diagonal
Backlight		Edge LED
Max. Resolution		3840 x 2160
Max. Colours		16.7 million colours (8 bit)
Brightness		400 cd / m ²
Contrast Ratio		4000:1
Viewing Angle (H/V)		178° / 178°
Supported Resolutions		640 x 480, 800 x 600, 1024 x 768, 1280 x 720, 1280 x 768, 1280 x 960, 1280 x 1024, 1400 x 1050, 1440 x 900, 1920 x 1080, 3840 x 2160
Supported Signals		VGA, SVGA, XGA, WXGA, Full HD, WUXGA, 4K
Panel Life Time		50,000 Hours
Max Daily Usage		16 hours
Frequency		120 Hz
Touch Screen		Infrared (10 points multi-touch support)
Glass		Anti-glare tempered
Input Terminals	Digital	2 x HDMI (2.0), 2 x display port (In/Out)
	Analog	VGA x 1 D-Sub 15-pin component (YPbPr)
	Audio	Microphone mini 3.5 mm jack x 1, Line out 3.5 mm x 1
	Control (RS-232C)	D-Sub 9-pin x 1 for device control Ethernet RJ45 Port
	USB	2 x Type A for Media playback
	LAN	10/100Mb
Wireless		Built in 802.11 a/g/n
Speaker		2 x 12W
Touch Panel	Detection Method	Infrared
	Detection Area	1650 (H) x 928 (V) mm
	Touch Accuracy	+ / -2 mm
	PC Connector	USB Mini A
	Driver	Windows multi touch support MAC single touch support
	Touch Pen	Yes
Power Requirement		110 - 240 V / 50 - 60 Hz
Operating/Storage Temperature		0 to 40°C
Operating/Storage Humidity		20% - 80%
Power Consumption		Operating: 320 W / Stand-by: <3 W
Dimensions (mm)		1731 (l) x 1008 (h) x 119 (d) mm
VESA Mount Dimensions		600 x 400 mm (M8 Screw Type)
Weight		59Kg
Colour		Black/white bezel
Main Accessories		Remote Control, Batteries: 2 x AAA, Quick start guide, IR Extender, OPS Antenna (if your model includes OPS), Mini USB to USB cable, 4 x Cable management clips, Wall mount, Touch pen
Remote Control		Part No: 30085692
Optional Accessories		Touch Pen
Certification		CE, R&TTE, RED, S Mark, WEEE, RoHS, EMC, Energy Rating Label, REACH
OPS PC Specification	Processor	Intel® Core™ i5-6200U Skylake-U SoC
	Operating system	Windows 10
	GPU Chipset	Intel® HD Graphics 520
	WLAN	802.11 a / g / n
	Bluetooth	V 4.0
	Ports	1 x RS232, 3 x USB3.0, 1 x USB2.0, 1 x VGA (OUTPUT), 1 x Headphone 3.5 mm jack, 1 x Microphone 3.5 mm jack, LAN 10/100 Mb, 2 x WiFi antenna connector
	System Memory	RAM 8 GB, HDD 500 GB
Warranty		3 or 5 years depending on your region (please check with your local dealer)

HITACHI
Inspire the Next

HITACHI DIGITAL MEDIA

Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road
Maidenhead, Berkshire SL6 8YA, United Kingdom

Tel: +44 (0)1628 585 000 / Fax: +44 (0)1628 585 163

www.hitachidigitalmedia.com