

## Graphic Floor Markers -

FM01-FM38



## Catalogue Text

A high visibility floor marker designed to highlight warnings or special requirements. The markers are printed onto the underside of a clear PVC film and then laminated on the back surface with an aggressive permanent adhesive. Suitable for use on dry, clean flat sealed surfaces and although designed for the floor, can be used on walls or anywhere a tough permanent sign is required.

## Material & Adhesive Specification

| Subject                                 | Value                          | Test Method |
|-----------------------------------------|--------------------------------|-------------|
| Material                                | 0.3mm PVC rigid film, plus DST | N/A         |
| Type of adhesive                        | Solvent acrylic (0.082mm)      | N/A         |
| Double sided Tape (DST)                 | 0.095mm                        | N/A         |
| Initial Tack (cm)                       | 12                             | PSTC-6      |
| Peel adhesion (kg/25.4mm <sup>2</sup> ) | 1.3                            | PSTC-1      |
| Holding power (hr.25.4mm <sup>2</sup> ) | Over 1                         | PSTC-7      |
| Resistance to water (months)            | 10                             | PSTC-35     |
| Resistance to chemicals (months)        | 8                              | PSTC-35     |
| Resistance to motor oil                 | Excellent                      | PSTC-35     |
| Temperature range                       | -30° C ~ +70° C                | See below   |
| Slip assessment dry pendulum test       | 66 median Low Slip Risk        | PTV@45°+90° |

The Independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, (test results available)  
NB All wet floors are hazardous so slip risk when wet not specified. All the above data is for reference only.