

Graphic Floor Markers -

No Text



FM01



FM24



FM31



FM28



FM38



FM21



FM30



FM29



FM32



FM34



FM25



FM26



FM27



Catalogue Text

- 430mm diameter high visibility floor markers
- Printed onto the underside of a clear PVC film
- Laminated with an aggressive permanent adhesive
- For use on dry, clean flat sealed surfaces, floors or walls

Material & Adhesive Specification

Subject	Value	Test Method
Material	0.3mm PVC rigid film, plus DST	N/A
Type of adhesive	Solvent acrylic (0.082mm)	N/A
Double sided Tape (DST)	0.095mm	N/A
Initial Tack (cm)	12	PSTC-6
Peel adhesion (kg/25.4mm ²)	1.3	PSTC-1
Holding power (hr.25.4mm ²)	Over 1	PSTC-7
Resistance to water (months)	10	PSTC-35
Resistance to chemicals (months)	8	PSTC-35
Resistance to motor oil	Excellent	PSTC-35
Temperature range	-30° C ~ +70° C	See below
Slip assessment dry pendulum test	66 median Low Slip Risk	PTV@45°+90°

The Independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, (test results available)
NB All wet floors are hazardous so slip risk when wet not specified. All the above data is for reference only.