

Half Circle Floor Graphic Markers



Catalogue Text

- Large 750mm wide x 375mm deep floor markers
- Ultra-low (0.45mm thick) helps prevent pallets catching the edge
- Super strong adhesive quality - suitable for use in busy workplace environments
- Slip-resistance tested to R9 standards
- Highlights the area to keep clear in front of fire doors to ensure safety
- Available in 12 text designs and 8 non-text designs

These large anti-slip floor markers can be used on any flat, sealed surface. Ideal for use in front of fire exit doors, to highlight fire extinguisher areas or to warn/highlight any important messaging. The slimline markers feature an aggressive, permanent adhesive suitable for busy industrial environments - offering quick and easy installation compared to traditional marking methods - whilst remaining extremely wear resistant.

Material Specification

Adhesive

80 micron Polymeric White PVC film
Permanent & Grey adhesive
Double-side PE Coated Liner
Up to 5 years durability
Fire Certification -
Class B. BS EN 13501-1:2007

Anti-slip laminate tested to R9 standards

Property	Specification	Test Method
Thickness (Including adhesive)	105 μ m \pm 10%	Micrometer
Tensile Strength	\geq 1.8kg/cm	ASTM 882
Elongation	\geq 100%	ASTM 882
Peel adhesion(24hrs)	\geq 1,500g/in	180 peeling PSTC-1
Application temp.	\geq 10°C	18 to 25°C optimum, on clean substrate
Gloss : LD3911G	60 \uparrow	@60, in Machine Direction
Gloss : LD3911M	20 \downarrow	(ASTM D 2457)
Dimensional Stability	Max 0.5mm	Adhered to Aluminum Plate, Length Direction (100°C Oven, 2hr , Average)
Release liner thickness	0.14mm \pm 10%	Micrometer