PANTUM
The New Era for Printing

Offer eco-friendly and affordable prints whenever you need it

Start a worry-less printing with the new Pantum P3010 series today that has extremely low paper jam rate and highly budget-saving and more eco-friendly separate drum unit and toner cartridge. It is designed for users from SMB to large workgroup requiring easy-to-use and cost-effective office tools for their rapidly growing business.

Silent printing mode to lower the noise and create a comfortable office environment

One-Step driver installation and direct printing

Lowpaper jam rate design for engine

Convenient to print

Office document direct print from mobile devices

High print speed

Separate drum and toner

mopria

WiFi and print from mobile device available for P3010DW

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS

P3010 Series
Monochrome Laser Printer

MODEL	■ P3010D	■ P3010DW

PRINTING

Print technology	Mono laser	
Print speed	30ppm(A4)/32ppm(Letter)	
First print out time	Less than 7.8 seconds	
Maximum Monthly Duty Cycle	60000 pages	
Recommended monthly volume	750 to 3500 pages	
Processor speed	350 MHz	
Memory	128 MB	
Resolution(dpi)	1200x1200 dpi (Max)	
Printer language	GDI	
Duplex mode	Auto	
Control panel	LED	2Line LCD
NFC print	No	Yes
Network print	No	Yes
Wireless print	No	Yes

PAPER HANDLING

Paper input tray	250 pages	
Multipurpose tray	1 pages	
Paper output tray	150 pages	
Media types	Plain, Thick, Transparency, Cardstock, Lable, Envelope	
Media sizes	A4, A5, JISB5, Is0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2	
Media weight	Input tray: 60-105g/ m² Multipurpose tray: 60-200g/ m²	

GENERAL

Dimensions (WxDxH)	354 x334x 218mm(13.9x 13.1x8.6in)	354 x334x 232mm(13.9x 13.1x9.1in)
Weight (with toner cartridge)	6.8kg (15lb)	
Operating temperature range Operating humidity range	10-32℃ (50-95°F) 20% - 80% RH	
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%,+10%), 50/60Hz(±2Hz), 4.5A	
Noise	Printing: ≦52dB(A) Standby: ≦30dB(A)	
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2 W	
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04);	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04); iOS 7.0 and above Android 4.4 and above
Interface	High-speedUSB2.0	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

SUPPLIES

Cartridge style	Separate drum and toner	
Starter cartridge capacity[1]	TL-410E (1000 pages)	
Cartridge and drum capacity[1]	Cartridge: TL-410 (1500 pages, Standard); TL-410H (3000 pages, High); TL- 410X (6000 pages , Extra high) Drum: DL-410 (12000pages)	
Starter drum unit lifetime[1] (Print with A4 paper page by page discontinuously)	DL-410E (9000 pages)	

WHAT'S IN THE BOX

Pinter×1/ 1000 Page Toner Cartridge×1/ 9000 Page Drum unit×1/ USB Interface Cable×1/
Power Cord×1/ CD-ROM×1/ Quick Setup Guide×1

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)