MANUFACTURER/SUPPLIER:

TECHNICAL CONCEPTS INTERNATIONAL LIMITED THE NEUTRALLE CENTRE PIN GREEN BUSINESS PARK EASTMAN WAY, STEVENAGE, HERTS, SG1 4UH

MATERIAL SAFETY DATA SHEET

ACCORDING TO 91/155/EC (as amended 2001/58/EC) ISSUING DATE: December 2003

SECTION 1 - IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Product Details.

Trade Name: **Technical Concepts**

Neutralle Microburst 3000 metered aerosols

Tranquil Sense. Fragrance:

Use: Fragranced metered aerosol space sprays designed for use in proprietary automated

dispensers.

Supplier: Technical Concepts International Ltd.,

> The Neutralle Centre Pin Green Business Park

Eastman Way, Stevenage, Herts, SG1 4UH

Tel: +44 870 5686824 Fax: +44 1438 311200

Informing Department: Technical Services Department

SECTION 2 - COMPOSITION/DATA ON COMPONENTS

Chemical Characterisation

Description: Mixture of organic solvents, perfume and propane/iso-butane (propellant)

Dangerous Components:

	Designation	CAS No.	EC No.	Symbol	R-Phrases	%
	Propan-2-ol	67-63-0	200-661-7	Xi, F	11-36-67	5 - 10
	Ethanol	67-17-5	200-578-6	F	11	10 - 15
2-Propenyl hexanoate						
		123-68-2	204-642-4	T, N	21/22-24-36/37-51/53	< 1
Hexahydro-hexamethyl-cyclopenta-benzopyran						
		1222-05-5	214-946-9	N	50/53	< 1
	Hexyl Cinnamal	101-86-0	202-983-3	Xi	43	< 1

Additional information For the wording of the listed risk phrases refer to section 16.

SECTION 3 - HAZARDS IDENTIFICATION

Hazard Designation: F+ Extremely flammable

Information pertaining to particular

dangers for man and environment: R12 Extremely flammable

> R52/53 Harmful to aquatic organisms, may cause long-term adverse effects

> > in the aquatic environment

Classification System The classification is in line with current EC lists. It is expanded, however, by information

from technical literature and by information furnished by supplier companies.

SECTION 4 - FIRST AID MEASURES

After inhalation Supply fresh air, consult a doctor if symptoms develop.

After skin contact Remove soaked clothing and launder before reuse. Wash skin with water and soap.

If symptoms develop or persist, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

After swallowing Rinse mouth. DO NOT INDUCE VOMITING. Consult a doctor.

SECTION 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Agents: CO₂, extinguishing powder or alcohol-resistant foam.

For safety reasons unsuitable

extinguishing agents:

Water jet.

Special hazards caused by the material, its products of

combustion or flue gases: In case of fire CO may be possible.

Protective Equipment: Wear protective clothing/equipment when fighting fires

CECCETON C A COMPONENT DELETAGE MELAGENERG

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

Measures for environmental

protection: No special measures required.

Measures for cleaning/collecting: Ensure adequate ventilation. Absorb liquid components with

liquid binding material (sand, diatomite, acid binders, universal binders,

sawdust).

SECTION 7 - HANDLING AND STORAGE

Handling

Information for safe handling: Ensure good ventilation/exhaustion at the workplace.

Information about protection B

Keep ignition sources away - Do not smoke.

against explosions and fires:

Beware: Container is pressurised. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or

throw into fire, even after use.

Do not spray on flames or red-hot objects

Storage

Requirements to be met by

Store in cool location

storerooms and containers:

Observe official regulations on storing packagings with

pressurised containers.

Information about storage in one

common storage facility: Do not store together with strong acids and strong oxidising agents.

Further information about

storage conditions: Protect from heat and direct sunlight.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Additional information about

design of technical systems: No further data; see item 7.

Components with critical values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the

workplace.

Additional information:

OEL - Values: EH40(2002)

> Ethanol **OES** 8hr TWA - $1000 \text{ ppm} (1920 \text{ mg/m}^3)$ Isopropanol **OES** 8hr TWA -400 ppm (999 mg/m³)

500 ppm (1250 mg/m³) 15min STEL

Propane Listed as an asphyxiant with no limit set

Personal protective equipment

General protective and hygienic

measures: Wash hands during breaks and at the end of the work.

Breathing equipment: Not required, but ensure adequate ventilation when using the product.

Protection of hands: Not required when used as directed.

Eye protection: Not required when used as directed.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form: Aerosol

Colour: According to Product specification.

Smell: Perfume

> Value/Range Unit Method

Change in condition

Melting point/Melting range: Not applicable, as aerosol

Boiling point/Boiling range: Not applicable, as aerosol

Flash point: Not applicable, as aerosol

Self-flammability: Product is not self-igniting.

Danger of explosion: Product is not explosive. However, formation of explosive

air/steam mixtures is possible.

Critical values for explosion:

Lower: 1.8 Vol % 19.0 Vol % Upper:

Vapour pressure: at 20°C $4.0~\pm~0.5$ bar

Density: at 20°C 0.619 - 0.645 g/cm³

Solubility in/Miscibility with

Water: Partly miscible **SECTION 10 - STABILITY AND REACTIVITY**

Thermal decomposition/

conditions to be avoided: No decomposition if used according to instructions.

Dangerous reactions: No dangerous reactions known.

Materials to be avoided: Oxidising agents and strong acids.

Dangerous products of

decomposition: In case of fire CO may be possible.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute toxicity:

Primary irritant effect:

On the skin: Irritation may be possible.

On the eye: Irritation may be possible.

SECTION 12 - ECOLOGICAL INFORMATION

General notes: Water hazard class 1 (Self-assessment): slightly hazardous for

Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13 - DISPOSAL CONSIDERATIONS

Product:

Recommendation: Disposal must be made according to local regulations or via a licensed waste

contractor.

Uncleaned packagings:

Recommendation: Disposal must be made according to local regulations or via a licensed waste

contractor.

SECTION 14 - TRANSPORT INFORMATION

Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)

ADR/RID Class: UN Number: 1950

Correct technical name: Aerosols (Flammable) Label: Diamond shaped, framed

UN 1950 AEROSOLS should be placed inside the diamond shaped label. Remarks:

Goods are classed as "Limited Quantities" and are therefore exempt from ADR

regulations. Check local local legislation for domestic transport.

Maritime transport IMDG/GGVSea

IMDG/GGVSea Class: UN Number: 1950 EMS Number: F-D. S-U **Marine Pollutant** No Correct technical name: Aerosols

Remarks "Limited Quantity"

AEROSOLS is required according to IMDG regulations

Air transport ICAO-TI and IATA-DGR

ICAO/IATA Class: 2.1 **UN/ID Number:** 1950

Correct Technical Name: Aerosols, flammable Remarks: "Limited Quantity"

SECTION 15 - REGULATORY INFORMATION

Designation according to EC

Guidelines:

The product has been labelled in accordance with

EC Directives/relevant national laws.

For professional use only

Code letter and hazard

designation of product: F+ Extremely flammable.

Risk phrases: 12 Extremely flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment

Safety phrases: 2 Keep out of reach of children.

16 Keep away from sources of ignition - No smoking.

23 Do not breathe spray.

51 Use only in well-ventilated areas.

Special label phrase: Contains Hexyl Cinnamal. May cause an allergic reaction.

National regulations:

Special designation of certain preparations:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

SECTION 16 - OTHER INFORMATION

R-phrases used in document:

R11

1111	Triging transmittee
R12	Extremely flammable
R21/22	Harmful in contact with skin and if swallowed
R24	Toxic in contact with skin
R36	Irritating to eyes
R36/37	Irritating to eyes and respiratory system
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R67	Vapours may cause drowsiness and dizziness

This data is based on our present knowledge. However, it shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing data specification sheet: Technical Services Department.

Contact: Mr. K. Anderson

Highly flammable

Sources: Raw material Safety Data sheets

EH40/2002 Occupational Exposure limits (UK)

Revision data: Rev.7

Rev.7 – Changes to section 14 (marked |).

Rev.6 - Changes to Section 2 and 15

Rev.5 - Changes to Section 2

 $Rev.4\,$ - Compliance to CHIP 3 and the 2001/58/EC amendments to 91/155/ECC

Print Date: