Page 1 of 5 MSDS No.: TK540Y-KME-03



MATERIAL SAFETY DATA SHEET

Date/ Revision: December 17, 2009

1. PRODUCT AND COMPANY IDENTIFICATION			
Product Name	: Yellow Toner for FS-C5100DN		
Manufacturer			
Name	: KYOCERA MITA CORPORATION		
Address	: 2-28, 1-Chome, Tamatsukuri, Chuo-ku, Osaka, Japan, 540-8585		
Supplier			
Name	: KYOCERA MITA Europe B.V		
Address	: Hoeksteen 40, 2132 MS Hoofddorp, Netherlands		
Telephone Number	: +31(0)20-6540000		

2. COMPOSITION/ INFORMATION ON INGREDIENTS

Substance or preparation ; Preparation

Ingredients;

Chemical Name(Common Name)	CAS No.	Weight %
Polyester resin 1	Confidential	70-80
Polyester resin 2	Confidential	5-10
Organic pigment	Confidential	1-5
Styrene acrylate copolymer	Confidential	1-5
Amorphous silica	7631-86-9	1-5

3. HAZARDS IDENTIFICATION

Most Important Hazards	: Not classified as dangerous.(1999/45/EC)
Specific Hazards	: None
Other Information on Haz	zards : Potential Health Effects
Ingestion	: Ingestion is not applicable route of entry for intended use.
Inhalation	: Prolonged inhalation of excessive dusts may cause lung damage. Use of this product, as intended, does not result in inhalation of
	excessive dusts.
Eye Contact	: May cause eye irritation.
Skin Contact	: Unlikely to cause skin irritation.

Page 2 of 5 MSDS No.: TK540Y-KME-03

4. FIRST-AID MEASURES		
Inhalation	: Remove from exposure to fresh air and gargle with plenty of water.	
	Consult a doctor in case of such a symptoms as coughing.	
Skin Contact	: Wash with soap and water.	
Eye Contact	: Flush with water immediately and see a doctor if irritating.	
Ingestion	: Rinse out the mouth. Drink one or two glasses of water to dilute.	
	Seek medical treatment if necessary.	

5. FIRE-FIGHTING MEASURES

Extinguishing Media	: Water (Sprinkle with Water), Foam, Powder, CO ₂ or	
	Dry Chemical Extinguisher	
Fire-Fighting Procedure : Pay attention not to blow away toner powder. Drain water off		
	around and decrease the atmosphere temperature to	
	extinguish the fire.	

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	: Avoid inhalation, ingestion, eye and skin contact in case of
	accidental toner release.
Environmental Precautions	: No special precaution
Method for Cleaning Up	: Gather the released toner not to blowing away and wipe up with a wet cloth.

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters <reference data="">:</reference>		
ACGIH TLV(2008)-TV	VA : Inhalable fraction 10mg/m ³ , Respirable fraction 3mg/m ³	
OSHA PEL(2006)-TWA : Total dust 15mg/m ³ , Respirable fraction 5mg/m ³		
	Silica 80mg/m ³ /%SiO ₂	
Protective Equipment	: Respiratory protection, eye protection, hand protection, skin and	
	body protection are not required under normal use.	
Ventilation	: Ventilator is not required under normal use.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

	Physical state: Solid	Form: Fine powder	Color: Yellow	Odor: Odorless
рН	: N.A.			

Page 3 of 5 MSDS No.: TK540Y-KME-03

Melting Point	: 100-120 °C
Explosion Properties	: Dust explosion is improbable under normal use.
	Experimental explosiveness of toner is classified into the same
	rank such kind of powder as flour, dry milk and resin powder
	according to the pressure rising speed.
Density	: 1.2-1.4 g/cm ³
Solubility	: Almost insoluble in water

10. STABILITY AND REACTIVITY

Stability/ Reactivity	: Stable under normal use.
Hazardous Decomposition Products	: None

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: (rat)LD ₅₀ >2,000mg/kg
	(Estimated from other products containing same materials.)
Acute dermal toxicity	: (rat)LD ₅₀ >2,000mg/kg
	(Estimated from Acute oral toxicity for same product.)
Acute inhalation toxicity	: (rat)LC ₅₀ (4hr)>5.02mg/l (Estimated from other products containing same materials.)
Acute eye irritation	: (rabbit)Minimal irritant
,	(Estimated from other products containing same materials.)
Acute skin irritation	: (rabbit)Mild irritant
	(Estimated from other products containing same materials.)
Skin sensitization	: (mouse)Non-Sensitiser
	(Estimated from other products containing same materials.)
Mutagenicity	: Ames Test is Negative.
Reproductive Toxicity	: No reproductive toxicant, according to MAK, California
	Proposition 65, TRGS905 and EU Directive(67/548/EEC).
Carcinogenicity	: No carcinogen or potential carcinogen, according to IARC,
	Japan Association on Industrial Health, ACGIH, EPA, OSHA, NTP,
	ILO, MAK, California Proposition 65, TRGS 905 and
	EU Directive(67/548/EEC).

Chronic effects:

In a study in rats by chronic inhalation exposure to a typical toner, a mild to moderate degree of lung fibrosis was observed in 92% of the rats in the high concentration(16mg/m³) exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animal in the middle(4mg/m³) exposure group. But no pulmonary change was reported in the lowest(1mg/m³) exposure group, the most relevant level to potential human exposures. Other information : None

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Do not incinerate toner and toner containers. Dangerous sparks may cause burn.

Any disposal practice should be done under conditions which meet local, state and federal laws and regulations relating to waste (contact local or state environmental agency for specific rules).

14. TRANSPORT INFORMATION

UN No. : None

UN Shipping Name : None

UN Classification : None

UN Packing Group : None

Special Precautions : None

15. REGULATORY INFORMATION

EU Information

Label information according to the Directives 67/548/EEC and 1999/45/EEC.

Symbol and Indication	: Not required
R-Phrase	: Not required
S-Phrase	: Not required
Special markings	: Not required
Hazardous ingredients for labeling: None	

US Information

All components in this product comply with order under TSCA.

16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate.

However, we cannot assume any liability whatsoever for the accuracy or completeness of the information contained herein.

<Abbreviation>

ACGIH	: American Conference of Governmental Industrial Hygienists
PEL	: Permissible Exposure Limit

OSHA : Occupational Safety and Health Administration

Page 5 of 5 MSDS No.: TK540Y-KME-03

- TLV : Threshold Limit Value
- TWA : Time Weighted Average
- MAK : MAK(Maximale Arbeitsplatzkonzentrationen) under Deutsche Forschungsgemeinschaft
- TRGS : Technische Regeln für Gefahrstoffe(Deutsche)
- IARC : International Agency for Research on Cancer
- EPA : Environmental Protection Agency(USA)
- NTP : National Toxicology Program
- ILO : International Labour Office
- UN : Nnited Nations
- TSCA : Toxic Substances Control Act(USA)

<Reference>

- ISO 11014-1 Safety data sheet for chemical products
- Commission Directive 91/155/EEC and 2001/58/EC
- Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats H.Muhle et.al
 - Fundamental and Applied Toxicology 17.280-299(1991)
- Lung Clearance and Retention of Toner, Utilizing a Tracer Technique, during Chronic Inhalation Exposure in Rats
 B.Bellmann
 - Fundamental and Applied Toxicology 17.300-313(1991)