

1.0 Product and Company Identification			
Identification of the p Company Identificati		HP Color LaserJ Cartridge C9731 Hewlett-Packard Cor 11311 Chinden Bould Boise, Idaho 83714 United States	A mpany
Emergency telephon Hewlett-Packard Hea		1-800-457-4209 (US Intl: +1-503-494-7199 Singapore: +001-800	9 (all other areas)
General information telephone number		1-208-323-2551 (USA and Canada) Intl: +1-208-323-2551 (all other areas)	
Local Contact Information			
Local Contact Inform	ation	Ireland Liffey Park Technolo Barnhall Road Leixlin Kildare, Ireland Phone: 01 6150000 United Kingdom Hewlett-Packard, Ltd Cain Road, Amen Co Bracknell, Berkshire, Phone: 1344 36-000	b, Co. I. prner RG12 1HN
Local Contact Inform	hation Hazard Rating	Liffey Park Technolo Barnhall Road Leixlip Kildare, Ireland Phone: 01 6150000 United Kingdom Hewlett-Packard, Ltd Cain Road, Amen Co Bracknell, Berkshire,	b, Co. I. prner RG12 1HN
Local Contact Inform		Liffey Park Technolo Barnhall Road Leixlip Kildare, Ireland Phone: 01 6150000 United Kingdom Hewlett-Packard, Ltd Cain Road, Amen Co Bracknell, Berkshire, Phone: 1344 36-000	b, Co. I. prner RG12 1HN
Local Contact Inform	Hazard Rating Health Flammability	Liffey Park Technolo Barnhall Road Leixlip Kildare, Ireland Phone: 01 6150000 United Kingdom Hewlett-Packard, Ltd Cain Road, Amen Co Bracknell, Berkshire, Phone: 1344 36-000 US NFPA/HMIS 1 1	b, Co. I. prner RG12 1HN
Local Contact Inform	Hazard Rating Health	Liffey Park Technolo Barnhall Road Leixlip Kildare, Ireland Phone: 01 6150000 United Kingdom Hewlett-Packard, Ltd Cain Road, Amen Co Bracknell, Berkshire, Phone: 1344 36-000 US NFPA/HMIS 1	b, Co. I. prner RG12 1HN

2.0 Composition/Information on Ingredients

This product is a cyan toner preparation that is used in Hewlett-Packard Color LaserJet 5500 and 5550 series printers.

Component/Substance	CAS Number	EU Number	% by Weight	Risk
				Phrases
Styrene Acrylate	-	-	75 - 85	-
Copolymer				
Wax	-	-	5 - 10	-
Copper Compound	-	-	1 – 5	-
			(as Cu: 0.1-0.5)	
Amorphous Silica	7631-86-9	231-545-4	1-2	-



3.0 Hazard Identification

This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, and as amended.

Routes of Exposure	Inhalation, Ingestion, skin and eyes.
Acute Health Hazards	
Inhalation:	Respiratory tract irritation may occur with exposure to large amounts of dust.
Ingestion:	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.
Skin:	Unlikely to cause skin irritation.
Eyes:	May cause transient slight irritation.
Chronic Health Hazards	Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this product as intended does not result in inhalation of excessive amounts of dust.
Carcinogenicity	Refer to section 11.

4.0 First Aid Measures

Inhalation:	Move person to fresh air immediately. If symptoms occur, consult a physician.
Ingestion:	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician immediately.
Skin:	Wash affected areas with soap and water. If irritation persists, consult a physician.
Eyes:	Do not rub eyes. Immediately flush with large amounts of clean, lukewarm water (low pressure) for at least 5 minutes or until particles are removed. If irritation persists, consult a physician.

5.0 Fire Fighting Measures

Extinguishing media	CO ₂ , water, dry chemical
Unsuitable Extinguishing Media	None
Special Firefighting Procedures	None
•	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
Auto-ignition temperature	Not available
Flashpoint (method)	Not applicable



Products

6.0 Accidental release measures		
Spill or leak procedures Environmental precautions	Avoid breathing dust. Minimize the release of particles. Slowly sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of waste toner in accordance with local requirements. Do not discharge into drains (See also Section 13, Disposal Considerations).	
7.0 Handling and Storage		
Advice on safe handling and protection against fire	Keep material out of reach of children. Avoid inhalation of dust and contact with eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.	
Requirements for storage rooms and advise on storage compatibility	Keep out of the reach of children. Keep container closed and store at room temperature. Keep away from strong oxidizers.	
8.0 Exposure control/ perso	onal protection	
Exposure Limit Values USA OSHA (TWA/PEL): ACGIH (TWA/TLV):	15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable Fraction) 10 mg/m ³ (Inhalable Particulate)	
TRGS 900 (Luftgrenzwert):	3 mg/m ³ (Respirable Particulate) 10 mg/m3 (Einatembare Partikel) 3 mg/m3 (Alveolengängige Fraktion)	
Amorphous Silica	USA OSHA PEL - 20 mppcf, 80(mg/m ³)/% SiO ₂ (TWA); ACGIH TLV - 10 mg/m ³ (TWA)	
Copper compound:	DFG MAK – 1.0 mg/m ³ (Inhalable fraction) Cu and its compounds.	
Exposure Controls Respiratory protection Ventilation	Not required under intended use. Good general ventilation should be sufficient under intended use.	



9.0 Physical and chemical properties

Flash point Melting point	Not applicable Not applicable Not applicable 100 - 150°C (Softening Point) Non-flammable solid (according to test methods of EU Directive 92/69/EEC and as amended, A10 Flammability (Solids))
Explosive properties	Toner material, like most organic material in powder form, is capable of creating a dust explosion.
Oxidizing properties	No data available
Vapor Pressure	Not applicable
Specific gravity (H ₂ O=1)	1.0 - 1.2
Solubility in water	Negligible
Solubility in organic	Partially soluble in toluene and xylene
solvents	
Partition coefficient	Not applicable
Viscosity	Not applicable
Vapor density	Not applicable
Evaporation rate	Not applicable
Physical state	
Color	Cyan
Odor	Slight plastic odor
Other	Decomposition Temperature: >200 ° C

10.0 Stability and reactivity

Stability	Stable under normal storage conditions
Incompatibilities	Strong oxidizers
Hazardous decomposition	CO_2, CO
products	
Hazardous polymerization	Will not occur

11.0 Toxicological information

Refer to Section 3 for potential heath effects and Section 4 for first aid measures

Inhalation:	LC ₅₀ :inh-rat>5mg/L/4 hrs., not harmful.
Ingestion:	LD ₅₀ :orl-rat>2000 mg/kg, not harmful.
Eye Contact:	Not classified as irritant, according to OSHA Hazard
	Communication Standard (HCS) and EU Directive
	67/548/EEC and as amended.
Skin Contact:	Not classified as irritant, according to OSHA Hazard
	Communication Standard (HCS) and EU Directive
	67/548/EEC and as amended.
Chronic Toxicity:	No data available



Sensitization:	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).
Mutagenicity:	Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)
Carcinogenicity:	Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations (USA), EU Directive, or Proposition 65 (California).
Reproductive Toxicity:	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, or DFG (Germany).

12.0 Ecological Information

No data available for ecological and wastewater treatment (sewage) systems. Avoid spills and dispose of in accordance with applicable laws and regulations.

13.0 Disposal considerations

Do not put toner or print cartridge into fire; heated toner may cause severe burns. Do not shred print cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

14.0 Transportation information

Not a regulated article under DOT, IATA, ADR, or RID

UN Number	None
Class	None
Proper Shipping Name	None
Packing Group	None
Special Precautions	None

15.0 Regulatory information

US EPA TSCA Inventory	All chemical substances in this product comply with all rules or orders under TSCA.
US EPA TSCA 12(b)	Contains p-Xylene - [CAS No. 106-42-3]
US California Proposition 65	None
EU Notification	All components in this product are compliant with EU Chemical Inventory regulations.
EU Hazard Label	This product does not require a label under
(1999/45/EC):	1999/45/EC and as amended.
Special Precautions under	None
1999/45/EC, Annex V	
USA Labeling	
Symbol	Not required



Hazard Warning Not required Safety Advice Not required Hazardous Component(s) None

16.0 Other information

Date Prepared:	September 1, 2004
HP-DMS Document Control	09000de780237e72
Number:	
Revision Information:	This MSDS replaces all prior versions
EU & US Information	This MSDS was prepared in compliance with EU
	Directive 91/155/EEC as amended by 2001/58/EC and
	USA OSHA Hazard Communications regulations
	(29CFR1910:1200).

DISCLAIMER: This Material Safety Data Sheet (MSDS) is provided without charge to customers of Hewlett-Packard. Data is the most current known to Hewlett-Packard at the time of preparation of this MSDS and is believed to be accurate. It should not be construed as guaranteeing specific properties of the product as described or its suitability for a particular application.