

1.0 Product and Company Identification			
Identification of the preparation Company Identification		HP Color LaserJet Yellow Print Cartridge C9722A Hewlett-Packard Company 11311 Chinden Boulevard Boise, Idaho 83714 United States	
Emergency telephone Hewlett-Packard Hea		1-800-457-4209 (US Intl: +1-503-494-719 Singapore: +001-800	9 (all other areas)
General information telephone number		1-208-323-2551 (USA and Canada) Intl: +1-208-323-2551 (all other areas)	
Local Contact Information		Ireland Liffey Park Technolo Barnhall Road, Leixlip, Co. Kildare Phone: 01 6150000 United Kingdom Hewlett-Packard, Lto Cain Road, Amen Co Bracknell, Berkshire, Phone: 1344 36-000	I. orner RG12 1HN
	Hazard Rating	US NFPA/HMIS	
	Health	1	
	Flammability	1	
	Instability/Reactivity	0	
	Special	N/A	
2.0 Composition/Ir	nformation on Ingred	lients	

This product is a yellow toner preparation that is used in Hewlett-Packard Color LaserJet 4600, and 4650 series printers.

Component/Substance	CAS Number	EU Number	% by Weight	Risk
				Phrases
Styrene acrylate copolymer	-	-	75 - 85	-
Wax	-	-	5 - 10	-
Pigment	-	-	1 – 5	-



3.0 Hazard Identification

This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, and as amended.

Routes of Exposure	Inhalation, Ingestion, skin and eyes.
Acute Health Hazards	
Inhalation:	Respiratory tract irritation may occur with exposure to large amounts of dust.
Ingestion:	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.
Skin:	Unlikely to cause skin irritation.
Eyes:	May cause transient slight irritation.
Chronic Health Hazards	Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this product as intended does not result in inhalation of excessive amounts of dust.
Carcinogenicity	Refer to section 11.

4.0 First Aid Measures

Inhalation:	Move person to fresh air immediately. If symptoms occur, consult a physician.
Ingestion:	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician immediately.
Skin:	Wash affected areas with soap and water. If irritation persists, consult a physician.
Eyes:	Do not rub eyes. Immediately flush with large amounts of clean, lukewarm water (low pressure) for at least 5 minutes or until particles are removed. If irritation persists, consult a physician.

5.0 Fire Fighting Measures

Extinguishing media	CO ₂ , water, dry chemical
Unsuitable Extinguishing Media	None
Special Firefighting Procedures	None
•	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
Auto-ignition temperature Flashpoint (method)	Not available



Hazardous Combustion

Products CO₂, CO

6.0 Accidental release measures		
Spill or leak procedures Environmental precautions	Avoid breathing dust. Minimize the release of particles. Slowly sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of waste toner in accordance with local requirements. Do not discharge into drains (See also Section 13, Disposal Considerations).	
7.0 Handling and Storage		
Advise on safe handling and protection against fire	Keep material out of reach of children. Avoid inhalation of dust and contact with eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.	
Requirements for storage rooms and advise on storage compatibility	Keep out of the reach of children. Keep container closed and store at room temperature. Keep away from strong oxidizers.	
8.0 Exposure control/ perso	onal protection	
Exposure Limit Values USA OSHA (TWA/PEL): ACGIH (TWA/TLV):	15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable Fraction) 10 mg/m ³ (Inhalable Particulate) 3 mg/m ³ (Respirable Particulate)	
DFG (Luftgrenzwert):	4 mg/m3 (Einatembare Partikel)	
Exposure Controls Respiratory protection Ventilation	1.5 mg/m3 (Alveolengängige Fraktion)Not required under intended use.Good general ventilation should be sufficient under intended use.	
Protective gloves Eye protection Other protective equipment	Not required under intended use. Not required under intended use. Not required under intended use.	

9.0 Physical and chemical properties

pHNot applicableBoiling pointNot applicableFlash pointNot applicable



Melting point	100 - 150°C (Softening Point)
Flammability	Non-flammable solid (according to test methods of
-	EU Directive 92/69/EEC and as amended, A10
	Flammability (Solids).
Explosive properties	Toner material, like most organic material in powder
p	form, is capable of creating a dust explosion.
Oxidizing properties	· · · ·
Vapor Pressure	
Specific gravity (H ₂ O=1)	••
Solubility in water	
Solubility in organic	regligible
solvents	Partially soluble in toluene and xylene.
Partition coefficient	,
	11
Viscosity	
Vapor density	••
Evaporation rate	
Physical state	•
Color	5
Odor	Slight plastic odor
Other	Decomposition Temperature: >200 ° C

10.0 Stability and reactivity

Stability	Stable under normal storage conditions
Incompatibilities	Strong oxidizers
Hazardous decomposition	
products	CO ₂ , CO
Hazardous polymerization	Will not occur

11.0 Toxicological information

Refer to Section 3 for potential heath effects and Section 4 for first aid measures

	LC ₅₀ :inh-rat>5mg/L/4 hrs., not harmful. LD ₅₀ :orl-rat>2000 mg/kg, not harmful.
Eye Contact:	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.
Skin Contact:	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.
Chronic Toxicity:	No data available.
Sensitization:	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).
Mutagenicity:	Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)



Carcinogenicity: Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations (USA), EU Directive, or Proposition 65 (California).
Reproductive Toxicity: Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, or DFG (Germany).

12.0 Ecological Information

No data available for ecological and wastewater treatment (sewage) systems. Avoid spills and dispose of in accordance with applicable laws and regulations.

13.0 Disposal considerations

Do not put toner or print cartridge into fire; heated toner may cause severe burns. Do not shred print cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulation.

14.0 Transportation information

Not a regulated article under DOT, IATA, ADR, or RID

UN Number	None
Class	None
Proper Shipping Name	None
Packing Group	None
Special Precautions	None

15.0 Regulatory information

US EPA TSCA	All chemical substances in this product comply with all rules and orders under TSCA.
US EPA TSCA 12(b)	Contains p-Xylene - [CAS No. 106-42-3]
US California Proposition 65	None
EU Notification	All components in this product are compliant with EU Chemical Inventory regulations.
EU Hazard Label	This product does not require a label under
(1999/45/EC)	1999/45/EC and as amended.
Special Precautions under	
1999/45/EC, Annex V	None
USA Labeling	
Symbol	Not required
Hazard Warning	Not required
Safety Advice	Not required
Hazardous Component(s)	None



16.0 Other information

Date Prepared:	July 1, 2004
HP-DMS Document Control	-
Number:	
Revision Information:	
ELL & LIS Information	

EU & US Information This MSDS was prepared in compliance with EU Directive 91/155/EEC as amended by 2001/58/EC and USA OSHA Hazard Communications regulations (29CFR1910:1200).

DISCLAIMER: This Material Safety Data Sheet (MSDS) is provided without charge to customers of Hewlett-Packard. Data is the most current known to Hewlett-Packard at the time of preparation of this MSDS and is believed to be accurate. It should not be construed as guaranteeing specific properties of the product as described or its suitability for a particular application.