

COLOR COPY



Substance g/m ²	90	100	120	160	200	250	280	300	350
Caliper μm (approx)	95	106	126	165	200	250	275	318	365
Opacity (ISO) %	90	92	95	98	99				
Brightness (ISO) D65	110	110	110	110	110	110	110	110	110
Whiteness CIE D65	157	157	157	157	157	157	157	157	157
Smoothness (Bendtsen) ml/min TS	30	30	30	30	30	30	30	40	40
Smoothness (Bendtsen) ml/min WS	30	30	30	30	30	30	30	40	40
Rigidity (Taber Stiffness Units) 15° MD	3	3.5	6.3	16.5	25.5	45.5	70	74	97
Rigidity (Taber Stiffness Units) 15° CD	1.5	2	3.3	8.5	14	25	40	42	45
Surface pH	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5

Technical Capability

Copier Guaranteed	Mono and colour
Laser Guaranteed	Mono and colour
Plain Paper Fax	90 and 100 g/m ²
Toy Safety	Yes, complies with EN71 Part 3 Toy Safety Regulations
Permanence of Paper	Yes, meets ISO9706 requirements for Permanence of Paper
Additional Information	This grade is not designed for pre-printing.

Environmental Information

Fibre Source	Virgin wood fibre from South Africa, South America, Scandinavia and Europe
Bleaching	Pulp is bleached using an Elemental Chlorine Free (ECF) process.
Disposal	This material can be disposed of by recycling and incineration for energy.
Accreditation	Produced at a mill that is certified to the ISO14001 environmental management standard. FSC Mixed Sources - Product group from well managed forests and other controlled sources

The Robert Horne Group is committed to the responsible purchasing of paper products. This commitment will be realised through a stepwise approach to responsible purchasing that utilises the best available techniques and information. Robert Horne requires its suppliers to abide by all local, state and national laws and international conventions. For further information and full Responsible Paper Purchasing Policy, visit: <http://www.roberthorne.co.uk/enviroment>