MSDS No.: TK540K-KME-03



# MATERIAL SAFETY DATA SHEET

Date/ Revision: December 17, 2009

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name : Black Toner for FS-C5100DN

Manufacturer

Name : KYOCERA MITA CORPORATION

Address : 2-28, 1-Chome, Tamatsukuri, Chuo-ku, Osaka, Japan, 540-8585

Supplier

Name : KYOCERA MITA Europe B.V

Address : Hoeksteen 40, 2132 MS Hoofddorp, Netherlands

Telephone Number : +31(0)20-6540000

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance or preparation; Preparation

Ingredients;

Chemical Name(Common Name)	CAS No.	Weight %
Polyester resin	Confidential	70-80
Carbon black	1333-86-4	5-10
Styrene acrylate copolymer	Confidential	1-5
Wax	Confidential	1-5
Amorphous silica	7631-86-9	1-5

# 3. HAZARDS IDENTIFICATION

Most Important Hazards : Not classified as dangerous.(1999/45/EC)

Specific Hazards : None

Other Information on Hazards : Potential Health Effects

Ingestion : Ingestion is not applicable route of entry for intended use.

Inhalation : Prolonged inhalation of excessive dusts may cause lung damage.

Use of this product, as intended, does not result in inhalation of

excessive dusts.

Eye Contact : May cause eye irritation.

Skin Contact : Unlikely to cause skin irritation.

MSDS No.: TK540K-KME-03

### 4. FIRST-AID MEASURES

Inhalation : Remove from exposure to fresh air and gargle with plenty of water.

Consult a doctor in case of such a symptoms as coughing.

Skin Contact : Wash with soap and water.

Eye Contact : Flush with water immediately and see a doctor if irritating.

Ingestion : Rinse out the mouth. Drink one or two glasses of water to dilute.

Seek medical treatment if necessary.

# 5. FIRE-FIGHTING MEASURES

Extinguishing Media : Water (Sprinkle with Water), Foam, Powder, CO<sub>2</sub> or

Dry Chemical Extinguisher

Fire-Fighting Procedure: Pay attention not to blow away toner powder. Drain water off

around and decrease the atmosphere temperature to

extinguish the fire.

# **6. ACCIDENTAL RELEASE MEASURES**

Personal Precautions : Avoid inhalation, ingestion, eye and skin contact in case of

accidental toner release.

Environmental Precautions : No special precaution.

Method for Cleaning Up : Gather the released toner not to blowing away and

wipe up with a wet cloth.

# 7. HANDLING AND STORAGE

Handling: Never open the toner container.

Storage : Keep the toner container tightly closed and store in a cool, dry and

dark place keeping away from fire.

Keep away from children.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters<Reference Data>:

ACGIH TLV(2008)-TWA: Inhalable fraction 10mg/m<sup>3</sup>, Respirable fraction 3mg/m<sup>3</sup>

Carbon black 3.5mg/m<sup>3</sup>

OSHA PEL(2006)-TWA: Total dust 15mg/m<sup>3</sup>, Respirable fraction 5mg/m<sup>3</sup>

Carbon black 3.5mg/m<sup>3</sup> Silica 80mg/m<sup>3</sup>/%SiO<sub>2</sub>

Protective Equipment : Respiratory protection, eye protection, hand protection, skin and

body protection are not required under normal use.

Ventilation : Ventilator is not required under normal use.

Page 3 of 5

MSDS No.: TK540K-KME-03

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state: Solid Form: Fine powder Color: Black Odor: Odorless

pH : N.A.

Melting Point : 100-120 °C

Explosion Properties : Dust explosion is improbable under normal use.

Experimental explosiveness of toner is classified into the same rank such kind of powder as flour, dry milk and resin powder

according to the pressure rising speed.

Density : 1.2-1.4 g/cm<sup>3</sup>

Solubility : Almost insoluble in water

# 10. STABILITY AND REACTIVITY

Stability/ Reactivity : Stable under normal use.

Hazardous Decomposition Products : None

# 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : (rat)LD<sub>50</sub>>2,000mg/kg

(Estimated from other products containing same materials.)

Acute dermal toxicity : (rat)LD<sub>50</sub>>2,000mg/kg

(Estimated from Acute oral toxicity for same product.)

Acute inhalation toxicity: (rat)LC<sub>50</sub>(4hr)>5.02mg/l

(Estimated from other products containing same materials.)

Acute eye irritation : (rabbit)Minimal irritant

(Estimated from other products containing same materials.)

Acute skin irritation : (rabbit)Mild irritant

(Estimated from other products containing same materials.)

Skin sensitization : (mouse)Non-Sensitiser

(Estimated from other products containing same materials.)

Mutagenicity : Ames Test is Negative.

(Estimated from the data of constituent materials.)

Reproductive Toxicity : No reproductive toxicant, according to MAK, California

Proposition 65, TRGS905 and EU Directive(67/548/EEC).

Carcinogenicity: No carcinogen or potential carcinogen(except carbon black),

according to IARC, Japan Association on Industrial Health, ACGIH, EPA, OSHA, NTP, ILO, MAK, California Proposition 65, TRGS 905

and EU Directive(67/548/EEC).

In 1996, the IARC reevaluated carbon black as a Group2B carcinogen(possible human carcinogen). This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the development of lung

MSDS No.: TK540K-KME-03

tumors in rat recieving chronic inhalation exposures to free carbon black at level that induce particle overload of the lung.

Studies performed in animal models other than rats have not demonstrated an association between carbon black and lung tumors. Moreover, a two-years cancer bioassay using a typical toner preparation containing carbon black demonstrated no association between toner exposure and tumor development in rats.

#### Chronic effects:

In a study in rats by chronic inhalation exposure to a typical toner, a mild to moderate degree of lung fibrosis was observed in 92% of the rats in the high concentration(16mg/m³) exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animal in the middle(4mg/m³) exposure group. But no pulmonary change was reported in the lowest(1mg/m³) exposure group, the most relevant level to potential human exposures.

Other information : None

# 12. ECOLOGICAL INFORMATION

No data available.

# 13. DISPOSAL CONSIDERATIONS

Do not incinerate toner and toner containers. Dangerous sparks may cause burn.

Any disposal practice should be done under conditions which meet local, state and federal laws and regulations relating to waste (contact local or state environmental agency for specific rules).

### 14. TRANSPORT INFORMATION

UN No. : None
UN Shipping Name : None
UN Classification : None
UN Packing Group : None
Special Precautions : None

# 15. REGULATORY INFORMATION

# **EU Information**

Label information according to the Directives 67/548/EEC and 1999/45/EEC.

Symbol and Indication : Not required R-Phrase : Not required

Page 5 of 5

MSDS No.: TK540K-KME-03

S-Phrase : Not required

Special markings : Not required

Hazardous ingredients for labeling: None

# **US Information**

All components in this product comply with order under TSCA.

# **16. OTHER INFORMATION**

To the best of our knowledge, the information contained herein is accurate.

However, we cannot assume any liability whatsoever for the accuracy or completeness of the information contained herein.

# <Abbreviation>

ACGIH : American Conference of Governmental Industrial Hygienists

PEL : Permissible Exposure Limit

OSHA : Occupational Safety and Health Administration

TLV : Threshold Limit Value
TWA : Time Weighted Average

MAK : MAK(Maximale Arbeitsplatzkonzentrationen) under Deutsche

Forschungsgemeinschaft

TRGS : Technische Regeln für Gefahrstoffe(Deutsche)
IARC : International Agency for Research on Cancer

EPA : Environmental Protection Agency(USA)

NTP : National Toxicology Program
ILO : International Labour Office

UN : Nnited Nations

TSCA : Toxic Substances Control Act(USA)

# <Reference>

- ISO 11014-1 Safety data sheet for chemical products
- Commission Directive 91/155/EEC and 2001/58/EC
- Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats H.Muhle et.al

Fundamental and Applied Toxicology 17.280-299(1991)

 Lung Clearance and Retention of Toner, Utilizing a Tracer Technique, during Chronic Inhalation Exposure in Rats

B.Bellmann

Fundamental and Applied Toxicology 17.300-313(1991)