

Material name	HP Color LaserJet CE251A Cyan Print Cartridge
Use of the preparation	This product is a cyan toner preparation that is used in HP Color LaserJet CP3525 and CM3530 series printers.
Version #	02
Revision date	03-17-2009
CAS #	Mixture
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-1501
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomerinquiries@hp.com
Date prepared	Mar 16, 2009
MSDS number	372154
Hazards Identification	
Acute health effects	
Skin contact	Unlikely to cause skin irritation.
Eye contact	May cause transient slight irritation
Inhalation	Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Use of this product as intended does not result in inhalation of excessive amounts of dust.
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.
Potential health effects	
Routes of exposure	Potential routes of exposure under normal use conditions are skin and eye contact; and inhalation
	Ingestion is not expected to be a primary route of exposure for this product under normal use conditions.
Chronic health effects	Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this product as intended does not result in inhalation of excessive amounts of dust.
Carcinogenicity	None of the ingredients have been classified as carcinogens according to EU, IARC, MAK,

1. Product and Company Identification

Other information

2.

This preparation contains no component classified as Persistent, Bioaccumulative, and Toxic (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC) 1907/2006.

This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU

3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	< 85	
Wax	Trade Secret	< 10	
Pigment	Trade Secret	< 6	

NTP, OSHA or ACGIH.

Directive 1999/45/EC, as amended.



Amorphous silica	7631-86-9 < 2	
. First Aid Measures		
First aid procedures		
Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.	
Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.	
Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.	
Ingestion	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician.	
. Fire Fighting Measures		
Flash point and method	Not applicable	
Hazardous combustion products	Carbon monoxide and carbon dioxide.	
Flammable properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.	
Extinguishing media		
Suitable extinguishing media	CO2, water, or dry chemical	
Unsuitable extinguishing media	None known.	
Unusual fire and explosion hazard	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.	
Protection of firefighters		
Protective equipment and precautions for firefighters	If fire occurs in the printer, treat as an electrical fire.	
Special firefighting procedures	None established.	
. Accidental Release Measures		
Personal precautions	Minimize dust generation and accumulation.	
Environmental precautions	Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.	
Other information	Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.	
. Handling and Storage		
Handling	Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.	
Storage	Keep out of the reach of children. Keep tightly closed and dry. Store away from strong oxidizers. Store at room temperature.	
. Exposure Controls / Personal I	Protection	
Exposure guidelines	USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)	
	ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)	
	Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3	



Personal protective equipment


General

No personal respiratory protective equipment required under normal conditions of use.

hysical & Chemical Properti	ies
Appearance	Fine powder
Color	Cyan
Odor	Slight plastic odor
Odor threshold	Not available.
Physical state	Not available.
Form	solid
рН	Not applicable
Melting point	Not available.
Freezing point	Not available.
Boiling point	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not flammable
Vapor pressure	Not applicable
Vapor density	Not applicable
Specific gravity	1 - 1.2 (H2O = 1)
Relative density	Not available.
Solubility (water)	Negligible in water. Partially soluble in toluene and xylene.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available.
Softening point	176 - 266 °F (80 - 130 °C)
Viscosity	Not applicable

10. Chemical Stability & Reactivity Information

Chemical stability	Stable under normal storage conditions.
Conditions to avoid	Imaging Drum: Exposure to light
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Will not occur.
11. Toxicological Information	
Oral toxicity	LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful Not classified for acute oral toxicity according to EU Directive 67/548/EEC and 1999/45/EC.
Inhalation toxicity	No information available.
	Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and 1999/45/EC.





invent	
Revision	2
Replaces sheet dated	Oct 26 2008 10:14PM
Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
MSDS sections updated	Hazards Identification: Other information
Explanation of abbreviations	

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209