

BLBK301

Information Sheet Revision 2.0

Substance Key: 000BI15B0002 Revision Date: 10/09/2008

Section 1 - Product and Company Identification

Product Name: BI-BK301

Produdct Use: Ink-Jet Printing Ink

Company Identification:

MANUFACTURER

Ninestar Technology Co., Ltd.

No. 63, Mingzhubei Road, Xiangzhou District

Zhuhai, Guangdong, P. R.

China 519075

Oversea sales department:

Tel: +86 756 8539388

Fax: +86 756 8539389

Emergency call: +86 800- 830- 7918 (24 hours hotline)

Section 2 - Composition, Information on Ingredients

Components (% by weight)

COMPONENTS	PERCENTAGE/BOTTLE	CAS#
Diethylene glycol	0%-9%	111-46-6
Isopropanol	0%-5%	67-63-0
Glycerol	0%-10%	56-81-5
Diethylene glycol monobutyl ether	0%-9%	112-34-5
urea	0%-10%	57-13-6
Water	60%-85%	7732-18-5

Dye component Black
Chemical family Azo*

Components (Remarks)

Section 3 - Hazards Identification

Potential Health Effects

THIS PRODUCT CAN BE USED SAFELY WHEN USED AS DIRECTED AND WHEN APPLICABLE SAFETY PRECAUTIONS ARE FOLLOWED.

^{*}The specific identity for each component not identified by a CAS Registry Number is withheld as a trade secret.



BI-BK301

Information Sheet Revision 2.0

PETENTIAL HEALTH EFFECTS FROM PRODUCT

Potential routes of overexposure to this product are skin contact, eye contact and inhalation of vapor.

Ingestion is not expected to be a significant route of exposure for this product under normal use conditions.

There is no toxicity data available for this specific formulation. Any potential hazards are presumed to be due to exposure to the components.

ADDITIONAL HEALTH EFFECTS

Since this mixture has not been tested as a whole to determine the hazards by all routes of exposure, information is provided for each hazardous component of the mixture to meet requirements of OSHA's Hazard Communication Standard (29 CFR 1910.1200). The effects noted occur from exposure to the pure component unless other noted.

INFORMATION FOR COMPONENTS

Diethylene glycol

Eye Contact - May cause eye irritation.

Skin Contact - May cause skin irritation.

Effects of Overexposure - Excessive exposure may cause gastrointestinal disturbances, nausea, headache and vomiting.

Isopropanol

Eye Contact - Contact with eyes may result in irritation.

Skin Contact - Contact with the skin may result in irritation.

Inhalation - Inhalation may result in respiratory irritation.

Ingestion - Ingestion may result in gastric disturbances.

Chronic Overexposure Effects - Developmental toxicity was seen in the offspring of rats at doses that were maternally toxic.

Diethylene glycol monobutyl ether

Eye Contact - Contact with eyes may result in irritation.

Skin Contact - Contact with the skin may result in irritation.

Inhalation - Inhalation may result in respiratory irritation.

Ingestion - Ingestion may result in gastric disturbances.

Chronic Overexposure Effects - Developmental toxicity was seen in the offspring of rats at doses that were maternally toxic.

Glycerol

Eye Contact - May cause eye irritation.

Skin Contact - May cause skin irritation.



RI-RK301

Information Sheet Revision 2.0

Effects of Overexposure - Excessive exposure may cause gastrointestinal disturbances, nausea, headache and vomiting.

UREA

Eye Contact -Effects on exposure: Irritation can occur upon contact with eyes.

Skin Contact-Repeated or prolonged contact with skin may cause reddening, irritation and inflammation

Inhalation-Mild irritation of the respiratory system may occur upon inhalation.

Ingestion Mild irritation of gastrointestinal tract may occur upon ingestion.

Carcinogenicity Information

None of the components present this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or other as a carcinogen.

Section 4 - First Aid Measures

First Aid

Eves: Immediately flush eyes with plenty of water for at least 15 minutes in case of

contact. Call a physician.

Skin: Immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing. Wash clothing before reuse.

Ingestion: Ingestion is not an expected route of exposure during normal use of the product. If

ingested, consult a physician.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing

: is difficult, give oxygen. Call a physician.

Section 5 - Fire Fighting Measures

Flammable Properties

Flash Point: >93.3 °C (>200 °F)

Method: Closed Cup

Approximate Flammable Limits in Air, % by Volume

LEL: Not available UEL: Not available

Autoignition Temperature: Not available

Product is a nonflammable water-based solution.

Hazardous combustion products (gases/vapors) produced in fire can include carbon monoxide, carbon dioxide, nitrogen oxides, and smoke.

Extinguishing Media

Use media appropriate for surrounding material.

Fire Fighting Instructions



ne≘tap™ Material Safety Data Sheet

BLBK30

Information Sheet Revision 2.0

This product is not flammable. Use normal firefighting procedures for the area

Section 6 - Accidental Release Measures

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Initial Containment

Dike spill

Spill Clean Up

Soak up with absorbent material.

Section 7 - Handling and Storage

Handling (Personnel)

Avoid contact with eyes, skin, or clothing.

Section 8 - Exposure Controls, Personal Protection

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses. Wear coverall chemical splash goggles and face shield when the possibility exists for eye and face contact due to splashing or spraying of the material.

RESPIRATORS

Respirators are not needed for normal use.

PROTECTIVE CLOTHING

If there is potential for significant dermal contact wear appropriate impervious clothing and gloves.

Applicable Exposure Limits and Exposure Data

WATER

PEL (OSHA): None Established

TLV (ACGIH): None Established

LD50 (rat, oral): >90 mL/kg (RTECS)

LC50 (rat, inhalation/4 hr.): No data available

Diethylene glycol

PEL (OSHA): None Established

TLV (ACGIH): None Established

LD50 (rat, oral) : >12565mg/kg(RTECS)

LC50 (rat, inhalation/4 hr.): No data available



RI-RK301

Information Sheet Revision 2.0

Isopropanol

PEL (OSHA): None Established

TLV (ACGIH): None Established

LD50 (rat, oral) : >5.47g/kg(RTECS)

LC50 (rat, inhalation/4 hr.): No data available

Diethylene glycol monobutyl ether

PEL (OSHA): None Established

TLV (ACGIH): None Established

LD50 (rat, oral): None Established

LC50 (rat, inhalation/4 hr.): No data available

Glycerol

PEL (OSHA): None Established

TLV (ACGIH): None Established

LD50 (rat, oral): >5.2 g/kg(RTECS)

LC50 (rat, inhalation/4 hr.): No data available

UREA

PEL (OSHA): None Established

TLV (ACGIH): None Established

LD50 (rat, oral): >14.3g/kg(RTECS)

LC50 (rat, inhalation/4 hr.): None Established

Section 9 - Physical and Chemical Properties

Physical Data

Form: Liquid

Color: BI-BK301

Odor: Slight

Solubility in Water: Miscible

pH: 7~9

Specific Gravity: > 1

Other Information

Flash Point : >93.3 °C (>200 °F)

Method: Closed Cup

Approximate Flammable Limits in Air, % by Volume

LEL: Not Available



ne≘tap™ Material Safety Data Sheet

BLBK301

Information Sheet Revision 2.0

UEL: Not Available

Autoignition Temperature: Not Available

Section 10 - Stability and Reactivity

Chemical Stability:

Stable under normal temperatures and pressures.

Incompatibilities with Other Materials:

None reasonably foreseeable.

Decomposition:

Decomposition does not occur during normal use.

Polymerization:

Polymerization will not occur.

Section 11 - Toxicological Information

Animal Data

No data available for product.

Section 12 - Ecological Information

Ecotoxicity:

No data available for product.

Physical:

No information available.

Other:

No information available.

Section 13 - Disposal Considerations

Waste Disposal

DO NOT DISCARD INTO ANY SEWERS, INTO ANY BODY OF WATER, OR ON THE GROUND.

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local laws and regulations.

Section 14 - Transport Information

(Not meant to be all inclusive)

DOT (Domestic Surface) : Not regulated ICAO/IATA (Air) : Not regulated



BI-BK301

Information Sheet Revision 2.0

IMO/IMDG (Ocean): Not regulated

Section 15 - Regulatory Information

U.S. Regulations

Federal Regulations

TSCA Inventory Status -

All components of this product are listed, or exempt from listing, on the TSCA 8(b) chemical inventory.

TSCA Section 12(b) Export Notification –

This product can contain: None

European Union Regulations

EU Inventory Status -

All components of this product are listed, or are exempt from listing, on the EINECS chemical inventory.

Transport Information -

This product is not classified as dangerous within the meaning of transport regulations.

Labeling -

This product does not need to be labeled in accordance with EC-Directive 1999/45/EC.

Section 16 - Additional Information

HMIS® Rating

Health: 1

Flammability: 0

Reactivity: 0

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

MSDS Contact Information:

MANUFACTURER

Ninestar Technology Co., Ltd.

No. 63, Mingzhubei Road, Xiangzhou District

Zhuhai, Guangdong, P. R.

China 519075

Oversea sales department:

Tel: +86 756 8539388

Fax: +86 756 8539389

Emergency call: +86 800- 830- 7918 (24 hours hotline)

Key:



Information Sheet Revision 2.0

EU European Union

HMIS[®] Hazardous Material Information System (National Paint and Coatings Associ

IEL Indicative Exposure Limit (EU Directive 2000/39/EC)

LEL or Lower Explosive Limit or Lower Flammable Limit

NTP National Toxicology Program (U.S.A.)

OEL Occupational Exposure Limit

OSHA Occupational Safety and Health Administration (U.S.A.)

PEL Permissible Exposure Limit