

invent	
1. Product and Company	/ Identification
Identification of the preparation	C6656Series
Product use	Inkjet printing
Version #	11
Revision date	12-Nov-2012
CAS #	Mixture
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-1501
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomer.inquiries@hp.com
2. Hazards Identification	1
Emergency overview	Contact with skin and eyes may result in irritation.
Acute health effects	
	Any potential hazards are presumed to be due to exposure to the components.
Skin contact	<i>2-pyrrolidone</i> Contact with skin may result in irritation.
Eye contact	<i>2-pyrrolidone</i> Contact with eyes may result in irritation. <i>Isopropyl Alcohol</i> Contact with eyes may result in severe irritation.
Inhalation	<i>2-pyrrolidone</i> Inhalation may result in respiratory irritation. <i>Isopropyl Alcohol</i> Inhalation may cause drowsiness or dizziness.
Ingestion	<i>2-pyrrolidone</i> Ingestion may result in nausea, vomiting and diarrhea.
Potential health effects	
Routes of exposure	Potential routes of overexposure to this product are skin and eye contact
	Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this product under normal use conditions.
	Complete toxicity data are not available for this specific formulation
Chronic health effects	None known.
Carcinogenicity	Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present this carcinogenic risk. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

Components			CAS #	Percent	
Water			7732-18-5	< 80	
2-pyrrolidone			616-45-5	< 15	
Carbon black			1333-86-4	< 5	
Isopropyl Alcohol			67-63-0	< 2.5	
Composition comments			mulation. eria specified in 29 CFR 19	10.1200 (Hazard	
	Carbon black is pres	ent only in a bound for	m in this preparation.		
4. First Aid Measures					
First aid procedures					
Eye contact			rge amounts of clean, war ved. If irritation persists go	m water (low pressure) for a et medical attention.	
Skin contact	Wash affected areas attention.	Wash affected areas thoroughly with mild soap and water. If irritation persists get medical			
Inhalation	Move to fresh air. If	symptoms persist, get	medical attention.		
Ingestion	If ingestion of a larg	e amount does occur,	seek medical attention.		
General advice	No additional inform	ation			
5. Fire Fighting Measure	S				
Flammable properties	None known.				
Extinguishing media Suitable extinguishing media	CO2, water, dry che	nical, or foam			
Unsuitable extinguishing media	None known.				
Specific methods	None established.				
Hazardous combustion products	Refer to section 10.				
6. Accidental Release Me	easures				
Personal precautions	Wear appropriate pe	rsonal protective equip	oment.		
Environmental precautions	Do not let product enter drains. Do not flush into surface water or sanitary sewer system.				
Methods for containment			sible. Absorb with inert abs ts, or recover using pumps	orbent such as dry clay, san	
Methods for cleaning up	Soak up with inert a	bsorbent material.			
Other information		spose of in compliance	vly vacuum or sweep the r with federal, state, and loo	naterial into a bag or other cal regulations. See also	
7. Handling and Storage					
Handling	Avoid contact with s	kin, eyes and clothing.			
Storage	Keep out of the read	h of children. Keep aw	ay from excessive heat or	cold.	
8. Exposure Controls / P	ersonal Protection	on			
Occupational exposure limits ACGIH		-			
Components		Туре	Value	Form	
Carbon black (1333-86-4)		TWA	3.0000 mg/m3	Inhalable fraction.	
Isopropyl Alcohol (67-63-0)		BEI STEL	40.0000 mg/l 400.0000 ppm		

TWA     200.0000 ppm       U.S OSHA     Type     Value       Lsopropyl Alcohol (67-63-0)     PEL     400.0000 ppm 980.0000 mg/m3       U.S Tennessee     Type     Value       Carbon black (1333-86-4)     TWA     3.5000 mg/m3       Lsopropyl Alcohol (67-63-0)     STEL     500.0000 ppm 1225.0000       TWA     3.5000 mg/m3       Exposure guidelines     Exposure limits have not been established for this product.       Engineering controls     Use in a well ventilated area.       Personal protective equipment     General hygiene considerations       General Hygiene considerations     Use personal protective equipment to minimize exposure to skin and eye.       9. Physical & Chemical Properties     Appearance       Appearance     Not available.       Color     Black:       Odor     Not available.       physical state     Liquid       Form     Not available.       Physical state     Not available.       point     7.8       Metting point     Not available.       Phase point     Not available.       Physical state     Not available.       Physical state     Not available.       Point     7.3       Metting point     Not available.       Physical state     Not available.    <	Components		Туре	Value Form
Components         Type         Value           Ispropyl Alcohol (67-63-0)         PEL         400.0000 ppm 980.0000 mg/m3           U.S Tennessee Components         Type         Value           Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0)         TWA         3.500 mg/m3           TWA         3.0000 ppm 1225 0000 mg/m3         3000 ppm 1225 0000 mg/m3           Exposure guidelines         Exposure limits have not been established for this product.         mg/m3           Empineering controls         Use is a well ventilated area.         Personal protective equipment considerations         Exposure limits have not been established for this product.           General hygiene considerations         Use personal protective equipment to minimize exposure to skin and eye.         9           9. Physical & Chemical Properties         Appearance         Not available.         5           Odor         Not available.         5         5           Physical state         Liquid         5         5           Boiling point         200 F (93.3 °C)         5         5           Freazing point         Not available.         5         49CFR173, Appendix H).           Physical state         Not available.         5         5           Boiling point         200 F (9 20.3 °C)         5         5			TWA	200.0000 ppm
Components         Type         Value           Ispropyl Alcohol (67-63-0)         PEL         400.0000 ppm 980.0000 mg/m3           U.S Tennessee Components         Type         Value           Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0)         TWA         3.500 mg/m3           TWA         3.0000 ppm 1225 0000 mg/m3         3000 ppm 1225 0000 mg/m3           Exposure guidelines         Exposure limits have not been established for this product.         mg/m3           Empineering controls         Use is a well ventilated area.         Personal protective equipment considerations         Exposure limits have not been established for this product.           General hygiene considerations         Use personal protective equipment to minimize exposure to skin and eye.         9           9. Physical & Chemical Properties         Appearance         Not available.         5           Odor         Not available.         5         5           Physical state         Liquid         5         5           Boiling point         200 F (93.3 °C)         5         5           Freazing point         Not available.         5         49CFR173, Appendix H).           Physical state         Not available.         5         5           Boiling point         200 F (9 20.3 °C)         5         5				
Isopropri/ Alcohol (67-63-0)         PEL         400.0000 ppm 980.0000 mg/m3           U.S Tennessee Components         Type         Value           Cathon black (1333-86-4) Isopropyl Alcohol (67-63-0)         TWA         3.5000 mg/m3 500.0000 ppm 1225.0000 mg/m3           TWA         400.0000 ppm 980.0000 mg/m3           Exposure guidelines         Exposure limits have not been established for this product. Engineering controls         Use in a well ventilated area.           Personal protective equipment General hygiene considerations         Handle in accordance with good industrial hygiene and safety practice. considerations           General Argiene considerations         Not available.           Appearance         Not available.           Physical & Chemical Properties Appearance         Not available.           Odor         Not available.           Physical state         Liquid           Form         Not available.           Physical state         Liquid           Freezing point         Not available.           Physical state         Not available.           Physical state         Not available.           Physical state         Not available.           Freezing point         Not available.           Freezing point         Not available.           Physical state         Not available			Turno	Value
U.S Tennessee     Type     Value       Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0)     TWA     3.5000 mg/m3 5TEL       Stepropyl Alcohol (67-63-0)     STEL     500.0000 ppm 1225.0000 mg/m3 TWA     400.0000 ppm 980.0000 mg/m3       Exposure guidelines     Exposure limits have not been established for this product.     mg/m3 980.0000 mg/m3       Emgineering controls     Use in a well ventilated area.     mg/m3       Personal protective equipment considerations     Use in a well ventilated area.       General hygiene     Handle in accordance with good industrial hygiene and safety practice.       Corlor     Use personal protective equipment to minimize exposure to skin and eye.       9. Physical & Chemical Properties     Japparance       Appearance     Not available.       Color     Not available.       Odor     Not available.       Physical state     Liquid       Form     Not available.       Freezing point     Not available.				
Components         Type         Value           Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0)         TWA         3.5000 mg/m3           STEL         500.0000 ppm 1225.0000 mg/m3         1225.0000 mg/m3           TWA         400.0000 ppm 980.0000 mg/m3           Exposure guidelines         Exposure limits have not been established for this product.           Engineering controls         Use in a well ventilated area.           Personal protective equipment         Handle in accordance with good industrial hygiene and safety practice.           General hygiene considerations         Use personal protective equipment to minimize exposure to skin and eye.           9. Physical & Chemical Properties         Not available.           Appearance         Not available.           Odor         Not available.           Odor         Not available.           Physical state         Liquid           Freezing point         Not available.           Point         131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).           Exporatior rate         Not available.           Freezing point         Not available.           Solubility (Water)         Not available.           Freasting point         Not determined	Isopropyl Alcohol (67-63-0)		PEL	
Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0)     TWA     3.5000 mg/m3       Stressoure guidelines     STEL     500.0000 ppm mg/m3       Exposure guidelines     Exposure limits have not been established for this product.       Engineering controls     Use in a well ventilated area.       Personal protective equipment General hygiene considerations     Handle in accordance with good industrial hygiene and safety practice.       General     Use personal protective equipment to minimize exposure to skin and eye.       9. Physical & Chemical Properties       Appearance     Not available.       Color     Black.       Odor     Not available.       Odor     Not available.       Freezing point     Not available.       Physical state     Liquid       Form     Not available.       Presezing point     Not available.       Freezing point     Not available.       Flash point     131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustai	U.S Tennessee			
Isopropyl Alcohol (67-63-0) STEL SOD.0000 ppm 1225.0000 mg/m3 TWA 400.0000 ppm 980.0000 mg/m3 TWA 400.0000 mg/m3 TWA 400.0000 mg/m3 Exposure guidelines Exposure guidelines Exposure guidelines Exposure guidelines Use in a well ventilated area. Personal protective equipment General hygiene Handle in accordance with good industrial hygiene and safety practice. General hygiene General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Golor Black. Odor Not available. Physical state Liquid Form Not available. Physical state Liquid Form Not available. Freezing point Not available. Boiling point 200 °F (93.3 °C) Flash point 210 °F (95.°C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not available. Freezing point Not availa	Components		Туре	Value
TWA     400.0000 ppm 980.0000 mg/m3       Exposure guidelines     Exposure limits have not been established for this product.       Engineering controls     Use in a well ventilated area.       Personal protective equipment     Handle in accordance with good industrial hygiene and safety practice.       General     Use personal protective equipment to minimize exposure to skin and eye.       9. Physical & Chemical Properties     Appearance       Appearance     Not available.       Color     Back.       Odor     Not available.       Odor     Not available.       Odor     Not available.       Physical state     Liquid       Freezing point     Not available.       Freezing point     Not a	. ,			500.0000 ppm 1225.0000
Engineering controls       Use in a well ventilated area.         Personal protective equipment considerations       Handle in accordance with good industrial hygiene and safety practice.         Seneral hygiene considerations       Use personal protective equipment to minimize exposure to skin and eye.         9. Physical & Chemical Properties         Appearance       Not available.         Color       Black.         Odor       Not available.         Odor       Not available.         Physical state       Liquid         Form       Not available.         pH       7.8         Melting point       Not available.         Freezing point       Not available.         Boiling point       200 °F (93.3 °C)         Flash point       131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).         Evaporation rate       Not available.         Flammability limits in air, upper, % by volume       Not available.         Flammability limits in air, upper, % by volume       Not available.         Specific gravity       1         Relative density       Not available.         Specific gravity       1         Relative density       Not available.      <			TWA	400.0000 ppm
Personal protective equipment         Handle in accordance with good industrial hygiene and safety practice.           General         Use personal protective equipment to minimize exposure to skin and eye.           9. Physical & Chemical Properties         Not available.           Color         Black.           Odor         Not available.           Odor threshold         Not available.           Physical state         Liquid           Form         Not available.           Ph         Not available.           Speing point         Not determined Combustibility Test (method in US 490FR173, Appendix H).           Evaporation rate         Not available.           Flammability limits in air, upper, % by volume         Not available.           Flammability limits in air, locavailable.         Not available. <t< td=""><td>Exposure guidelines</td><td>Exposure limits have</td><td>e not been established</td><td>d for this product.</td></t<>	Exposure guidelines	Exposure limits have	e not been established	d for this product.
General hygien considerations GeneralHandle in accordance with good industrial hygiene and safety practice.9. Physical & Chemical PropertiesAppearanceNot available.ColorBlack.OdorNot available.Odor thresholdNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flash pointNot available.Flash pointNot available.Flash pointNot available.Flash pointNot available.Vapor densityNot available.Flash pointNot available.Flash pointNot available.Flash pointNot available.Flash pointNot available.Soluble:Not available.Flash pointNot available.Specific gravity1Re	Engineering controls	Use in a well ventila	ted area.	
considerations         default         Use personal protective equipment to minimize exposure to skin and eye.           9. Physical & Chemical Properties         Appearance         Not available.           Color         Black.         Odor           Odor         Not available.         Odor           Odor         Not available.         Odor           Odor threshold         Not available.         Physical state           Eiquid         E         Form           Form         Not available.         Physical state           pH         7.8         Melting point           Roling point         Not available.         Freezing point           Boiling point         200 °F (93.3 °C)         Flash point           Flash point         131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).           Evaporation rate         Not available.           Flammability limits in air, upper, % by volume         Not available.           Isomer, % by volume         Not available.           Vapor density         Not available.           Specific gravity         1           Relative density         Not available.           Solublity (water)         Soluble in water <td>Personal protective equipmen</td> <td>t</td> <td></td> <td></td>	Personal protective equipmen	t		
9. Physical & Chemical Properties         Appearance       Not available.         Color       Black.         Odor       Not available.         Odor threshold       Not available.         Physical state       Liquid         Form       Not available.         pH       7.8         Melting point       Not available.         Boiling point       200 °F (93.3 °C)         Flash point       131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).         Evaporation rate       Not available.         Flammability limits in air, upper, % by volume       Not available.         Vapor gressure       Not determined         Vapor density       Not available.         Specific gravity       1         Relative density       Not available.         Solubility (water)       Soluble in water         Auto-ignition temperature       Not available.		Handle in accordanc	e with good industria	I hygiene and safety practice.
AppearanceNot available.ColorBlack.OdorNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash pointNot determinedFlash pointNot determinedFlash pointNot available.Flash pointNot available.Flash pointNot available.Flash pointNot available.Flash pointNot determinedFlash pointNot available.Flash pointNot available.Specific gravity1Relative densityNot available. <tr< th=""><th>General</th><th>Use personal protect</th><th>tive equipment to mir</th><th>nimize exposure to skin and eye.</th></tr<>	General	Use personal protect	tive equipment to mir	nimize exposure to skin and eye.
ColorBlack.OdorNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, upper, % by volumeNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	9. Physical & Chemical P	roperties		
OdorNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubli Ity (water)Soluble in waterAuto-ignition temperatureNot available.	Appearance	Not available.		
Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Color	Black.		
Physical stateLiquidPhysical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Odor	Not available.		
FormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solublity (water)Soluble in waterAuto-ignition temperatureNot available.	Odor threshold	Not available.		
pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Specific gravityNot available.Specific gravity1Relative densityNot available.Solublity (water)Soluble in waterAuto-ignition temperatureNot available.	Physical state	Liquid		
Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Form	Not available.		
Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	pH	7.8		
Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecter using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Melting point	Not available.		
Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Freezing point	Not available.		
Lising the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Boiling point	200 °F (93.3 °C)		
Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Flash point			
upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Evaporation rate	Not determined		
Iower, % by volumeVapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.		Not available.		
Vapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Flammability limits in air, ower, % by volume	Not available.		
Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Vapor pressure	Not determined		
Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Vapor density	Not available.		
Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Specific gravity	1		
Auto-ignition temperature Not available.		Not available.		
Auto-ignition temperature Not available.	-	Soluble in water		
		Not available.		
		Not available.		

Viscosity	2 cp				
Bulk density	1 gm/ml				
VOC	Not available.				
Other information	For other VOC regulatory data/information see section 15.				
10. Chemical Stability & I	Reactivity Information				
Chemical stability	Stable under recommended storage conditions.				
Incompatible materials	Incompatible with strong bases and oxidizing agents.				
Hazardous decomposition products	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.				
Possibility of hazardous reactions	Will not occur.				
11. Toxicological Informa	ation				
Carcinogenicity	Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Grou 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint.				
ACGIH Carcinogens					
Carbon black (CAS 1333-8	A3 Confirmed animal carcinogen with unknown relevance to humans.				
Isopropyl Alcohol (CAS 67 IARC Monographs. Overall					
Carbon black (CAS 1333-8					
IARC Monographs: Evidence	ce of carcinogenicity in humans				
Carbon black (CAS 1333-8					
Serious eye damage/eye irritation	Not available.				
Symptoms and target organs					
Target Organs (NIOSH)					
Carbon black (CAS 1333-8					
Isopropyl Alcohol (CAS 67	-63-0) Respiratory system Eyes				
	Respiratory system Skin				
Further information	Complete toxicity data are not available for this specific formulation. Refer to Section 2 for potential health effects and Section 4 for first aid measures.				
12. Ecological Informatio	n				
Aquatic toxicity	LC50/96h/Fathead minnows =>750 mg/L				
Persistence and degradability	Not available.				
Partition coefficient	Not determined				
<b>13. Disposal Consideratio</b> Disposal instructions	Do not allow this material to drain into sewers/water supplies. Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.				
	HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.				
14. Transport Informatio	n				
Further information	Not a dangerous good under DOT, IATA, ADR, IMDG, or RID. No ignition, sustained combustion, or flashing detected, using the Sustained Combustibility Test prescribed in the UN Manual of Tests and Criteria, Part III subsection 32.5.2. Refer to Dangerous Goods Regulations Section 3.3.1.3. No ignition, sustained combustion or flashing detected using the sustained combustibility test (method in US CFR173, Appendix H).				

## DOT

Not regulated as dangerous goods.

## IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

## RID

Not regulated as dangerous goods.

# 15. Regulatory Information

US federal regulations					US TSCA 12(b): Does not contain listed chemicals.	

# **DEA Exempt Chemical Mixtures Code Number**

Not regulated. Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) Not regulated. Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** 

Not listed.

## **CERCLA** (Superfund) reportable quantity

None

## **Occupational Safety and Health Administration (OSHA)**

29 CFR 1910.1200 Yes hazardous chemical

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance	No

#### Section 311 hazardous No chemical

## State regulations

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black (CAS 1333-86-4)

Listed: February 21, 2003 Carcinogenic.

# US - New Jersey RTK - Substances: Listed substance

Carbon black (CAS 1333-86-4) Isopropyl Alcohol (CAS 67-63-0) Listed. Listed.

Listed. Listed.

Listed.

# **US. Massachusetts RTK - Substance List**

2-pyrrolidone (CAS 616-45-5) Carbon black (CAS 1333-86-4) Isopropyl Alcohol (CAS 67-63-0)

# US. New Jersey Worker and Community Right-to-Know Act .

Not regulated. vlvania DTV \_ U-

US. Pennsylvania RTK - Hazardous Substances					
-					
2-pyrrolidone (CAS 616-45-5)					
Carbon black (CAS 1333-86-4)					
Isopropyl Alcohol (CAS 67-63-0)					

Isopropyl Alcohol (CAS 67-
Phodo Island DTK

# **US. Rhode Island RTK**

Carbon black (CAS 1333-86-4) Isopropyl Alcohol (CAS 67-63-0)

## **Regulatory information**

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

Other information

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments). Exposure Limits (See Section 8): Executive regulation of Minister of Labour and Social Policy dated Nov. 29, 2002 concerning the highest exposure limits and volume of factors harmful for health and environment at work (Official Journal of Laws no 217/2002 item 1833 with further amendments).

16. Other Information	
Other information	This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).
HMIS® ratings	Health: 1 Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 2 Instability: 0
Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
Issue date	12-Nov-2012
This data sheet contains changes from the previous version in section(s):	Product and Company Identification: Alternate Trade Names
Manufacturer information	Hewlett-Packard Company 3000 Hanover Street Palo Alto, California 94304-1112 US (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209

# Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	
	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds