

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refill ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS09

Signal word

Danger

Hazard statement(s)

H225

H319

H411

Highly flammable liquid and vapour.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

Hazardous ingredients

| No | Substance name | Additional information | |
|----|---|---|-------------------|
| | CAS / EC / Index / REACH no | Classification (EC) 1272/2008 (CLP) | Concentration % |
| 1 | ethanol | | |
| | 64-17-5 200-578-6 603-002-00-5 01-2119457610-43 | Flam. Liq. 2; H225 | 61.00 - 63.00 wt% |
| 2 | propan-2-ol | | |
| | 67-63-0 200-661-7 603-117-00-0 01-2119457558-25-0085 | Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336 | 15.00 wt% |
| 3 | Bis(2-ethylhexyl) maleate | | |
| | 142-16-5 205-524-5 - 01-2119524002-60 | STOT RE 2; H373 Aquatic Chronic 1; H410 | 7.00 - 9.00 wt% |
| 4 | Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3) | | |
| | 147-14-8 205-685-1 - - | - | 15.00 wt% |

Full Text for all H-phrases and EUH-phrases: pls. see section 16

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air. In case of persisting adverse effects consult a physician.

After skin contact

Wash immediately with plenty of water for several minutes. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing. Run-off water from fire fighting must not be discharged into drains or enter surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: oxidizing agents; Alkali metals; Earth alkali metals; Nitric acid; sulfuric acid; Peroxides

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

| No | Substance name | CAS no. | EC no. |
|---|--|----------|----------------------------|
| 1 | ethanol | 64-17-5 | 200-578-6 |
| List of approved workplace exposure limits (WELs) / EH40 | | | |
| Ethanol | | | |
| | WEL long-term (8-hr TWA reference period) | 1920 | mg/m ³ 1000 ppm |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| List of approved workplace exposure limits (WELs) / EH40 | | | |
| Propan-2-ol | | | |
| | WEL short-term (15 min reference period) | 1250 | mg/m ³ 500 ppm |
| | WEL long-term (8-hr TWA reference period) | 999 | mg/m ³ 400 ppm |
| 3 | Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3) | 147-14-8 | 205-685-1 |
| List of approved workplace exposure limits (WELs) / EH40 | | | |
| Copper and compounds (as Cu) dusts and mists | | | |
| | WEL short-term (15 min reference period) | 2 | mg/m ³ |
| | WEL long-term (8-hr TWA reference period) | 1 | mg/m ³ |

DNEL, DMEL and PNEC values

DNEL values (worker)

| No | Substance name | CAS / EC no | | |
|----|-------------------|----------------------|----------|-----------------------|
| | Route of exposure | Exposure time | Effect | Value |
| 1 | ethanol | 64-17-5 200-578-6 | | |
| | dermal | Long term (chronic) | systemic | 343 mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 950 mg/m ³ |
| 2 | propan-2-ol | 67-63-0 200-661-7 | | |
| | dermal | Long term (chronic) | systemic | 888 mg/kg/day |

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

| | | | | | |
|---|----------------------------------|---------------------|----------|------------------|-------------------|
| 3 | inhalative | Long term (chronic) | systemic | 500 | mg/m ³ |
| | Bis(2-ethylhexyl) maleate | | | 142-16-5 | |
| | | | | 205-524-5 | |
| | dermal | Long term (chronic) | local | 3.91 | mg/kg/day |
| | dermal | Long term (chronic) | systemic | 0.42 | mg/kg/day |
| | inhalative | Long term (chronic) | local | 1.95 | mg/m ³ |
| | inhalative | Long term (chronic) | systemic | 1.95 | mg/m ³ |

DNEL value (consumer)

| No | Substance name | | | CAS / EC no | |
|----|--------------------|---------------------|----------|------------------|-------------------|
| | Route of exposure | Exposure time | Effect | Value | |
| 1 | ethanol | | | 64-17-5 | |
| | | | | 200-578-6 | |
| | oral | Long term (chronic) | systemic | 87 | mg/kg/day |
| | dermal | Long term (chronic) | systemic | 206 | mg/kg/day |
| | inhalative | Short term (acute) | local | 950 | mg/m ³ |
| | inhalative | Long term (chronic) | systemic | 114 | mg/m ³ |
| 2 | propan-2-ol | | | 67-63-0 | |
| | | | | 200-661-7 | |
| | oral | Long term (chronic) | systemic | 26 | mg/kg/day |
| | dermal | Long term (chronic) | systemic | 319 | mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 89 | mg/m ³ |

PNEC values

| No | Substance name | | CAS / EC no | |
|----|----------------------------------|-----------------------|------------------|-------|
| | ecological compartment | Type | Value | |
| 1 | ethanol | | 64-17-5 | |
| | | | 200-578-6 | |
| | water | fresh water | 0.96 | mg/L |
| | water | marine water | 0.79 | mg/L |
| | water | fresh water sediment | 3.6 | mg/kg |
| | with reference to: dry weight | | | |
| | water | Aqua intermittent | 2.75 | mg/L |
| | water | marine water sediment | 2.9 | mg/kg |
| | with reference to: dry weight | | | |
| | soil | - | 0.63 | mg/kg |
| | with reference to: dry weight | | | |
| | sewage treatment plant | - | 580 | mg/L |
| | secondary poisoning | - | 0.38 | g/kg |
| | with reference to: food | | | |
| 2 | propan-2-ol | | 67-63-0 | |
| | | | 200-661-7 | |
| | water | fresh water | 140.9 | mg/L |
| | water | Aqua intermittent | 140.9 | mg/L |
| | water | marine water | 140.9 | mg/L |
| | water | fresh water sediment | 552 | mg/L |
| | water | marine water sediment | 552 | mg/L |
| | soil | - | 28 | mg/kg |
| | sewage treatment plant | - | 2251 | mg/L |
| | secondary poisoning | - | 160 | mg/kg |
| | with reference to: food | | | |
| 3 | Bis(2-ethylhexyl) maleate | | 142-16-5 | |
| | | | 205-524-5 | |
| | water | fresh water | 0.001 | mg/L |
| | water | marine water | 0.0001 | mg/L |
| | water | fresh water sediment | 15.95 | mg/kg |
| | water | marine water sediment | 1.595 | mg/kg |
| | soil | - | 3.19 | mg/kg |
| | sewage treatment plant | - | 100 | mg/L |

8.2 Exposure controls

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Short term: filter apparatus, Filter A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

| | | | |
|----------------------|-----------------------------|-----|----|
| Appropriate Material | butyl rubber | | |
| Material thickness | | 0.5 | mm |
| Breakthrough time | >= | 8 | h |
| Appropriate Material | Fluorocarbon rubber (Viton) | | |
| Material thickness | | 0.4 | mm |
| Breakthrough time | >= | 8 | h |
| Appropriate Material | Polychloroprene | | |
| Material thickness | | 0.5 | mm |
| Breakthrough time | >= | 2 | h |

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--------------------------------------|-----------|
| State of aggregation | |
| liquid | |
| Form/Colour | |
| liquid | |
| blue | |
| Odour | |
| alcohol-like | |
| pH value | |
| Value | 3 - 9 |
| Boiling point / boiling range | |
| Value | 78.3 °C |
| Melting point/freezing point | |
| Value | -114.5 °C |
| Decomposition temperature | |
| No data available | |
| Flash point | |
| Value | 12 °C |
| Ignition temperature | |
| No data available | |

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

| Auto-ignition temperature | | | |
|--|----------------|---------|-----------|
| Value | 425 °C | | |
| Flammability | | | |
| No data available | | | |
| Lower explosion limit | | | |
| Value | 3.5 % vol | | |
| Upper explosion limit | | | |
| Value | 15.0 % vol | | |
| Vapour pressure | | | |
| Value | 59 | hPa | |
| Reference temperature | 20 | °C | |
| Relative vapour density | | | |
| No data available | | | |
| Relative density | | | |
| No data available | | | |
| Density | | | |
| No data available | | | |
| Solubility in water | | | |
| Comments | miscible | | |
| Solubility | | | |
| No data available | | | |
| Partition coefficient n-octanol/water (log value) | | | |
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| log Pow | | 0.05 | |
| Reference temperature | | 25 °C | |
| Source | | ECHA | |
| Kinematic viscosity | | | |
| Value | 7.5 | - 12 | cP |
| Reference temperature | 20 | | °C |
| Type | dynamic | | |
| Particle characteristics | | | |
| No data available | | | |

9.2 Other information

| |
|--------------------------|
| Other information |
| No data available. |

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents; Alkali metals; Earth alkali metals; Nitric acid; sulfuric acid; Peroxides

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

| Acute oral toxicity | | | |
|---------------------------|---|----------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| LD50 | | 10740 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| LD50 | | 5840 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| 3 | Bis(2-ethylhexyl) maleate | 142-16-5 | 205-524-5 |
| LD50 | > | 2000 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |

| Acute dermal toxicity | | | |
|-----------------------|---------------------------|----------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | Bis(2-ethylhexyl) maleate | 142-16-5 | 205-524-5 |
| LD50 | | 14000 | mg/kg bodyweight |
| Species | rabbit | | |
| Source | ECHA | | |

| Acute inhalational toxicity | | | |
|-----------------------------|---|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| LC50 | | 124.7 | mg/l |
| Duration of exposure | | 4 | h |
| State of aggregation | Dust/mist | | |
| Species | rat | | |
| Method | OECD 403 | | |
| Source | ECHA | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| LC50 | > | 10000 | ppmV |
| Duration of exposure | | 6 | h |
| State of aggregation | Vapour | | |
| Species | rat | | |
| Method | OECD 403 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Skin corrosion/irritation | | | |
|---------------------------|---|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| Species | rabbit | | |
| Source | ECHA | | |
| Evaluation | non-irritant | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Serious eye damage/irritation | | | |
|-------------------------------|----------------|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

| | |
|---------------------------|---|
| Species | rabbit |
| Method | OECD 405 |
| Source | ECHA |
| Evaluation | irritant |
| Evaluation/classification | Based on available data, the classification criteria are met. |

| Respiratory or skin sensitisation | | | |
|-----------------------------------|---|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Route of exposure | | Skin | |
| Species | mouse | | |
| Method | OECD 429 | | |
| Source | ECHA | | |
| Evaluation | non-sensitizing | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| Route of exposure | | Skin | |
| Species | guinea pig | | |
| Method | OECD 406 | | |
| Source | ECHA | | |
| Evaluation | non-sensitizing | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Germ cell mutagenicity | | | |
|---------------------------|----------------|---|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| Reproduction toxicity | | | |
|---------------------------|----------------|---|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| Carcinogenicity | | | |
|---------------------------|----------------|---|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| STOT - single exposure | |
|------------------------|--|
| No data available | |

| STOT - repeated exposure | | | |
|---------------------------|----------------|---|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| Route of exposure | | inhalational | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| Aspiration hazard | |
|-------------------|--|
| No data available | |

| Delayed and immediate effects as well as chronic effects from short and long-term exposure | |
|---|--|
| Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation. | |

11.2 Information on other hazards

Endocrine disrupting properties

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

No data available.

Other information

No data available.

SECTION 12: Ecological information
12.1 Toxicity

| Toxicity to fish (acute) | | | |
|---------------------------------|---|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| LC50 | > | 14000 | mg/l |
| Duration of exposure | | 96 | h |
| Species | Pimephales promelas | | |
| Method | EPA E03-05 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| LC50 | > | 9640 | mg/l |
| Duration of exposure | | 96 | h |
| Species | Pimephales promelas | | |
| Method | OECD 203 | | |
| Source | ECHA | | |

| Toxicity to fish (chronic) | | | |
|-----------------------------------|--|--|--|
| No data available | | | |

| Toxicity to Daphnia (acute) | | | |
|------------------------------------|----------------|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| EC50 | > | 10000 | mg/l |
| Duration of exposure | | 24 | h |
| Species | Daphnia magna | | |
| Method | OECD 202 | | |
| Source | ECHA | | |

| Toxicity to Daphnia (chronic) | | | |
|--------------------------------------|--|--|--|
| No data available | | | |

| Toxicity to algae (acute) | | | |
|----------------------------------|--|--|--|
| No data available | | | |

| Toxicity to algae (chronic) | | | |
|------------------------------------|--|--|--|
| No data available | | | |

| Bacteria toxicity | | | |
|--------------------------|--|--|--|
| No data available | | | |

12.2 Persistence and degradability

| Biodegradability | | | |
|-------------------------|-----------------------|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| Type | BOD/COD | | |
| Value | | 53 | % |
| Duration | | 5 | day(s) |
| Source | ECHA | | |
| Evaluation | readily biodegradable | | |

12.3 Bioaccumulative potential

| Partition coefficient n-octanol/water (log value) | | | |
|--|----------------|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| log Pow | | 0.05 | |

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

| | | |
|-----------------------|------|----|
| Reference temperature | 25 | °C |
| Source | ECHA | |

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

| | |
|--|------------------------|
| Class | 3 |
| Classification code | F1 |
| Packing group | II |
| Hazard identification no. | 33 |
| UN number | UN1263 |
| Proper shipping name | PAINT |
| Special Provision 640 | 640C |
| Tunnel restriction code | D/E |
| Label | 3 |
| Environmentally hazardous substance mark | Symbol "fish and tree" |

14.2 Transport IMDG

| | |
|-----------------------|---------------------------|
| Class | 3 |
| Packing group | II |
| UN number | UN1263 |
| Proper shipping name | PAINT |
| Technical name | Bis(2-ethylhexyl) maleate |
| EmS | F-E, S-E |
| Label | 3 |
| Marine pollutant mark | Symbol "fish and tree" |

14.3 Transport ICAO-TI / IATA

| | |
|----------------------|--------|
| Class | 3 |
| Packing group | II |
| UN number | UN1263 |
| Proper shipping name | Paint |
| Label | 3 |

14.4 Other information

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

| No | Substance name | CAS no. | EC no. | No |
|----|----------------|---------|-----------|----|
| 1 | propan-2-ol | 67-63-0 | 200-661-7 | 75 |

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5b

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

REGULATION (EU) No 528/2012 concerning the making available on the market and use of biocidal products

Bis(2-ethylhexyl) maleate 9 wt%

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

| | |
|------|---|
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H410 | Very toxic to aquatic life with long lasting effects. |

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Trade name: edding refill ink whiteboard marker (blue) BT30 contained in: edding 365

Current version : 4.0.0, issued: 23.06.2022

Replaced version: 3.0.0, issued: 25.11.2021

Region: GB

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 17415