

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding refill ink whiteboard marker RBTK25 blue (1133003)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refill ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH
Bookkoppel 7
D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

Details of the importer

Address

edding UK Ltd.
edding House, Merlin Centre
AL4 0JY St Albans
Hertfordshire
United Kingdom

Telephone no. +44 (0)1727 84 66 88

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB


GHS02



GHS07



GHS09

Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	ethanol		
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225	61.00 - 63.00 wt%
2	propan-2-ol		
	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-0085	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	15.00 wt%
3	Bis(2-ethylhexyl) maleate		
	142-16-5 205-524-5 - 01-2119524002-60	STOT RE 2; H373 Aquatic Chronic 1; H410	7.00 - 9.00 wt%
4	Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3)		
	147-14-8 205-685-1 - -	-	15.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)**Current version :** 5.0.0, issued: 23.06.2022**Replaced version:** 4.0.0, issued: 25.11.2021**Region:** GB

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air. In case of persisting adverse effects consult a physician.

After skin contact

Wash immediately with plenty of water for several minutes. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing. Run-off water from fire fighting must not be discharged into drains or enter surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities
Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: oxidizing agents; Alkali metals; Earth alkali metals; Nitric acid; sulfuric acid; Peroxides

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
List of approved workplace exposure limits (WELs) / EH40			
Ethanol			
	WEL long-term (8-hr TWA reference period)	1920 mg/m ³	1000 ppm
2	propan-2-ol	67-63-0	200-661-7
List of approved workplace exposure limits (WELs) / EH40			
Propan-2-ol			
	WEL short-term (15 min reference period)	1250 mg/m ³	500 ppm
	WEL long-term (8-hr TWA reference period)	999 mg/m ³	400 ppm
3	Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3)	147-14-8	205-685-1
List of approved workplace exposure limits (WELs) / EH40			
Copper and compounds (as Cu) dusts and mists			
	WEL short-term (15 min reference period)	2 mg/m ³	
	WEL long-term (8-hr TWA reference period)	1 mg/m ³	

DNEL, DMEL and PNEC values
DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	ethanol	64-17-5 200-578-6		
	dermal	Long term (chronic)	systemic	343 mg/kg/day
	inhalative	Long term (chronic)	systemic	950 mg/m ³
2	propan-2-ol	67-63-0 200-661-7		
	dermal	Long term (chronic)	systemic	888 mg/kg/day

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

3	inhalative	Long term (chronic)	systemic	500	mg/m ³
	Bis(2-ethylhexyl) maleate			142-16-5	205-524-5
	dermal	Long term (chronic)	local	3.91	mg/kg/day
	dermal	Long term (chronic)	systemic	0.42	mg/kg/day
	inhalative	Long term (chronic)	local	1.95	mg/m ³
	inhalative	Long term (chronic)	systemic	1.95	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethanol			64-17-5	200-578-6
	oral	Long term (chronic)	systemic	87	mg/kg/day
	dermal	Long term (chronic)	systemic	206	mg/kg/day
	inhalative	Short term (acute)	local	950	mg/m ³
	inhalative	Long term (chronic)	systemic	114	mg/m ³
2	propan-2-ol			67-63-0	200-661-7
	oral	Long term (chronic)	systemic	26	mg/kg/day
	dermal	Long term (chronic)	systemic	319	mg/kg/day
	inhalative	Long term (chronic)	systemic	89	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	ethanol		64-17-5	200-578-6
	water	fresh water	0.96	mg/L
	water	marine water	0.79	mg/L
	water	fresh water sediment	3.6	mg/kg
	with reference to: dry weight			
	water	Aqua intermittent	2.75	mg/L
	water	marine water sediment	2.9	mg/kg
	with reference to: dry weight			
	soil	-	0.63	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	580	mg/L
	secondary poisoning	-	0.38	g/kg
	with reference to: food			
2	propan-2-ol		67-63-0	200-661-7
	water	fresh water	140.9	mg/L
	water	Aqua intermittent	140.9	mg/L
	water	marine water	140.9	mg/L
	water	fresh water sediment	552	mg/L
	water	marine water sediment	552	mg/L
	soil	-	28	mg/kg
	sewage treatment plant	-	2251	mg/L
	secondary poisoning	-	160	mg/kg
	with reference to: food			
3	Bis(2-ethylhexyl) maleate		142-16-5	205-524-5
	water	fresh water	0.001	mg/L
	water	marine water	0.0001	mg/L
	water	fresh water sediment	15.95	mg/kg
	water	marine water sediment	1.595	mg/kg
	soil	-	3.19	mg/kg
	sewage treatment plant	-	100	mg/L

8.2 Exposure controls

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Appropriate engineering controls

No data available.

Personal protective equipment
Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Short term: filter apparatus, Filter A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.5	mm
Breakthrough time	>=	8	h
Appropriate Material	Fluorocarbon rubber (Viton)		
Material thickness		0.4	mm
Breakthrough time	>=	8	h
Appropriate Material	Polychloroprene		
Material thickness		0.5	mm
Breakthrough time	>=	2	h

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form/Colour	
liquid	
blue	
Odour	
alcohol-like	
pH value	
Value	3 - 9
Boiling point / boiling range	
Value	78.3 °C
Melting point/freezing point	
Value	-114.5 °C
Decomposition temperature	
No data available	
Flash point	
Value	12 °C
Ignition temperature	
No data available	

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Auto-ignition temperature			
Value	425	°C	
Flammability			
No data available			
Lower explosion limit			
Value	3.5	% vol	
Upper explosion limit			
Value	15.0	% vol	
Vapour pressure			
Value	59	hPa	
Reference temperature	20	°C	
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
No data available			
Solubility in water			
Comments	miscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source		ECHA	
Kinematic viscosity			
Value	7.5	- 12	cP
Reference temperature		20	°C
Type	dynamic		
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents; Alkali metals; Earth alkali metals; Nitric acid; sulfuric acid; Peroxides

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		10740	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
2	propan-2-ol	67-63-0	200-661-7
LD50		5840	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	Bis(2-ethylhexyl) maleate	142-16-5	205-524-5
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Bis(2-ethylhexyl) maleate	142-16-5	205-524-5
LD50		14000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124.7	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
2	propan-2-ol	67-63-0	200-661-7
LC50	>	10000	ppmV
Duration of exposure		6	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	irritant
Evaluation/classification	Based on available data, the classification criteria are met.

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure		Skin	
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
2	propan-2-ol	67-63-0	200-661-7
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
Route of exposure		inhalational	
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard			
No data available			

Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.			

11.2 Information on other hazards

Endocrine disrupting properties

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

No data available.

Other information

No data available.

SECTION 12: Ecological information
12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50	>	14000	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA E03-05		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
LC50	>	9640	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
EC50	>	10000	mg/l
Duration of exposure		24	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No data available			

Toxicity to algae (acute)			
No data available			

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
Type	BOD/COD		
Value		53	%
Duration		5	day(s)
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Reference temperature	25	°C
Source	ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information
Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information
14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640C
Tunnel restriction code	D/E
Label	3
Environmentally hazardous substance mark	Symbol "fish and tree"

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
Technical name	Bis(2-ethylhexyl) maleate
EmS	F-E, S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	propan-2-ol	67-63-0	200-661-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5b

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

REGULATION (EU) No 528/2012 concerning the making available on the market and use of biocidal products

Bis(2-ethylhexyl) maleate 9 wt%

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Trade name: edding refill ink whiteboard marker RBTK25 blue (1133003)

Current version : 5.0.0, issued: 23.06.2022

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 679968