

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Refill ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

**Details of the importer**

**Address**

edding UK Ltd.

edding House, Merlin Centre

AL4 0JY St Albans

Hertfordshire

United Kingdom

Telephone no. +44 (0)1727 84 66 88

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

Eye Dam. 1; H318

Flam. Liq. 2; H225

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB


GHS02



GHS05



GHS07

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

 propan-1-ol  
 1-methoxy-2-propanol

**Hazard statement(s)**

 H225 Highly flammable liquid and vapour.  
 H318 Causes serious eye damage.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statement(s)**

 P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.  
 P405 Store locked up.  
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**
**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name	Classification (EC) 1272/2008 (CLP)	Additional information	
	CAS / EC / Index / REACH no		Concentration	%
1	<b>propan-1-ol</b>			
	71-23-8 200-746-9 603-003-00-0 01-2119486761-29	Eye Dam. 1; H318 Flam. Liq. 2; H225 STOT SE 3; H336	< 55.00	wt%
2	<b>1-methoxy-2-propanol</b>			
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35-0034	Flam. Liq. 3; H226 STOT SE 3; H336	< 30.00	wt%
3	<b>[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7</b>			

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

2390-60-5	Acute Tox. 3; H301	< 2.50	wt%
219-232-0	Aquatic Acute 1; H400		
-	Eye Dam. 1; H318		
-	Aquatic Chronic 1; H410		

Full Text for all H-phrases and EUH-phrases: pls. see section 16

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person. Rinse the mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

#### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

### 5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing. Suppress gases/vapours/mists with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

### 6.4 Reference to other sections

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

#### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

#### Incompatible products

Do not store together with: oxidizing agents; Alkali metals; Earth alkali metals; Acids

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	propan-1-ol	71-23-8		200-746-9	
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Propan-1-ol					
	WEL short-term (15 min reference period)	625	mg/m <sup>3</sup>	250	ppm
	WEL long-term (8-hr TWA reference period)	500	mg/m <sup>3</sup>	200	ppm
	Comments	Sk			
2	1-methoxy-2-propanol	107-98-2		203-539-1	
<b>2000/39/EC</b>					
1-Methoxypropanol-2					
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm
	Skin resorption / sensibilisation	Skin			
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
1-Methoxypropan-2-ol					
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

Comments	Sk
----------	----

**DNEL, DMEL and PNEC values**
**DNEL values (worker)**

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	<b>propan-1-ol</b>			<b>71-23-8</b> <b>200-746-9</b>
	dermal	Long term (chronic)	systemic	136 mg/kg/day
	inhalative	Short term (acut)	systemic	1723 mg/m <sup>3</sup>
	inhalative	Long term (chronic)	systemic	268 mg/m <sup>3</sup>
2	<b>1-methoxy-2-propanol</b>			<b>107-98-2</b> <b>203-539-1</b>
	dermal	Long term (chronic)	systemic	183 mg/kg/day
	inhalative	Long term (chronic)	systemic	369 mg/m <sup>3</sup>
	inhalative	Short term (acut)	local	553.5 mg/m <sup>3</sup>

**DNEL value (consumer)**

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	<b>propan-1-ol</b>			<b>71-23-8</b> <b>200-746-9</b>
	oral	Long term (chronic)	systemic	61 mg/kg/day
	dermal	Long term (chronic)	systemic	81 mg/kg/day
	inhalative	Short term (acut)	systemic	1036 mg/m <sup>3</sup>
	inhalative	Long term (chronic)	systemic	80 mg/m <sup>3</sup>
2	<b>1-methoxy-2-propanol</b>			<b>107-98-2</b> <b>203-539-1</b>
	oral	Long term (chronic)	systemic	33 mg/kg/day
	dermal	Long term (chronic)	systemic	78 mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9 mg/m <sup>3</sup>

**PNEC values**

No	Substance name			CAS / EC no
	ecological compartment	Type		Value
1	<b>propan-1-ol</b>			<b>71-23-8</b> <b>200-746-9</b>
	water	fresh water		6.83 mg/L
	water	Aqua intermittent		10 mg/L
	water	marine water		0.683 mg/L
	water	fresh water sediment		27.5 mg/kg dry weight
	water	marine water sediment		2.75 mg/kg dry weight
	soil	-		1.49 mg/kg dry weight
	sewage treatment plant	-		96 mg/L
2	<b>1-methoxy-2-propanol</b>			<b>107-98-2</b> <b>203-539-1</b>
	water	fresh water		10 mg/L
	water	marine water		1 mg/L
	water	Aqua intermittent		100 mg/L
	water	fresh water sediment		52.3 mg/kg
	with reference to: dry weight			
	water	marine water sediment		5.2 mg/kg
	with reference to: dry weight			
	soil	-		4.59 mg/kg
	with reference to: dry weight			
	sewage treatment plant	-		100 mg/L

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Short term: filter apparatus, Filter A

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.5	mm
Breakthrough time	>=	480	min
Appropriate Material	nitrile rubber		
Material thickness		0.35	mm
Breakthrough time	>=	480	min

#### Other

Normal chemical work clothing.

### Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>			
liquid			
<b>Form/Colour</b>			
liquid			
blue			
<b>Odour</b>			
alcohol-like			
<b>pH value</b>			
Value	7	-	9
Concentration			100 %
<b>Boiling point / boiling range</b>			
Value		97	°C
Reference substance	CAS 71-23-8		
<b>Melting point/freezing point</b>			
Value		-127.5	°C
Reference substance	CAS 71-23-8		
<b>Decomposition temperature</b>			
No data available			
<b>Flash point</b>			
Value		23.5	°C
Reference substance	CAS 71-23-8		

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

<b>Ignition temperature</b>			
No data available			
<b>Flammability</b>			
No data available			
<b>Lower explosion limit</b>			
No data available			
<b>Upper explosion limit</b>			
No data available			
<b>Vapour pressure</b>			
No data available			
<b>Relative vapour density</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value	0.96 g/cm <sup>3</sup>		
<b>Solubility in water</b>			
Comments	miscible		
<b>Solubility</b>			
No data available			
<b>Partition coefficient n-octanol/water (log value)</b>			
<b>No</b>	<b>Substance name</b>	<b>CAS no.</b>	<b>EC no.</b>
1	propan-1-ol	71-23-8	200-746-9
log Pow	0.2	- 1.6	
Reference temperature		25	°C
with reference to	pH 7		
Method	OECD 117		
Source	ECHA		
<b>Viscosity</b>			
Value	4 - 6 mm <sup>2</sup> /s		
Source	Manufacturer		
<b>Particle characteristics</b>			
No data available			

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

Vapours may form an explosive mixture with air.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

### 10.5 Incompatible materials

Oxidizing agents; Alkali metals; Earth alkali metals; Acids

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

## 10.6 Hazardous decomposition products

None, if handled according to intended use.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
LD50		3730	mg/kg bodyweight
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
LD50		4032	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	1-methoxy-2-propanol	107-98-2	203-539-1
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
LC50	>	33.8	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
Species	rabbit		
Method	OECD 404		
Source	ECHA		

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

Evaluation	non-irritant
Evaluation/classification	Based on available data, the classification criteria are not met.
<b>2</b>	<b>1-methoxy-2-propanol</b> <b>107-98-2</b> <b>203-539-1</b>
Species	rabbit
Method	EC 440/2008, B.4
Source	ECHA
Evaluation	non-irritant
<b>3</b>	<b>[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7</b> <b>2390-60-5</b> <b>219-232-0</b>
Species	rabbit
Source	Manufacturer
Evaluation	non-irritant

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>propan-1-ol</b>	<b>71-23-8</b>	<b>200-746-9</b>
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	Irreversible effects on the eye		
Evaluation/classification	Based on available data, the classification criteria are met.		
<b>2</b>	<b>1-methoxy-2-propanol</b> <b>107-98-2</b> <b>203-539-1</b>		
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		
<b>3</b>	<b>[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7</b> <b>2390-60-5</b> <b>219-232-0</b>		
Species	rabbit		
Source	Manufacturer		
Evaluation	Irreversible effects on the eye		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>propan-1-ol</b>	<b>71-23-8</b>	<b>200-746-9</b>
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>2</b>	<b>1-methoxy-2-propanol</b> <b>107-98-2</b> <b>203-539-1</b>		
Route of exposure	Skin		
Species	guinea pig		
Method	440/2008/EC B.6		
Source	ECHA		
Evaluation	non-sensitizing		
<b>3</b>	<b>[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7</b> <b>2390-60-5</b> <b>219-232-0</b>		
Route of exposure	Skin		
Species	guinea pig		
Method	maximization test		
Source	Manufacturer		
Evaluation	non-sensitizing		

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

<b>Germ cell mutagenicity</b>			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
Type of examination		in vitro gene mutation study in bacteria	
Species		Salmonella typhimurium / Escherichia coli	
Method		OECD 471	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Type of examination		In vitro mammalian cell gene mutation test	
Species		Chinese hamster Ovary (CHO)	
Method		OECD 476	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Type of examination		In vitro Mammalian Chromosomal Aberration Test	
Species		Chinese hamster V79 cells	
Method		OECD 473	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

<b>Reproduction toxicity</b>			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
Route of exposure		inhalational	
Type of examination		Toxicity study	
Species		rat	
Method		OECD 413	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		inhalational	
Type of examination		Prenatal Developmental Toxicity Study	
Species		rat	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

<b>Carcinogenicity</b>		
No data available		

<b>STOT - single exposure</b>		
No data available		

<b>STOT - repeated exposure</b>			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
Route of exposure		inhalational	
Species		rat	
Method		OECD 413	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		oral	
Species		rat	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

<b>Aspiration hazard</b>		
No data available		

<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>		
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.		

## 11.2 Information on other hazards

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

**Endocrine disrupting properties**

No data available.

**Other information**

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

<b>Toxicity to fish (acute)</b>			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
LC50		4555	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7	2390-60-5	219-232-0
LC50		0.03	mg/l
Duration of exposure		96	h
Species	Leuciscus idus		
Method	DIN 38 412, Part 15		
Source	Manufacturer		
<b>Toxicity to fish (chronic)</b>			
No data available			
<b>Toxicity to Daphnia (acute)</b>			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
EC50		3644	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	DIN 38412 Part 11		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7	2390-60-5	219-232-0
EC50		0.015	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	DIN 38412 T.11		
Source	Manufacturer		
<b>Toxicity to Daphnia (chronic)</b>			
No data available			
<b>Toxicity to algae (acute)</b>			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
EC50		9170	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

Toxicity to algae (chronic)
No data available

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7	2390-60-5	219-232-0
EC50		14	mg/l
Species	Pseudomonas putida		
Method	DIN 38412 T.27		
Source	Manufacturer		

## 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
Type	aerobic biodegradation		
Value		75	%
Duration		20	day(s)
Source	ECHA		
Evaluation	readily biodegradable		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		
Value		96	%
Duration		28	day(s)
Method	OECD 301 E		
Source	ECHA		
Evaluation	readily biodegradable		

## 12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
log Pow		0.2	- 1.6
Reference temperature			25 °C
with reference to	pH 7		
Method	OECD 117		
Source	ECHA		

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

with the regional waste disposal company.

#### **Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

### **SECTION 14: Transport information**

#### **14.1 Transport ADR/RID/ADN**

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

#### **14.2 Transport IMDG**

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

#### **14.3 Transport ICAO-TI / IATA**

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

#### **14.4 Other information**

No data available.

#### **14.5 Environmental hazards**

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### **14.6 Special precautions for user**

No data available.

#### **14.7 Maritime transport in bulk according to IMO instruments**

Not relevant

### **SECTION 15: Regulatory information**

#### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulations**

###### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

###### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

###### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON**

**Trade name:** edding refill ink permanent marker RMTK25 (blue) contained in: edding retract 11

**Current version :** 4.0.0, issued: 02.02.2022

**Replaced version:** 3.1.2, issued: 15.09.2021

**Region:** GB

#### THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.		No 3, 40		
The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.				
No	Substance name	CAS no.	EC no.	No
1	[4-[4-(diethylamino)-alpha-[4-(ethylamino)-1-naphthyl]benzylidene]cyclohexa-2,5-dien-1-ylidene]diethylammonium chloride, C.I. 42595, Basic Blue 7	2390-60-5	219-232-0	75
2	2-amino-2-methylpropanol	124-68-5	204-709-8	75
3	propan-1-ol	71-23-8	200-746-9	75
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances				
This product is subject to Part I of Annex I, risk category:				P5b

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

#### Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

#### Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 24851