

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Ink for use in felt pens

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Flam. Liq. 2; H225

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02

**Signal word**

Danger

**Hazard statement(s)**

H225

Highly flammable liquid and vapour.

**Hazard statements (EU)**

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

**Precautionary statement(s)**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.  
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**
**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	<b>Naphtha (petroleum), light alkylate</b>		<b>Contains &lt; 0.1 % w/w benzene (EC No 200-753-7). pls. refer to footnote (1)</b>	
	64741-66-8 265-068-8 649-276-00-X -	Asp. Tox. 1; H304	>= 25.00 - < 50.00	wt%
2	<b>ETHYLCYCLOHEXANE</b>			
	1678-91-7 216-835-0 - -	Asp. Tox. 1; H304 Flam. Liq. 2; H225	>= 10.00 - < 25.00	wt%
3	<b>aluminium powder (stabilised)</b>			
	7429-90-5 231-072-3 013-002-00-1 -	Flam. Sol. 1; H228 Water-react. 2; H261	< 5.00	wt%
4	<b>Naphta (Petroleum), hydrodesulfurized heavy</b>			
	64742-82-1 265-185-4 649-330-00-2 -	Asp. Tox. 1; H304	< 5.00	wt%
5	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>			
	13463-67-7 236-675-5 022-006-00-2 -	Carc. 2; H351i	< 2.50	wt%
6	<b>Tetrabeno-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3)</b>			
	147-14-8 205-685-1 - -	-	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	P	-	-	-
3	T	-	-	-
5	V, W, 10	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
5	H351i inhalational; -; -

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide; Water spray jet

#### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO); Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

**6.4 Reference to other sections**

No data available.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

**Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

**Advice on protection against fire and explosion**

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

**7.2 Conditions for safe storage, including any incompatibilities**

**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

**Requirements for storage rooms and vessels**

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

**Incompatible products**

Do not store together with: oxidizing agents; Acids; Bases

**7.3 Specific end use(s)**

No data available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

**Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	aluminium powder (stabilised)	7429-90-5	231-072-3
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Aluminium metal		
	total inhalable dust		
	WEL long-term (8-hr TWA reference period)	10	mg/m <sup>3</sup>
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Aluminium metal		
	respirable dust		
	WEL long-term (8-hr TWA reference period)	4	mg/m <sup>3</sup>
2	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

List of approved workplace exposure limits (WELs) / EH40		
Titanium dioxide		
total inhalable dust		
WEL long-term (8-hr TWA reference period)	10	mg/m <sup>3</sup>
List of approved workplace exposure limits (WELs) / EH40		
Titanium dioxide		
respirable dust		
WEL long-term (8-hr TWA reference period)	4	mg/m <sup>3</sup>
<b>3</b>	<b>Tetrabenz-5,10,15,20-diazaphorphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3)</b>	<b>147-14-8 205-685-1</b>
List of approved workplace exposure limits (WELs) / EH40		
Copper and compounds (as Cu) dusts and mists		
WEL short-term (15 min reference period)	2	mg/m <sup>3</sup>
WEL long-term (8-hr TWA reference period)	1	mg/m <sup>3</sup>

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

#### Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form/Colour</b>	
liquid	
violet; metallic	
<b>Odour</b>	
characteristic	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	116 °C
<b>Melting point/freezing point</b>	
No data available	

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	7 °C
<b>Ignition temperature</b>	
Value	200 - 262 °C
<b>Flammability</b>	
No data available	
<b>Lower explosion limit</b>	
Value	0.9 % vol
<b>Upper explosion limit</b>	
Value	8.4 % vol
<b>Vapour pressure</b>	
No data available	
<b>Relative vapour density</b>	
No data available	
<b>Relative density</b>	
No data available	
<b>Density</b>	
Value	0.84 g/cm <sup>3</sup>
<b>Solubility in water</b>	
Comments	insoluble
<b>Solubility</b>	
No data available	
<b>Partition coefficient n-octanol/water (log value)</b>	
No data available	
<b>Kinematic viscosity</b>	
Value	18.6 mPa*s
Type	dynamic
Value	22.1 mm <sup>2</sup> /s
Reference temperature	40 °C
Type	kinematic
<b>Particle characteristics</b>	
No data available	

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

### 10.5 Incompatible materials

Oxidizing agents; Acids; Bases

### 10.6 Hazardous decomposition products

Nitrous oxides (NOx)

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute oral toxicity</b>
No data available

<b>Acute dermal toxicity</b>
No data available

<b>Acute inhalational toxicity</b>
No data available

<b>Skin corrosion/irritation</b>
No data available

<b>Serious eye damage/irritation</b>
No data available

<b>Respiratory or skin sensitisation</b>
No data available

<b>Germ cell mutagenicity</b>
No data available

<b>Reproduction toxicity</b>
No data available

<b>Carcinogenicity</b>
No data available

<b>STOT - single exposure</b>
No data available

<b>STOT - repeated exposure</b>
No data available

<b>Aspiration hazard</b>
No data available

<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

### 11.2 Information on other hazards

**Endocrine disrupting properties**

No data available.

**Other information**

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

<b>Toxicity to fish (acute)</b>
No data available

<b>Toxicity to fish (chronic)</b>
No data available

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

<b>Toxicity to Daphnia (acute)</b>
------------------------------------

No data available
-------------------

<b>Toxicity to Daphnia (chronic)</b>
--------------------------------------

No data available
-------------------

<b>Toxicity to algae (acute)</b>
----------------------------------

No data available
-------------------

<b>Toxicity to algae (chronic)</b>
------------------------------------

No data available
-------------------

<b>Bacteria toxicity</b>
--------------------------

No data available
-------------------

## 12.2 Persistence and degradability

No data available.

## 12.3 Bioaccumulative potential

No data available.

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

<b>Other information</b>
--------------------------

Do not discharge product unmonitored into the environment.
--

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

### 14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

Proper shipping name PAINT  
EmS F-E, S-E  
Label 3

#### 14.3 Transport ICAO-TI / IATA

Class 3  
Packing group II  
UN number UN1263  
Proper shipping name Paint  
Label 3

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

No data available.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulations

##### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

##### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

##### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	aluminium powder (stabilised)	7429-90-5	231-072-3	75
2	CALCIUM-3-HYDROXY-4-[4-METHYL-2-SULFONATOPHENYL)AZO]-2-NAPHTHOATE, C.I. 15850:1 PIGMENT RED 57:1	5281-04-9	226-109-5	75
3	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5	75

##### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category: P5b

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### SECTION 16: Other information

#### **Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

**Trade name:** edding Paint Marker Ink (violet metallic) contained in: edding 751, edding 780

**Current version :** 3.1.0, issued: 14.06.2022

**Replaced version:** 3.0.0, issued: 22.09.2021

**Region:** GB

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.  
The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H228	Flammable solid.
H261	In contact with water releases flammable gases.
H304	May be fatal if swallowed and enters airways.
H351i	Suspected of causing cancer by inhalation.

**Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)**

P	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
T	This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
V	If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
W	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.
1	The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

**Creation of the safety data sheet**

UMCO GmbH  
Georg-Wilhelm-Str. 187, D-21107 Hamburg  
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.  
The safety data sheet describes products with a view to safety requirements.  
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:  
Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.  
Prod-ID 629306