

Trade name: edding 8200 grout marker (silvergrey)

Current version : 4.0.0, issued: 16.04.2020

Replaced version: 3.0.0, issued: 10.11.2019

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding 8200 grout marker (silvergrey)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Tile-Joint Marker

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

-

Signal word

-

Hazard statement(s)

-

Hazard statements (EU)

EUH208 Contains 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Precautionary statement(s)

-

Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

2.3 Other hazards

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB

No data available.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Chemical characterization**

Mixture (preparation)

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	poly(propene oxide)		
	25322-69-4 500-039-8 - -	Acute Tox. 4; H302	< 5.00 %-b.w.
2	2-phenoxyethanol		
	122-99-6 204-589-7 603-098-00-9 01-2119488943-21	Acute Tox. 4; H302 Eye Irrit. 2; H319	< 2.50 %-b.w.
3	2-methyl-2H-isothiazol-3-one		
	2682-20-4 220-239-6 613-326-00-9 -	Acute Tox. 2; H330 Acute Tox. 3; H301 Acute Tox. 3; H311 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1B; H314 Skin Sens. 1A; H317	< 0.10 %-b.w.
4	titanium dioxide		
	13463-67-7 236-675-5 - 01-2119489379-17-0231	-	>= 10.00 - < 25.00 %-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	-	Skin Sens. 1A; H317: C >= 0.0015%	M = 10	M = 1

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off immediately with copious amounts of water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

Trade name: edding 8200 grout marker (silvergrey)

Current version : 4.0.0, issued: 16.04.2020

Replaced version: 3.0.0, issued: 10.11.2019

Region: GB

After ingestion

Rinse mouth thoroughly with water. Call a doctor immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide; Extinguishing powder; Foam; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition. Take precautionary measures against static charges.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep from freezing.

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB**Requirements for storage rooms and vessels**

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original. Keep container tightly closed.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	titanium dioxide	13463-67-7	236-675-5
List of approved workplace exposure limits (WELs) / EH40			
	Titanium dioxide		
	total inhalable dust		
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
	Titanium dioxide		
	respirable dust		
	WEL long-term (8-hr TWA reference period)	4	mg/m ³

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	2-phenoxyethanol			122-99-6 204-589-7
	dermal	Long term (chronic)	systemic	34.72 mg/kg/day
	inhalative	Long term (chronic)	systemic	8.07 mg/m ³
	inhalative	Long term (chronic)	local	8.07 mg/m ³

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	2-phenoxyethanol			122-99-6 204-589-7
	oral	Long term (chronic)	systemic	17.43 mg/kg/day
	oral	Short term (acute)	systemic	17.43 mg/kg/day
	dermal	Long term (chronic)	systemic	20.83 mg/kg/day
	inhalative	Long term (chronic)	systemic	2.41 mg/m ³
	inhalative	Long term (chronic)	local	2.41 mg/m ³

PNEC values

No	Substance name	CAS / EC no		
	ecological compartment	Type	Value	
1	2-phenoxyethanol			122-99-6 204-589-7
	water	fresh water	0.943	mg/L
	water	marine water	0.0943	mg/L
	water	Aqua intermittent	3.44	mg/L
	water	fresh water sediment	7.2366	mg/kg
	with reference to: dry weight			
	water	marine water sediment	0.7237	mg/L
	with reference to: dry weight			
	soil	-	1.26	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	24.8	mg/L

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB**8.2 Exposure controls****Appropriate engineering controls**

No data available.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form/Colour			
liquid			
silver-grey			
Odour			
mild			
Odour threshold			
No data available			
pH value			
Value	7 - 9		
Boiling point / boiling range			
Value	> 90 °C		
Source	Manufacturer		
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
Value	> 90 °C		
Auto-ignition temperature			
No data available			
Oxidising properties			
No data available			
Explosive properties			
not explosive			
Flammability (solid, gas)			

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB

No data available				
Lower flammability or explosive limits				
No data available				
Upper flammability or explosive limits				
No data available				
Vapour pressure				
No data available				
Vapour density				
No data available				
Evaporation rate				
No data available				
Relative density				
No data available				
Density				
Value	1.0	-	1.2	kg/l
Reference temperature			20	°C
Source	Manufacturer			
Solubility in water				
Comments	miscible			
Solubility(ies)				
No data available				
Partition coefficient: n-octanol/water				
No	Substance name	CAS no.		EC no.
1	2-phenoxyethanol	122-99-6		204-589-7
log Pow			1.2	
Reference temperature			23	°C
Method	EU Method A.8			
Source	ECHA			
Viscosity				
Value	33.5	-	43.5	mPa*s
Reference temperature			25	°C
Type	dynamic			
Method	Brookfield			
Source	Manufacturer			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

No data available.

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB**10.6 Hazardous decomposition products**

No data available.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding 8200 grout marker (silvergrey)
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
LD50		1840	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity	
No data available	

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
LC50	>	1.0	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 412		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	Irritating to eyes		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB

Germ cell mutagenicity			
No data available			
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Carcinogenicity			
No data available			
STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Aspiration hazard			
No data available			

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
LC50		344	mg/l
Duration of exposure		96	h
Species		Pimephales promelas	
Method		ASTM	
Source		ECHA	

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
NOEC		23	mg/l
Duration of exposure		34	day(s)
Species		Pimephales promelas	
Method		OECD 210	
Source		ECHA	

Toxicity to Daphnia (acute)				
No	Substance name	CAS no.	EC no.	
1	2-phenoxyethanol	122-99-6	204-589-7	
EC50		>	500	mg/l
Duration of exposure			48	h
Species		Daphnia magna		
Method		OECD 202		
Source		ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
NOEC		9.43	mg/l
Duration of exposure		21	day(s)
Species		Daphnia magna	
Method		OECD 211	
Source		ECHA	

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
EC50	>	500	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	DIN 38412 T.9		
Source	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
Value	>	90	%
Duration		15	day(s)
Method	OECD 301 A		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	2-phenoxyethanol	122-99-6	204-589-7
log Pow		1.2	
Reference temperature		23	°C
Method	EU Method A.8		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information	
Do not discharge product unmonitored into the environment.	

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

The product is not subject to ADR/RID/ADN regulations.

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB**14.2 Transport IMDG**

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
EU regulations**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances requiring authorisation as listed on Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	1.35	%
-------------	------	---

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.

Trade name: edding 8200 grout marker (silvergrey)**Current version :** 4.0.0, issued: 16.04.2020**Replaced version:** 3.0.0, issued: 10.11.2019**Region:** GB

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 626442