

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding Permanent Industriemarker Ink (red) contained in: edding 8300

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H312

Acute Tox. 4; H332

Flam. Liq. 3; H226

Skin Irrit. 2; H315

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Warning

Hazardous component(s) to be indicated on label:

m-xylene

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

Hazard statement(s)

H226 Flammable liquid and vapour.
H312+H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	m-xylene		
	108-38-3 203-576-3 601-022-00-9 -	Acute Tox. 4*; H312 Acute Tox. 4*; H332 Flam. Liq. 3; H226 Skin Irrit. 2; H315	>= 70.00 - < 90.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16
(*, **, ***, ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures
4.1 Description of first aid measures
General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300**Current version :** 5.0.0, issued: 26.07.2021**Replaced version:** 4.0.0, issued: 14.04.2021**Region:** GB**After ingestion**

Rinse the mouth thoroughly with water. Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

None known

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	m-xylene	108-38-3	203-576-3
	2000/39/EC		
	m-Xylene		
	WEL short-term (15 min reference period)	442	mg/m ³ 100 ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	Xylene, o-, m-, p- or mixed isomers		
	WEL short-term (15 min reference period)	441	mg/m ³ 100 ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m ³ 50 ppm
	Comments	Sk, BMGV	
2	2-methylpropan-1-ol	78-83-1	201-148-0
	List of approved workplace exposure limits (WELs) / EH40		
	2-Methylpropan-1-ol		
	WEL short-term (15 min reference period)	231	mg/m ³ 75 ppm
	WEL long-term (8-hr TWA reference period)	154	mg/m ³ 50 ppm

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation		
liquid		
Form/Colour		
liquid		
red		
Odour		
solvent-like		
pH value		
No data available		
Boiling point / boiling range		
Value	139	°C
Reference substance	CAS 108-38-3	
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Value	27	°C
Ignition temperature		
No data available		
Flammability		
No data available		
Lower explosion limit		
Value	1.1	% vol
Reference substance	CAS 108-38-3	
Upper explosion limit		
Value	7.0	% vol
Reference substance	CAS 108-38-3	
Vapour pressure		
Value	5	mm Hg
Reference temperature	20	°C
Reference substance	CAS 108-38-3	
Relative vapour density		
No data available		
Relative density		
No data available		
Density		
Value	0.9	g/cm³
Solubility in water		
Comments	insoluble	
Solubility		
No data available		
Partition coefficient n-octanol/water (log value)		
No data available		

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

Viscosity			
No data available			
Solvent content			
Value	73	- 75	%
Value			%
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	m-xylene	108-38-3	203-576-3
LD50		5011	mg/kg bodyweight
Species	rat		
Source	Manufacturer		

Acute dermal toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	edding Permanent Industriemarker Ink (red) contained in: edding 8300		
ATE (Mixture)	1466.67	mg/kg	
Method	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.		

Acute dermal toxicity			
No data available			

Acute inhalational toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	edding Permanent Industriemarker Ink (red) contained in: edding 8300		
ATE (Mixture)	14.6667	mg/l	
Route of exposure / physical form	Vapour		
Method	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.		

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

Acute inhalational toxicity
No data available
Skin corrosion/irritation
No data available
Serious eye damage/irritation
No data available
Respiratory or skin sensitisation
No data available
Germ cell mutagenicity
No data available
Reproduction toxicity
No data available
Carcinogenicity
No data available
STOT - single exposure
No data available
STOT - repeated exposure
No data available
Aspiration hazard
No data available
Delayed and immediate effects as well as chronic effects from short and long-term exposure
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)
No data available
Toxicity to fish (chronic)
No data available
Toxicity to Daphnia (acute)
No data available
Toxicity to Daphnia (chronic)
No data available
Toxicity to algae (acute)
No data available
Toxicity to algae (chronic)
No data available
Bacteria toxicity
No data available

12.2 Persistence and degradability

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information
Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information
14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulations
Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information
Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
---	--

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Trade name: edding Permanent Industriemarker Ink (red) contained in: edding 8300

Current version : 5.0.0, issued: 26.07.2021

Replaced version: 4.0.0, issued: 14.04.2021

Region: GB

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 25063