

MATERIAL SAFETY DATA SHEET

[MSDS NO.AX7002A-000]

PRODUCT: X stamper PRE-INKED RUBBER STAMPS
CX-AN, CX-BN, CX-BN(2),
CE-16N,CE-9,CE-6,CA-2N,CA-2N(2),CA-13
(All colours)

Issue Date Jan.5,2007

Not classified as Hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

JAPAN:

SUPPLIER NAME : Shachihata Inc.
ADDRESS : 4-69,Amazuka-chou,Nishi-ku,Nagoya,451-0021,Japan
TELEPHONE NUMBER : ++81 52 521 3600
FAX NUMBER : ++81 52 521 3899

AUSTRALIA:

AGENT : Pelikan Artline Pty Limited.
ABN : 51 084 958 556
ADDRESS : 2 Coronation Avenue,Kings Park,
Blacktown Business Centre, NSW 2148
TELEPHONE NO : 02-9674-0900
FAX NO : 02-9674-0910
EMERGENCY PHONE NUMBER : 02-9674-0900 or Mobile:0419-206-163

IDENTIFICATION

Product Name : X stamper
Ship Name (CSN) : non hazardous
Other Names : -
UN No. : n/a **D.G.CLASS :** n/a **PACK. GRP :** n/a
HAZCHEM : n/a **SUB. RISK :** No Data **SUSDP :** Not Scheduled
PRODUCT USE : PRE-INKED RUBBER STAMPS

PHYSICAL DATA (INK)

APPEARANCE AND ODOUR Liquid, solvent odour.
BOILING POINT No data available
MELTING POINT n/a
VAPOUR PRESSURE n/a
VOLATILE (wt.%) 5~10
DENSITY(g/cm3) 1.0
FLASH POINT 40 °C(closed cup)
FLAMMABILITY LIMITS no data
REL. VAPOUR DENSITY no data

INGREDIENTS (INK)

CHEMICAL OR COMMON NAME(S)	CAS NO.	INGREDIENTS(wt.%)
Ethanol	64-17-5	5~15

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

ACUTE EFFECTS

SWALLOWED :

Not applicable

EYE :

A moderate eye irritant.
May cause watering of eyes.
High concentrations of vapors will cause irritation.

SKIN :

Contact with skin may result in irritation.
Repeated or prolonged skin contact may lead to dermatitic effects.
Will have a degreasing action on the skin.

INHALED :

Toxic by inhalation.
The vapor is an irritant to the mucous membranes and respiratory tract.
Inhalation of vapor can result in headaches, dizziness and possible nausea.
Possible CNS effects.

CHRONIC EFFECTS

Possible liver and kidney disorders.
Repeated or prolonged skin contact can cause chronic dermatitis.

FIRST AID

SWALLOWED :

Not applicable

EYE CONTACT :

Immediately flush with plenty of water.
Seek medical advice immediately.

SKIN CONTACT :

Wipe off with dry cloth and wash with mild soap.
Seek medical advice immediately.

INHALATION :

Move to well ventilated place.
Seek medical advice immediately.

FIRST AID FACILITIES :

No Data

ADVICE TO DOCTOR

Treat symptomatically.

ACUTE TOXICITY (RTECS):

(Ethanol)

Oral	LD ₅₀ (rat)	7,060mg/Kg
Inhalation	LC ₅₀ (rat)	20,000ppm/10H

PRECAUTIONS FOR USE

EXPOSURE CONTROL PARAMETERS :

[Ethanol]

ACGIH TLV (1990-91) TWA 1000ppm(1880mg/m³)

OSHA PEL(1993) 1000ppm(1990mg/m³)

ENGINEERING CONTROLS :

Not required.

Maintain concentration below recommended exposure limit.

Vapor heavier than air.

Keep stock in a well ventilated area.

PERSONAL PROTECTION

Not required.

Avoid skin and eye contact.

Do not smoke.

Remove any naked lights or strong heat sources.

FLAMMABILITY

Vapors are flammable, may form explosive mixtures with air.

While in use, keep away from heat, sparks or naked flames.

Heating may cause explosion.

ENVIRONMENT :

Not applicable

OTHER PRECAUTIONS :

Keep away from oxidizing agents, peroxides, acids, acid chlorides, acid anhydrides, alkali metals and ammonia.

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT

Store in a cool, dry location.

SPILLS AND DISPOSAL :

Disposal as usual industrial waste goods, follow all regulations in your country.

FIRE /EXPLOSION HAZARD

Extinguish fire with the following:

Use water fog.

OTHER SAFE HANDLING INFORMATION

OTHER INFORMATION

Risk Statement: n/a

Safety statement: S23 Do not breathe fumes

REFERENCES :

N.IRVING Sax and RICHARD J. LEWIS, SR, "Dangerous Properties of industrial Materials Seventh Edition", Van Nostrand Reinhold (1989).
REGISTRY OF TOXIC EFFECTS IF CHEMICAL SUBSTANCES 1985-86 Edition

Contact Point : Mr. C Watt , Product Manager , Phone(02-9674-0900) Fax(02-9674-0910)

IMPORTANT ADVICE :

This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace.

Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products.

If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact the supplier. Our responsibility for products sold is subject to our standard terms and conditions.