

Product: DURACELL LITHIUM MANGANESE DIOXIDE COIN BATTERIES

Date / revised: 20/05/99 Revision: 1

1. Substance/preparation and company name

Duracell Lithium Manganese Dioxide Coin Batteries: 3V: DL1616; DL1620; DL2016; DL2025; DL2430; DL2450; DL2032

Company: Country contact numbers:

Duracell Batteries Ltd. Austria: 02236 645240 Netherlands: 070 4131 800 c/o Gillette U.K. Ltd. Belgium: 02 711 9102 Norway: 022 72 8810 **Great West Road** Denmark: 33 26 9100 Portugal: 011 7210950 Finland: 09 452 8737 Isleworth, Middlesex Spain: 091 387 9600 TW75NP France: 01 47 48 70 00 Sweden: 08 6292700 UK Germany: 02 21 59670 Switzerland: 017 55 62 42

Italy: 02 66 7811 United Kingdom: 0181 560 1234

Page 1 of 4

GMEL # 1500E

2. Composition/information on ingredients

Chemical nature:	<u>Wt. %</u>	CAS No.	EEC No.	Index No.	<u>Classification</u>
Manganese Dioxide	65-75	1313-13-9	215-202-6	025-001-00-3	Xn, R20/22
Propylene Carbonate	10-15	108-32-7	203-572-1	607-194-00-1	Xi; R36; S2
Lithium	5-10	7439-93-2	231-102-5	003-001-00-4	F; C; R14/15/34; S1/2
1,2-Dimethoxyethane	1-10	110-71-4	203-794-9	603-031-00-3	Xn; R10/19/20; S2/24/25

3. Possible hazards

Critical hazards to man: If battery leaking, exposure to harmful ingredients may occur.

Critical hazards to the environment: Not applicable

Other Information: Keep batteries away from small children.

4. First aid measures

General advice: These chemicals and metals are contained in a sealed can. For consumer use, adequate hazard warnings are included on both the package and on the battery. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused.

If inhaled: Not anticipated. Respiratory (and eye) irritation may occur if fumes are released due to heat or an abundance of leaking batteries. Remove to fresh air. Contact physician if irritation persists.

On skin contact: Not anticipated. Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. Irrigate exposed skin with copious amounts of clear, tepid water for at least 15 minutes. If irritation, injury or pain persists, consult a physician.

On contact with eyes: Not anticipated. Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. It battery is leaking and material contacts eyes, flush with copious amounts of clear, tepid water for 30 minutes. Contact physician at once.

Product: DURACELL LITHIUM MANGANESE DIOXIDE COIN BATTERIES

Date / revised: 20/05/99 Revision: 1

4. First aid measures (continued)

On ingestion: An initial x-ray should be obtained promptly to determine battery location. Batteries lodged in the esophagus should be removed immediately since leakage, burns and perforation can occur as soon as 4-6 hours after ingestion. Irritation to the internal/external mouth areas may occur following exposure to a leaking battery.

Notes to Physician: 1) Potential leakage of less than 50 milligrams of propylene carbonate (CAS#108-32-1) and 1,2-dimethoxyethane (CAS#110-71-4).

- 2) 1,2-dimethoxyethane readily evaporates.
- 3) Under certain misuse conditions and by abusively opening the battery, exposed lithium can react with water or moisture in the air causing potential thermal burns or fire hazard.

5. Fire fighting measures

Suitable extinguishing media: As appropriate for surrounding area.

Special protective equipment: In fires involving large quantities of product, use self-contained breathing

apparatus and full protective clothing.

Further information: Hazardous decomposition products may be produced. (Sec. 10).

6. Accidental release measures

Personal precautions: Notify safety personnel of large spills. Increase ventilation. Avoid eye or skin contact. **DO NOT** inhale vapours. Clean-up personnel should wear appropriate protective gear.

Remove spilled liquid with absorbent and contain for disposal.

Environmental precautions: Not applicable

Methods for cleaning up: Not applicable

7. Handling and storage

Handling

Avoid mechanical or electrical abuse. **DO NOT** short or install incorrectly. Batteries may explode, pyrolize or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Replace all batteries in equipment at the same time. Do not carry batteries loose in pocket or bag.

Storage

Store at room temperature.

8. Exposure controls and personal protection

8-Hour TWAs: Manganese Dioxide (as Mn) - 5 mg/m³ (U.K.), (Ceiling) (OSHA); 0.2 mg/m³ (ACGIH/Duracell)

1,2-Dimethoxyethane - 0.15 ppm (Duracell)

Graphite - 15 mg/m³ (Dust); 5 mg/m³ (Respirable) (OSHA); 2 mg/m³ (ACGIH)

These levels are not anticipated under normal consumer use conditions.

Page 2 of 4 GMEL # 1500E

Product: DURACELL LITHIUM MANGANESE DIOXIDE COIN BATTERIES

Date / revised: 20/05/99 Revision: 1

Page 3 of 4

GMEL # 1500E

8. Exposure controls and personal protection (continued)

Personal protective equipment

Respiratory equipment: None required under normal use conditions.

Hand protection: None required under normal use conditions. Use butyl gloves when handling leaking

batteries.

Eye protection: None required under normal use conditions. Wear safety glasses when handling leaking

batteries.

General safety and hygiene measures: Use only as directed.

9. Physical and chemical properties

Form and Colour: Button cells. Contents dark in colour.

Odour: Not applicable

Change in physical state

Melting point/melting range: Not available Boiling point/boiling range: Not available

Flash point: Not applicable

Explosion limits: Not available

Ignition temperature: Not available

Vapour pressure: Not available

Specific Gravity: Not available

% Volatiles: Not available

Solubility in water: Not applicable

Solubility in other solvents: Not applicable

pH value: Not applicable

Octanol/water partition coefficient (log POW): Not available

Viscosity: Not available

10. Stability and reactivity

Thermal decomposition: Batteries may burst and release hazardous decomposition products when exposed

to a fire situation.

Substance(s) to avoid: Strong oxidisers

Hazardous reactions: Contents incompatible with strong oxidising agents.

Hazardous decomposition products: Thermal degradation may produce hazardous fumes of manganese

and lithium; oxides of carbon and other toxic by-products.

Product: DURACELL LITHIUM MANGANESE DIOXIDE COIN BATTERIES

Date / revised: 20/05/99 Revision: 1

11. Toxicological information

Toxicity information is available on the battery ingredients noted in Section 2, but, generally not applicable to intact batteries.

Page 4 of 4

GMEL #1500E

Chronic Health Effects: Not applicable to intact batteries.

12. Ecological information

None available regarding product.

13. Disposal considerations

Product: Dispose of in accordance with local regulations. If in doubt, contact your national Gillette office for

information.

14. Transport information

UN Number: None IMO Classification: None ADR Classification: None IATA Classification: None

These batteries are not regulated by U. S. DOT or international agencies as hazardous materials or dangerous goods when shipped. A shipping name of 'Alkaline Batteries - Non-hazardous' may be used on all domestic and international bills of lading.

15. Regulatory information

EC Labeling: None Risk Phrases: None Safety Phrases: None

Labeling is not required because batteries are classified as "articles" under the Dangerous Preparations Directive and as such are exempt from the requirements of the Directive.

16. Other information:

Preparation of MSDS:

Prepared by: Gillette Medical Evaluation Laboratories **Phone Number:** Date: 20/05/99 37 A Street 781.292.8151 Revision: 1

Needham, MA 02492 USA Replaces: 1354E

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.