PRODUCT DATASHEET


NiMH Battery Charger (CHDC7)

Compact Charger

North American Region Download Instructions and Warranty Information

English | Français | Español

Product Detail:



Color: Black and Silver

Charging Capability: 2 or 4 "AA" NiMH Batteries

2 or 4 "AAA" NiMH Batteries

2 "AA" and 2 "AAA" NiMH Batteries

Charging Current: "AA" 450 mAx2

"AAA" 450 mAx2

Trickle Charge: 50mA

Charging Times: (estimated)

| Battery | Capacity | Estimated | (NiMH) | (mAh) | (time) | |
| AA | 1300-2000 | 4-5 hrs | |
| AAA | 2100-2500 | 6.5 hrs | |
| AAA | 850-900 | 2-3 hrs |

Weight: 112 grams (4.0 oz.) **Dimensions (mm)**: 86 x 82 x 33 (H x L x W)

Charger Input: 100-240VAC Charger Output: 2.8VDC

Shutoff Mechanism: Delta V and Timer Control

Max Timer Control 8.0 Hours


Safety Features: Reverse Polarity Protection

Delta V Charging Cut Off

Safety Timer to Prevent Over Charge

Primary (non-rechargeable) Battery Detection

COMPACT





- No cords
- Space saving foldable plug design

FEATURE PACKED

- Battery reversal protection
- Delta V and Timer controlled
- Charge status indicators

UNIVERSAL

- 100-240VAC
- 50/60Hz





Before Using Your Charger:

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with Energizer NiMH batteries.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

© Energizer Holdings, Inc.
Contents herein do not constitute a warranty.