SAFETY DATA SHEET

1. Identification

Product identifier HP Color LaserJet CF470X-XC Black Print Cartridge

Other means of identification Not available.

Recommended use This product is a black toner preparation that is used in HP Color LaserJet LJ M652 / HP Color

LaserJet M681 / HP Color LaserJet LJ M653 / HP Color LaserJet M682 series printers.

Recommended restrictions Company identification

None known.

HP Inc.

1501 Page Mill Road

Palo Alto, CA 94304-1112

United States

Telephone 650-857-5020

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209

(Direct) 1-760-710-0048 HP Inc. Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None. Signal word None.

Hazard statement Not available.

Precautionary statement

PreventionNot available.ResponseNot available.StorageNot available.DisposalNot available.

Hazard(s) not otherwise

classified (HNOC)

Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present

this carcinogenic risk. None of the other ingredients in this preparation are classified as

carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

Supplemental information This product is not classified as hazardous according to OSHA CFR 1910.1200 (HazCom 2012).

3. Composition/information on ingredients

Mixtures

| Chemical name Common name and synonyms | | <u> </u> | |
|--|--------------|---|--|
| | Trade Secret | <85 | |
| | 1333-86-4 | <10 | |
| Wax | Trade Secret | <10 | |
| Amorphous silica | 7631-86-9 | <3 | |
| | 13463-67-7 | <1 | |
| | Wax | Trade Secret 1333-86-4 Wax Trade Secret Amorphous silica 7631-86-9 | |

Material name: CF470X-XC SDS US

4. First-aid measures

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

Most important

symptoms/effects, acute and

delayed

Not available.

5. Fire-fighting measures

Suitable extinguishing media

None known.

CO2, water, or dry chemical

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment

and precautions for

firefighters

Not available.

Fire-fighting

equipment/instructions

If fire occurs in the printer, treat as an electrical fire.

Specific methods None established.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Minimize dust generation and accumulation.

Methods and materials for containment and cleaning up Not available.

Environmental precautions

Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.

7. Handling and storage

Precautions for safe handling

Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Conditions for safe storage, including any

incompatibilities

Keep out of the reach of children. Keep tightly closed and dry. Store at room temperature. Store away from strong oxidizers.

8. Exposure controls/personal protection

Occupational exposure limits

13463-67-7)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Туре | Value | Form |
|---|------|-----------|---------------------|
| Carbon black (CAS 1333-86-4) | PEL | 3.5 mg/m3 | |
| Titanium dioxide (CAS 13463-67-7) | PEL | 15 mg/m3 | Total dust. |
| US. ACGIH Threshold Limit Values | | | |
| Components | Туре | Value | Form |
| Carbon black (CAS 1333-86-4) | TWA | 3 mg/m3 | Inhalable fraction. |
| Titanium dioxide (CAS | TWA | 10 mg/m3 | |

Material name: CF470X-XC SDS US

US. NIOSH: Pocket Guide to Chemical Hazards Components **Type**

Amorphous silica (CAS **TWA** 6 mg/m3 7631-86-9)

Carbon black (CAS **TWA** 0.1 mg/m3

1333-86-4)

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

Value

mg/m3

TRGS 900 (Luftgrenzwert) - 10 mg/m3 (Einatembare partikel), 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust), 5 mg/m3 (Inhalable Dust)

Appropriate engineering

Use in a well ventilated area.

controls

Individual protection measures, such as personal protective equipment

Eye/face protection Not available.

Skin protection

Hand protection Not available. Other Not available. Respiratory protection Not available. Thermal hazards Not available.

9. Physical and chemical properties

Appearance Fine powder **Physical state** Solid. Color Black.

Odor Slight plastic odor **Odor threshold** Not available. Not applicable Melting point/freezing point Not available. Initial boiling point and Not applicable

boiling range

Flash point Not applicable **Evaporation rate** Not applicable Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not flammable

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

Not available.

(%)

Not available.

Explosive limit - upper (%)

Not applicable

Vapor pressure Solubility(ies)

> Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient Not available.

(n-octanol/water)

Material name: CF470X-XC SDS US

Auto-ignition temperature Not applicable **Decomposition temperature** > 392 °F (> 200 °C)

Viscosity

Not applicable

Other information

Percent volatile 0 % estimated

Softening point 176 - 266 °F (80 - 130 °C)

Specific gravity 1 - 1.2

10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable under normal storage conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid

Imaging Drum: Exposure to light

Incompatible materials Strong oxidizers

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Respiratory sensitization Based on available data, the classification criteria are not met. Skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

> Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans. Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicity Based on available data, the classification criteria are not met. Specific target organ toxicity Based on available data, the classification criteria are not met.

- single exposure

Specific target organ toxicity

- repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met. **Further information** Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

Material name: CF470X-XC SDS US

| Components | Species | Test Results | |
|--------------------------|----------|---------------|--|
| Amorphous silica (CAS 76 | 31-86-9) | | |
| Acute | | | |
| Oral | | | |
| LD50 | Mouse | > 15000 mg/kg | |
| | Rat | > 22500 mg/kg | |
| Carbon black (CAS 1333-8 | 36-4) | | |
| Acute | | | |
| Oral | | | |
| LD50 | Rat | > 8000 mg/kg | |

12. Ecological information

Ecotoxicity

| Product | | Species | Test Results |
|-------------------------------|----------------|-----------------------------------|-----------------------|
| CF470X-XC | | | |
| Aquatic | | | |
| Algae | ErC50 | Algae | > 100 mg/l, 72 Hours |
| Crustacea | EC50 | Crustacea | > 100 mg/l, 48 Hours |
| Fish | LC50 | Fish | > 100 mg/l, 96 Hours |
| Components | | Species | Test Results |
| Titanium dioxide (CAS 13463-6 | 67-7) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | > 1000 mg/l, 48 hours |
| Fish | LC50 | Mummichog (Fundulus heteroclitus) | > 1000 mg/l, 96 hours |
| rsistence and degradability | Not available. | | |
| accumulative potential | Not available. | | |
| bility in soil | Not available. | | |
| ner adverse effects | Not available. | | |

13. Disposal considerations

Disposal instructions

Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

14. Transport information

Further information Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

15. Regulatory information

under TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US federal regulations

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: CF470X-XC

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

Safe Drinking Water Act

Other federal regulations

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Amorphous silica (CAS 7631-86-9) Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous silica (CAS 7631-86-9) Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (AIRBORNE, UNBOUND PARTICLES Listed: February 21, 2003

OF RESPIRABLE SIZE [<= 10 MICROMETERS]) (CAS

1333-86-4)

TITANIUM DIOXIDE (AIRBORNE, UNBOUND Listed: September 2, 2011

PARTICLES OF RESPIRABLE SIZE) (CAS 13463-67-7)

Regulatory information All chemical substances in this HP product have been notified or are exempt from notification under

chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and

China.

16. Other information, including date of preparation or last revision

Issue date 24-Mar-2017

Version # 01

Disclaimer This Safety Data Sheet document is provided without charge to customers of HP. Data is the most

current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other

countries.

Manufacturer information HP Inc.

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Material name: CF470X-XC SDS US

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act VOC Volatile Organic Compounds

Material name: CF470X-XC SDS US 7/7