



MATERIAL SAFETY DATA SHEET
IBM, 3930 DEVELOPER UNIT: P/N 70X7441

Lexmark International, Inc.
740 New Circle Rd. NW
Lexington, Kentucky 40550-1876 Information: 1-606-232-3000

Revision Date: 3/10/98

Emergency: 1-606-232-3333

SECTION 1 - CHEMICAL PRODUCTS & COMPANY IDENTIFICATION

Name: IBM, 3930 Developer Unit

Part Number: 70X7441

Chemical Family: Developer

Product Use: Electrophotography; container of developer for exclusive use in IBM 3930 Printer.

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	PERCENT (wt.)	CAS#	OSHA PEL	ACGIH TLV
TONER	4.5 - 6.5			
Polyester Resin - Trade Secret	87 - 93	(1)	(2)	(2)
Carbon Black	5 - 7	1333-86-4	3.5 mg/m ³	3.5 mg/m ³
Wax	1 - 3	9003-07-0	(2)	(2)
Pigment	0.5 - 2.0	31714-55-3	(2)	(2)
Magnetite	2 - 4	1309-38-2	(2)	(2)
Amorphous Silica	0.5 - 2.0	68611-44-9	(2)	(2)
CARRIER	93.5 - 95.5			
Copper - Zinc Ferrite Core	< 99			
Iron Oxide	approx. 70	1309-37-1	10 mg/m ³	5 mg/m ³ (3)
Copper Oxide	approx. 11	1317-38-0	(2)	(2)
Zinc Oxide	approx. 19	1314-13-2	15 mg/m ³ (4) 5 mg/m ³ (5)	10 mg/m ³ (4)
Coated Resin	> 1			
Silicone Resin		123127-08-2	(2)	(2)

- Notes:**
- (1) TSCA Confidential
 - (2) Specific work place exposure limits have not been established.
 - (3) Total particulate, as Fe
 - (4) Total dust
 - (5) Respirable dust

SECTION 3 - HAZARDS IDENTIFICATION

Primary Routes of Entry: Inhalation of dust, skin contact.

Signs and Symptoms of Exposure: Developer on skin or mucus membranes (mouth & nose).

Medical Conditions Aggravated by Exposure: None known at intended levels of use.

Exposures to high airborne dust concentrations, including toner, may aggravate existing respiratory conditions.

Physical Hazards: As with most finely divided dusts, explosion is possible when extremely high concentrations of dust and an ignition source are present. Not a hazard when using adequate workplace controls.

POTENTIAL HEALTH EFFECTS:

- Inhalation:** Short Term Exposure - Testing and/or information on this or similar toners, or on the constituents of this toner indicate low inhalation toxicity. As with exposure to high concentrations of any dust, minimal respiratory tract irritation may occur if excessive amounts of toner dust are inhaled.
- Long Term Exposure - No adverse chronic effects known at intended level of use. Exposure not probable with intended use.
- Skin Contact:** Short Term Exposure - Test data from this or similar toner materials indicate this toner is not a skin irritant and is of low dermal toxicity.
- Long Term Exposure - Rare individuals may note skin rash with repeated contact. Exposure not probable with intended use.
- Eye Contact:** Short Term Exposure - Toner may act as a mechanical irritant.
- Long Term Exposure - No adverse chronic effects known. Exposure not probable with intended use.
- Ingestion:** Short Term Exposure - Testing and/or information on this or similar toners, or on the constituents of this toner indicate low oral toxicity. Exposure not probable with intended use.
- Long Term Exposure - No adverse chronic effects known. Exposure not probable with intended use.

SECTION 4 - FIRST AID MEASURES

Inhalation: If symptoms, such as shortness of breath or persistent coughing are experienced, remove source of contamination and move individual to fresh air. If symptoms persist, seek medical attention.

Skin Contact: Wash affected area with soap and water. Should irritation occur, seek medical attention.

MATERIAL SAFETY DATA SHEET
IBM, 3930 DEVELOPER UNIT: P/N 70X7441

Eye Contact: Do not rub eyes. Flush immediately with plenty of water. Remove contact lenses and continue flushing for at least 15 minutes. Seek medical attention if irritation develops and persists.

Ingestion: If conscious, immediately wash mouth out with plenty of water. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: Not applicable

Autoignition: Not available

Extinguishing Media: CO₂, water spray or fog, dry chemical, or foam

Firefighting: NIOSH approved self contained breathing apparatus may be required.

Fire and Explosion Hazard: Like many finely divided materials, toner dust, in high concentrations can form an explosive mixture in air which, if ignited, could result in dust explosion.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, and low molecular weight organics.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Occupational Spill: If a dust cloud is possible due to a spill, remove all sources of ignition such as open sparks, flames or static discharge to prevent the ignition of the dust. Minimize dust generation during clean up. Sweep up spill with non-metallic broom and dust pan. To avoid possible dust explosion, do not use vacuum cleaners to cleanup spills. Contain for disposal. Oil permeated sweeping compound may assist in the cleanup of toner spilled on nonporous surfaces.

SECTION 7 - HANDLING AND STORAGE

Store in a cool dry place. Store away from oxidizing materials.

When handling, minimize generation of dust. Supply adequate ventilation.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

OSHA : 15 mg/m³ (total dust, particulates not otherwise regulated-PNOR)
5 mg/m³ (respirable dust, particulates not otherwise regulated-PNOR)
3.5 mg/m³ (total dust, measured as carbon black)

ACGIH : 10 mg/m³ (total dust, particulates not otherwise classified-PNOC)
3 mg/m³ (respirable dust, particulates not otherwise classified-PNOC)
3.5 mg/m³ (total dust, measured as carbon black)

MATERIAL SAFETY DATA SHEET
IBM, 3930 DEVELOPER UNIT: P/N 70X7441

Ventilation: Mechanical room ventilation

Eye Protection: None required for intended use in printer.

Protective Clothing: None required for intended use in printer.

Gloves: None required for intended use in printer.

Respirator: None required for intended use in printer.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Description: Fine black powdery odorless material

Pressurized: No

Vapor Pressure: Not available

Vapor Density (Air = 1): Not applicable

Melting Point: Approximately 1300 °C

Boiling Point: Not applicable

pH: Not applicable

Specific Gravity (H₂O = 1): 5.0

Evaporation Rate: Not applicable

Water Solubility: Negligible

% Volatility: Not applicable

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Combustible atmospheres of toner dust. Ignition sources, excessive heat, sparks and open flames.

Incompatibilities: Strong oxidizers; strong acids or alkali

Hazardous Decomposition: Carbon dioxide, carbon monoxide, and unidentified organics.

Hazardous Polymerization: This product will not polymerize.

SECTION 11 - TOXICOLOGY INFORMATION

Acute Toxicity: Not acutely toxic: LD₅₀ expected to be > 5000 mg/kg, based on data from similar toners.

Chronic Toxicity: Not expected to be toxic. Industry tests on similar generic toner showed no signs of overt toxicity. Rats exposed to high levels of toner showed a chronic inflammatory response and a mild to moderate degree of lung fibrosis. There were no pulmonary changes of any type at the lower toner exposure level, which is most relevant in regard to potential human exposures. Pure carbon black, a minor component of this toner, has been listed by IARC as a group 2B (possible carcinogen) based on rat "lung particulate overload" studies. Toner is not listed by IARC, NTP, or OSHA.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental impact rating (0-4): Not available

Acute Aquatic Toxicity: Not available

Degradability: Not available

Log Bioconcentration Factor (BCF): Not available

Log Octanol/Water Partition Coefficient: Not available

SECTION 13 - WASTE DISPOSAL INFORMATION

Dispose of in accordance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION INFORMATION

This product is not regulated as a hazardous material by the DOT.

SECTION 15 - REGULATORY INFORMATION

All ingredients are registered under the **Toxic Substances Control Act (TSCA)** or under polymer exemption.

None of the product ingredients is listed as **Emergency Planning and Community Right-to Know Act (EPCRA)- Section 302: Extremely Hazardous Substances (EHS)**.

None of the product ingredients has a final Reportable Quantity (RQ) under **EPCRA Title III - CERCLA Section 302**.

This material contains no ingredients which, if spilled or released in quantities equal to or greater than the Reportable Quantity (RQ), are subject to the reporting requirements of **CERCLA and/or EPCRA (40 CFR parts 302 and 355)**.

This product contains less than 12% of a copper compound. Copper compounds are subject to the reporting requirement of **Section 313 of Title III of EPCRA and 40 CFR Part 372**.

This product contains less than 20% of a zinc compound. Zinc compounds are subject to the reporting requirement of **Section 313 of Title III of EPCRA and 40 CFR Part 372**.

This product contains no known materials at levels which the State of California has found to cause cancer, birth defects or other reproductive harm - **California Proposition 65**.

This product contains a component (carbon black CAS# 1333-86-4) at a concentration above the MSL de minimus concentration - **Massachusetts Right to Know**.

This product contains a component (carbon black CAS# 1333-86-4) at a concentration above the de minimus concentration - **New Jersey Right to Know**.

This product contains a component (carbon black CAS# 1333-86-4) at a concentration above the de minimus concentration - **Pennsylvania Right to Know**.

SECTION 16 - OTHER

Disclaimer: Data are most current known to Lexmark at the time of preparation and are believed to be accurate. No warranty as to their accuracy or completeness is expressed or implied.

MATERIAL SAFETY DATA SHEET
IBM, 3930 DEVELOPER UNIT: P/N 70X7441