



SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

Product Name	: Cyan Toner for FS-C5300DN, C5350DN, ECOSYS P6030cdn
	(TK-560C)
Relevant identified uses	s: Toner for electrophotographic equipments
Manufacturer	
Name	: KYOCERA Document Solutions Inc.
Address	: 2-28, 1-Chome, Tamatsukuri, Chuo-ku Osaka 540-8585, Japan
Supplier	
Name	: KYOCERA Document Solutions Europe B.V.
Address	: Bloemlaan 4, 2132 NP Hoofddorp, The Netherlands
Telephone Number	: +31(0)20-6540000

2. HAZARDS IDENTIFICATION

Most Important Hazards : Not classified as dangerous. (Directive 1999/45/EC)

Specific Hazards : None

Other Information on Hazards: Potential Health Effects

Ingestion	: Use of this product as intended does not result in ingestion of toner.	
Inhalation	: Prolonged inhalation of excessive dusts may cause lung damage.	
	Use of this product as intended does not result in prolonged inhalation	
	of excessive toner dusts.	
Eye Contact	: May cause transient eye irritation.	
Skin Contact	: Unlikely to cause skin irritation.	

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Substance or Mixture ; Mixture

Ingredients;

Chemical Name(Common Name)	CAS No.	Weight %
Polyester resin (2 kinds)	Confidential	75-85
Organic pigment	Confidential	1-5
Amorphous silica	7631-86-9	1-5
Titanium dioxide	13463-67-7	< 1

Page 2 of 6 MSDS No.: TK560C-KDE-04 Issue date: April 1, 2012 Revision date: June 6, 2014

Information of Ingredients:

PBT or vPvB substance under Regulation (EC) No 1907/2006: None Substance listed in Candidate List of SVHC for Authorisation under Regulation (EC) No 1907/2006: None

4. FIRST-AID MEASURES

Inhalation	: Remove from exposure to fresh air and gargle with plenty of water.	
	Consult a doctor in case of such symptoms as coughing.	
Skin Contact	: Wash with soap and water.	
Eye Contact	: Flush with water immediately and see a doctor if irritating.	
Ingestion	: Rinse out the mouth. Drink one or two glasses of water to dilute.	
	Seek medical treatment if necessary.	

5. FIRE-FIGHTING MEASURES

Extinguishing Media	: Water (Sprinkle with Water), Foam, Powder, CO ₂ or Dry Chemical
	Extinguisher
Fire-Fighting Procedure	: Pay attention not to blow away toner powder. Drain water off around
	and decrease the atmosphere temperature to extinguish the fire.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions : Avoid inhalation, ingestion, eye and skin contact in case of accidental toner release.

Environmental Precautions: Do not release into drains and surface water.

Method for Cleaning Up : Gather the released toner not to blow away and wipe up with a wet cloth.

7. HANDLING AND STORAGE

Handling : Never open the toner container.

Storage: Keep the toner container tightly closed and store in a cool, dry and dark
place keeping away from fire. Keep away from children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters<Reference Data>:

ACGIH TLV₍₂₎-TWA : Inhalable fraction 10mg/m³, Respirable fraction 3mg/m³ Titanium dioxide 10mg/m³

OSHA PEL₍₃₎-TWA : Total dust 15mg/m³, Respirable fraction 5mg/m³

	Amorphous silica	80mg/m ³ /%SiO ₂	
	Titanium dioxide	15mg/m ³ (Total dust)	
DFG-MAK	: Inhalable fraction	4 mg/m ³	
	Amorphous silica	4mg/m ³ (Inhalable fraction)	
Protective Equipment	: Respiratory protection, eye protection, hand protection, skin and body		
	protection are not re	equired under normal use.	
Ventilation	: Ventilator is not required under normal use.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state:	Solid	Form: Fine powder	Color: Cyan	Odor: Odorless
рН	: Not applicable			
Melting Point	: 100-120 °C			
Explosion Properties	: Dust explosion is improbable under normal use.			
	Experimental explosiveness of toner is classified into the same rank			
	such kind of powder as flour, dry milk and resin powder according to			
	the pressure rising speed.			
Density	: 1.2-1.	4 g/cm ³		
Solubility	: Almost insoluble in water			

10. STABILITY AND REACTIVITY

Stability/ Reactivity : Stable under normal use. Hazardous Decomposition Products: None

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: (rat)LD ₅₀ >2,000mg/kg
	(Estimated from other products containing same materials.)
Acute dermal toxicity	: (rat)LD ₅₀ >2,000mg/kg
	(Estimated from Acute oral toxicity for same product.)
Acute inhalation toxicity	/ : (rat)LC ₅₀ (4hr) >4.98mg/l
	[This value is the maximum attainable concentration for dust.]
	(Estimated from other products containing same materials.)
Acute eye irritation	: (rabbit)Minimal irritant
	(Estimated from other products containing same materials.)
Acute skin irritation	: (rabbit)Mild irritant
	(Estimated from other products containing same materials.)

Page 4 of 6 MSDS No.: TK560C-KDE-04 Issue date: April 1, 2012 Revision date: June 6, 2014

Skin sensitisation : (mouse)Non-sensitiser

(Estimated from other products containing same materials.)

Mutagenicity : Ames Test is Negative.

(Estimated from the data of constituent materials.)

Information of Ingredients: No mutagen, according to MAK, TRGS905 and (EC)No 1272/2008 AnnexVI Table3.2.

Reproductive Toxicity:

Information of Ingredients: No reproductive toxicant, according to MAK, California Proposition 65, TRGS905 and (EC)No 1272/2008 AnnexVI Table3.2.

Carcinogenicity:

Information of Ingredients: No carcinogen or potential carcinogen, (except titanium dioxide) according to IARC, Japan Association on Industrial Health, ACGIH, EPA,OSHA,NTP, MAK, California Proposition 65, TRGS 905 and (EC)No 1272/2008 AnnexVI Table3.2.

The IARC reevaluated titanium dioxide as a Group 2B carcinogen (possibly carcinogenic to humans) as the result of inhalation exposure test in rats. But, oral/skin test does not show carcinogenicity. (4) In the animal chronic inhalation studies for titanium dioxide, the lung tumor was observed in only rats. It is estimated that this is attributed to the overload of rat's lung clearance mechanism (overload phenomenon). (5)

The inhalation of excessive titanium dioxide dose not occur in normal use of this product. Also, epidemiological studies to date have not revealed any evidence of the relation between occupational exposure to titanium dioxide and respiratory tract diseases. Chronic effects:

In a study in rats by chronic inhalation exposure to a typical toner, a mild to moderate degree of lung fibrosis was observed in 92% of the rats in the high concentration(16mg/m³) exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animal in the middle(4mg/m³) exposure group. (1) But no pulmonary change was reported in the lowest(1mg/m³) exposure group, the most relevant level to potential human exposures. Other information : None

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Do not attempt to incinerate the toner container or unit and the waste toner yourself. Dangerous sparks may cause burn. Any disposal practice should be done under conditions which meet local, state and federal laws and regulations relating to waste (contact local or state environmental agency for specific rules).

14. TRANSPORT INFORMATION

: None
: None
: None
: None
: None

15. REGULATORY INFORMATION

EU Information

Label information according to the Directives 67/548/EEC and 1999/45/EC.

Symbol and Indication	: Not required	
R-Phrase	: Not required	
S-Phrase	: Not required	
Special markings	: Not required	
Hazardous ingredients for labeling: None		

US Information

All ingredients in this product comply with order under TSCA.

16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, we cannot assume any liability whatsoever for the accuracy or completeness of the information contained herein.

<Reference>

- Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats H.Muhle et.al Fundamental and Applied Toxicology 17.280-299(1991)
 - Lung Clearance and Retention of Toner, Utilizing a Tracer Technique, during Chronic Inhalation Exposure in Rats B.Bellmann

Fundamental and Applied Toxicology 17.300-313(1991)

- (2) ACGIH TLV (Threshold Limit Values)
- (3) OSHA PEL (Permissible Exposure Limits)
- IARC Monograph on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, Vol.93
- (5) NIOSH CURRENT INTELLIGENCE BULLETIN "Evaluation of Health Hazard and

Page 6 of 6 MSDS No.: TK560C-KDE-04 Issue date: April 1, 2012 Revision date: June 6, 2014

Recommendation for Occupational Exposure to Titanium Dioxide DRAFT"

ISO 11014-1 Safety data sheet for chemical products

• Regulation (EC) No 1907/2006

<Abbreviation>

ACGIH : American Conference of Governmental Industrial Hygienists

2010 TLVs and BEIs (Threshold Limit Values for Chemical Substances and Physica Agents and Biological Exposure Indices)

OSHA : Occupational Safety and Health Administration (29 CFR Part1910 Subpart Z)

- TWA : Time Weighted Average
- IARC : International Agency for Research on Cancer

(IARC Monographs on the Evaluations of Carcinogenic Risks to Humans)

EPA: Environmental Protection Agency (Integrated Risk Information System) (USA)

NTP: National Toxicology Program (Report on Carcinogens) (USA)

MAK: Maximale Arbeitsplatz-Konzentrationen (List of MAK and BAT Values 2011)

(DFG: Deutsche Forschungsgemeinschaft)

Proposition 65: California, Safe Drinking Water and Toxic Enforcement Act of 1986

TRGS905: Technische Regeln für Gefahrstoffe (Deutsche)

(EC)No.1272/2008 AnnexVI Table3.2: Regulation(EC) No 1272/2008 on classification,

labelling and packaging of substances and mixtures (CLP) AnnexVI Table3.2

UN: United Nations

TSCA: Toxic Substances Control Act (USA)