Material Safety Data Sheet acc. to ISO/DIS 11014



DOKUMENTAL

GmbH & Co KG Schreibfarben

1 Identification of substance

- · Product details
- · Trade name: MA 4500 blue / blau
- · Manufacturer/Supplier:

DOKUMENTAL GmbH & Co KG Schreibfarben Woellnerstraße 26 D-67065 Ludwigshafen Phone + 49 (0) 6 21 /54 02 - 227 Fax + 49 (0) 6 21 /54 02 394

www. dokumental.de

· Information department:

Technical Service, Dr. B. Polzin Tel.: +49-621-5402322

Mobile +49-1726204412 · Emergency information:

Product Safety, Dr. Polzin +49-621-5402322 +49-172-6204412

2 Composition/Data on components

· Chemical characterization

Mixture of the following substances, containing non-hazardous substances and colouring agents.

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
71-23-8	propan-1-ol	50-100%		
298-07-7	bis(2-ethylhexyl) hydrogen phosphate	≤ 2.5%		
6786-83-0	alpha,alpha-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol	≤ 2.5%		

· Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· Hazard description:



Irritant

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Has a narcotizing effect.

Flammable.

Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

NFPA ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- $\boldsymbol{\cdot}$ After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- \cdot After swallowing: If symptoms persist consult doctor.

Material Safety Data Sheet acc. to ISO/DIS 11014

DOKUMENTAL

GmbH & Co KG Schreibfarben

Trade name: MA 4500 blue / blau

(Contd. of page 1)

5 Fire fighting measures

- \cdot Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- \cdot For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· Protective equipment: No special measures required.

6 Accidental release measures

- $\cdot \ \textbf{Person-related safety precautions:} \ \textbf{Wear protective equipment.} \ \textbf{Keep unprotected persons away.}$
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- · Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Components with limit values that require monitoring at the workplace:

71-23-8 propan-1-ol

PEL 500 mg/m³, 200 ppm

REL Short-term value: 625 mg/m³, 250 ppm

Long-term value: $500~\text{mg/m}^3$, 200~ppm

Skin

TLV Short-term value: (614) mg/m³, (250) ppm

- Long-term value: 492 mg/m³, 200 ppm NIC-400; 984; NIC-A 3; delete Skin
- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

GmbH & Co KG Schreibfarben

Trade name: MA 4500 blue / blau

(Contd. of page 2)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties					
General Information					
Form: Color: Odor:	Fluid According to product specification Characteristic				
Change in condition Melting point/Melting range: Boiling point/Boiling range:					
Flash point:	21 - 55°C (70 - 131°F)				
Ignition temperature:	360.0°C (680°F)				
Auto igniting:	Product is not selfigniting.				
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.				
Explosion limits: Lower: Upper:	2.1 Vol % 13.5 Vol %				
Vapor pressure at 20°C (68°F):	19.0 hPa (14 mm Hg)				
Density at 20°C (68°F):	0.840 g/cm³				
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.				
Viscosity: Dynamic at 20°C (68°F):	4 mPas				
Solvent content: Organic solvents:	88.3 %				
Solids content:	9.2 %				

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

12 Ecological information

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

USA

Material Safety Data Sheet acc. to ISO/DIS 11014



Trade name: MA 4500 blue / blau

(Contd. of page 3)

13 Disposal considerations

- · Product:
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· DOT regulations:



· Hazard class: Identification number: UN1263 · Packing group: III· Proper shipping name (technical name): PAINT

· Land transport ADR/RID (cross-border):



· ADR/RID class: 3 (F1) Flammable liquids

· Danger code (Kemler): 30 · UN-Number: 1263 · Packaging group: III· Description of goods: 1263 PAINT

· Maritime transport IMDG:



· IMDG Class: · UN Number: 1263 · Label · Packaging group: III· EMS Number: F-E.S-E· Marine pollutant: No · Propper shipping name: PAINT

· Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class: 3 · UN/ID Number: 1263 · Label .3 · Packaging group: III· Propper shipping name: PAINT

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

71-23-8 propan-1-ol

298-07-7 bis(2-ethylhexyl) hydrogen phosphate

6786-83-0 alpha,alpha-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol

Printing date 07/29/2004 Reviewed on 07/29/2004

Material Safety Data Sheet acc. to ISO/DIS 11014

DOKUMEN IAL

GmbH & Co KG Schreibfarben

Trade name: MA 4500 blue / blau

(Contd. of page 4)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:



Irritant

· Risk phrases:

Flammable.

Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness

· Safety phrases:

Keep out of the reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

Dispose of this material and its container at hazardous or special waste collection point

· National regulations:

· Technical instructions (air):

Class	Share	in	%
NK	88.	. 4	

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.