



# **Material Safety Data Sheet**

1/3

MSDS No.: **TN131-00MO** Date Revision 2003.01:24

#### 1. **PRODUCT AND COMPANY IDENTIFICATION**

Manufacturer :Fuji Xerox Co., Ltd <u>Address</u> :Akasaka Twin Tower East,

17-22, Akasaka-2-choume,

Minato-ku, Tokyo, Japan 107-0052

**Contact Point** 

ASIA PACIFIC REGION:

JAPAN: Koichi Takashima, azuhiko. Ando, Fuji Xerox Asia Pacific Pte Ltd Fuji Xerox Co., Ltd Address:

77 Robinson Road # 26-00 1600, Takematsu, Minamiashigara-shi Address: SIA Building Singapore 068896 Kanagawa-ken, Japan 250-0111

Telephone Number: +81-465-70-1721/FAX Number: +81-465-70-1792 Telephone Number: 65 6239 2833/FAX Number: 65 6239 2714 kazuhiko.ando@fxap.sgp.xerox.com

E-mail: msds-admin@fujixerox.co.jp E-mail:

Product Name:

Magicolor 3300 Toner(Cyan)

# 2. COMPOSITION, INFORMATION ON INGREDIENTS

#### Chemical Nature:

Chemical Name	Ingredients (% by wt.)	CAS Registry Number
Polyester	80-90	_
Blue pigment	< 5	_
Paraffin waxes	< 5	_
Vegetable wax	< 5	_
Amorphous silica	< 5	_

UN Hazard Class: None UN Number: None

#### 3. HAZARDOUS IDENTIFICATION

Physical and Chemical Hazard: None Adverse Human Health Effects: None **Environmental Effects:** None

#### 4.FIRST-AID MEASURES

Eye contact Flush with a large amount of water for at least 15 minutes. Seek medical advice.

Skin contact Wash with soap and water.

Inhalation Remove from exposure and provide fresh air. Rinse mouth with water.

Ingestion Rinse mouth with water. Give several glasses of water to drink and seek medical advice. MSDS No: TN131-00MO 2/3

#### 5. FIRE-FIGHTING MEASURES

Specifid method : In case of fire use extinguishing media.

When in a machine, treat as an electrical fire.

Extingishing media : Water spray, Foam, Dry chemicals

#### **6.ACCIDENTAL RELEASE MEASURES**

Shut off ignition sources. For small spills, sweep up or soak up with damp cloth.

For large spills, wear proper protective equipment and place waste material in closed container.

Dispose of in accordance with federal, state and local regulations.

#### 7.HANDLING AND STORAGE

Handling : Do not incinerate toner or a toner cartridge. Do not dissemble a cartridge. Storage : Keep in cool, dry and well-ventilated area. Keep out of reach of children.

#### 8. EXPOSURE CONTROL /PERSONAL PROTECTION

Control Parameter

ACGIH TLV (2001) :  $10 \text{ mg/m}^3$  (Total)

3 mg/m<sup>3</sup> (Respirable)

Precautionary Measured : None required when used as intended in Fuji Xerox equipment.

For use other than normal customer operating procedures(such as in bulk toner

processing facilities), local exhaust ventilation may be required.

Personal Protective Equipment: None required when used as intended in Fuji Xerox equipment.

For use other than normal customer operating procedures(such as in bulk toner processing facilities), protective glove, goggles and respirators may be required.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor: Blue Powder / Faint Odor

Solubility in water: Negligible Other Data: None

### 10.STABILITY AND REACTIVITY

Flash Point(OC) :Not applicable Auto-Ignition Temperature:Not applicable

Explosion Limit :Not applicable

Flammability :Not flammable under conditions of use Spontaneous Combustibility / Reactivity with water :None Self-reactivity / Explosive :None

Dust Explosive : Like most organic materials in powder form, it can form explosive mixtures when dispersed in

aır.

Stability and Reactivity :Stable Other Data :None

MSDS No: TN131-00MO 3/3

#### 11. TOXICOLOGICAL INFORMATION

Skin Corrosive : None

Skin Irritant (rabbit) : Not an irritant Eye Irritant (rabbit): Not an irritant

Human Patch : Not available

Sensitization : Skin (guinea-pig) : Not a sensitizer Acute Toxicity : Swallowed→LD50 (rat) : > 5000 mg/kg¹¹)

Swallowed $\rightarrow$ LD50 (rat) : > 5000 mg/kg<sup>1)</sup> (practically non-toxic) Skin $\rightarrow$ LD50 (rabbit) : > 5000 mg/kg<sup>1)</sup> (practically non-toxic) Inhaled $\rightarrow$ LC50 (rat) : > 5 mg/L/4hr<sup>1)</sup> (practically non-toxic)

Chronic Toxicity : The results obtained from a Xerox sponsored, Chronic Toner Inhalation Study, demonstrated no lung change in rats for the lowest (1mg/m3) exposure level (i.e. the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of the animals at the middle (4mg/m3) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m3) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with EPA testing protocol. The test toner was ten times more respirable than commercially available Xerox toner, and would not be functionally suitable for Xerox equipment.<sup>1)</sup>

Carcinogenicity : Not classified as "Carcinogens ref.1".

Mutagenicity: Ames Assay: Negative

Reproduction and Development: Not classified as "Reproductive and Development chemicals ref.2".

1) This information is based on toxicity data for similar materials and ingredients.

#### 12. ECOLOGICAL INFORMATION

Biodegradability : Not available. Bioaccumulation : Not available. Acute Toxicity : Not available.

Other Information : None

## 13.DISPOSAL CONSIDERATION

Dispose of in accordance with federal, state and local regulations.

#### 14 TRANSPORT INFORMATION

Transport in accordance with federal, state, and local regulations.

# 15.REGULATORY INFORMATION

Ensure this product in compliance with federal requirements and ensure doformity to local regulations.

#### **16.OTHER INFORMATION**

The above mentioned data correspond to our present state of knowledge and experience, but no warranty is made. Users should consider these data only as a supplement to other information and must make independent determination of the suitability and completeness of information from all sources to ensure proper use and disposal of the materials and safety and health of employees and customers.

#### References

- - ◆ National Toxicology Program(NTP) Report on Carcinogens (NTP)
  - ◆ TLVs and BEIs (American Conference of Governmental Industrial Hygienists)
  - Council Directive 67/548/EEC on the approximation of the laws, regulations, and administratives provisions relating to the classification, packing and labelling of dangerous substances; Annex 1 (EU)
  - ◆ Journal of Occupational Health(Japan Society for Occupational Heatth)
- 2: Council Directive 67/548/EEC on the approximation of the laws, regulations, and administratives provisions relating to the classification, packing and labelling of dangerous substances; Annex 1 (EU)

\*XEROX, The Document Company, and the digital X are trademarks of XEROX CORPORATION.