

# Safety data sheet for chemical products

---

## 1. PRODUCT AND COMPANY IDENTIFICATION

---

Product name: UB-155 Red (uni-ball micro DELUXE)

Manufacture's name : MITSUBISHI PENCIL CO.,LTD  
Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN  
Telephone number : 03-3458-6281      Telefax number : 03-3450-0363  
Telex number : 2422337 MBPENC J.  
Prepared by : KAZUHIRO OYAIZU  
  
Creation Date : APRIL 19, 2001  
File No. : 066103A

---

## 2. CONPOSITION/INFORMATION ON INGREDIENTS

---

The chemical product is a substance or a preparation: Preparation

Chemical nature:

<Component parts>	<Chemical or generic name>	<CAS No.>	<Concentration range (wt%)>
Ink	Water	7732-18-5	63-66
	Ethylene glycol	107-21-1	31-34
	Pigment Red	Registered	7-10
	Resin 2	Registered	1- 4

Other parts : Other parts are excluded from 'chemical substances'.

---

## 3. HAZARDS IDENTIFICATION

---

Most important hazards : Not available

Specific hazards : Not available

---

## 4. FIRST-AID MEASURES

---

Inhalation:

Not applicable. (Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

## Skin contact:

Wash skin with soap or mild detergent and large amount of water until no evidence of chemical remain (at least 15-20 minutes). Get medical attention, if needed.

## Eye contact:

Wash eyes immediately with large amounts of water or normal saline, occasionally lifting upper and lower lids, until no evidence of chemical remains. (at least 15-20 minutes) Get medical attention, if necessary.

## Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.  
[Ink quantity of product: about 1.75g]

---

## 5. FIRE-FIGHTING MEASURES

---

Fire and explosion measures : Slight fire hazard.

## Extinguishing media:

Suitable : alcohol resistant foam, carbon dioxide, regular dry chemical,  
water, alcohol resistant foam

Large fires : Use alcohol-resistant foam or flood with fine water spray.

Fire fighting : The Product is no flammable.  
Move container from fire area if it can be done without risk. Use  
extinguishing agents appropriate for surrounding fire. Avoid inhalation of  
material or combustion by-products. Stay upwind and keep out of low  
areas.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

Personal precautions : Not available

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.  
: In accordance with national, state and local regulations.

---

## 7. HANDLING AND STORAGE

---

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

### Handling:

Technical measures	: Don't swallow ink.
	: Recap after use.
	: Don't shake.
	: Keep out of the reach of children.
	: Avoid contact with skin and eyes.
Precautions	: Not available
Safe handling advice	: Not available

### Storage:

Technical measures	: Keep away from oxidizing materials, ignition sources and high temperature.
Storage condition	: Avoid direct sunlight.
	: Do not leave the products in high temperature space
	: Recommended temperature : 0 - 30 °C.

Incompatible products : ( Information of components.)

strong oxidizers; phosphorus(V) sulfide; sodium hydroxide; chromium trioxide; dimethyl terephthalate + titanium butoxide; potassium permanganate; silvered copper wire; sodium peroxide; perchloric acid; strong bases; chlorosulfonic acid; oleum  
<Ethylene glycol>

oxidizing materials, strong oxidizers <Pigment Red>

Packaging materials : Not applicable.

---

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

---

Engineering measures : Not required

Control parameters ( Information of components. )

OSHA	: 50ppm(125mg/m <sup>3</sup> )ceiling <Ethylene glycol>
ACGIH	: 100mg/m <sup>3</sup> ceiling (particulate) <Ethylene glycol>
DFG	: 26mg/m <sup>3</sup> ( 10ml/m <sup>3</sup> ) DFG MAK 1 times/shift <Ethylene glycol>
UK	: 10mg/m <sup>3</sup> TWA(particulate) , 60mg/m <sup>3</sup> TWA(vapour) , 125mg/m <sup>3</sup> STEL(vapour) <Ethylene glycol>

EC : 20ppm, 52mg/m<sup>3</sup>(8 hours), 40ppm, 104mg/m<sup>3</sup>(short-term) <Ethylene glycol>  
JAIH : 8mg/m<sup>3</sup> <Pigment Red>

Personal protective equipment : Not required

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

[ ] : Information of components.

Physical state and form : Low viscous liquid.  
Colour : Red.  
Odour : None odour.  
pH : 8.7±0.7  
Boiling point : Not available. [ Ethylene glycol / 197°C ]  
Melting point : < -10°C  
Flashpoint : Not available. [ Ethylene glycol / 111°C ]  
Autoignition temperature : Not available. [ Ethylene glycol / 398°C ]  
Explosion limits (vol %) : Not applicable.  
[ Lower flammable limit / 3.2 , Upper flammable limit / 15.3 <Ethylene glycol>]  
Vapour density (air=1) : Not available. [ Ethylene glycol / 2.14 ]  
Density : 1.1±0.1  
Solubility in water : Soluble.  
Evaporation rate : Not available.  
Volatile (%) : 89-92%

---

## 10. STABILITY AND REACTIVITY

---

Stability : Stability.

Hazardous reactions : Will not occur.

Conditions to avoid : May burn dose not ignite ready. Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials

Materials to avoid : (Information of components.)

strong oxidizers; phosphorus(V) sulfide; sodium hydroxide; chromium trioxide; dimethyl terephthalate + titanium butoxide; potassium permanganate; silvered copper wire; sodium peroxide; perchloric acid; strong bases; chlorosulfonic acid; oleum  
<Ethylene glycol>

oxidizing materials, strong oxidizers <Pigment Red>

Hazardous decomposition products : (Information of components.)  
oxides of carbon, water. < common decomposition products.>  
oxides of nitrogen. <Pigment Red>

---

## 11. TOXICOLOGICAL INFORMATION

---

(Information of components)

### Acute toxicity

Ingestion LD50 :  $\geq 5000$ mg/kg-Rat <Pigment Red>  
: 1650mg/kg-Cat, 7500mg/kg-Mouse <Ethylene glycol>  
Inhalation LC50 : 10876mg/kg-Rat <Ethylene glycol>  
Skin LD50 : 9530uL/kg-Rabbit <Ethylene glycol>

Local effects : Irritation; Inhalation, Skin, eye <Ethylene glycol>

Chronic toxicity and long term toxicity : Central nervous system depressant. <Ethylene glycol>

### Signs and Symptoms of overexposure and aggravated by exposure

Inhalation : irritation <Pigment Red>  
: irritation, headache <Ethylene glycol>  
Skin contact : redness, swelling <Pigment Red>  
: irritation, redness <Ethylene glycol>  
Eye contact : irritation, redness <Ethylene glycol>  
Ingestion : fever, nausea <Pigment Red>  
: nausea, vomiting <Ethylene glycol>

Specific effects : Not available.

---

## 12. ECOLOGICAL INFORMATION

---

Not available.

---

## 13. DISPOSAL CONSIDERATIONS

---

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

---

## 14. TRANSPORT INFORMATION

---

International regulations : Not restricted

UN classification number : Not applicable

---

## 15. REGULATORY INFORMATION

---

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) <Ethylene glycol>

EU labeling: 25%≤Xn;R22( R22: Harmful if swallowed.) <Ethylene glycol>

CANADA Hazardous Products Act - Ingredient Disclosure List

: 1% over <Ethylene glycol>

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

---

## 16. OTHER INFORMATION

---

This sheet completes the technical sheet of use but it doesn't replace it.

The information contained in this sheet are based knowledge of the products at the data : ( APRIL 19, 2001 ). They are given quite sincerely.

Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.