

Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 29/01/2015

Revision date: 09/05/2016

Version: 1.9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Name : Dry Erase Marker Screamer Ink WB 600 Series
 Product code : 1903775, 2104183, 2104175, 2104174, 2104176, 2104177, 2104178, 2104179, 2104180, 2104182, 1903949, 2104181, 1903949, 1901072, 1901073, 1901074, 1901075, 1901076, 1901077, 1901419, 1902665, 1902666, 1902667, 1902668, 1902669, 1902670, 1902671, 1902672, 1902673, 1902674, 1902675, 1902676, 1902677, 1902678, 1902679, 1902680, 1902681, 1902682, 1902650, 1902651, 1902652, 1902653, 1902655, 1902656, 1902657, 1902658, 1902659, 1902660, 1902662, 1902704, 1902661, 1902705, 1902706, 1902663, 1902664, 1902703, 30930392, 30930393, 31030410, 3103041, 1902683, 1902684, 1902685, 1902686, 1902408, 1903773, 1903774, 1903792, 1903802, 1903803, 1903858, 1903859, 1903860, 1903861, 1903862, 1903866, 1903867, 1903868, 1903870, 1903872, 1903893, 1903894, 1903895, 1903896, 1903873, 1903897, 1903875, 1903817, 1903807, 1903808, 1903834, 1903835, 1903836, 1903837, 1903838, 1903839, 1903840, 1903841, 1903842, 1903843, 1903844, 1903845, 1903846, 1903847, 1903848, 1903849, 1903881, 1903882, 1903883, 1903892, QBPk9060, 1903798, 1903893, 1903894, 1903895, 1903896, 1903925, 1903926, 1903927, 1903928, 1903931, 1903932, 1903933, 1903934, 1902335, 1901321, 1901323, 1903977, 1904048, 1904047, 1903978, 1904049, 1904050, 1904045, 1903975, 1903972, 1903974, 1904046, 1903973, 1903976, 1903941, 1903948, 1903957, 1903956, 1901072, 1901073, 1901074, 1901075, 1901076, 1901077, 1901419, 1902407, 1902408, 1902096, 1902162, 1902079, 1902080, 1902081, 1902096, 1902162, 1902079, 1902080, 1902081, 1902077, 1902076, 1902090, 1902091, 1902092, 1902093, 1902094

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
 Main use category : Consumer use, Industrial use, Professional use
 Use of the substance/mixture : Marking ink for use in writing instruments

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Acco UK Ltd.
 Oxford House, Oxford Road,
 Aylesbury, Bucks,
 HP21 8SZ.

Telephone: +44 (0) 844 209 8360 (9am to 5pm)
 Fax: +44 (0) 845 603 1731
 Website: www.acco.co.uk
 Email: informationeurope@acco.com

1.4. Emergency telephone number

Emergency number : 0844 2098360

Country	Organisation/Company	Address	Emergency number
IRELAND (REPUBLIC OF)	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
UNITED KINGDOM	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225

Eye Irrit. 2 H319

STOT SE 3 H336

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11

R67

Full text of R-phrases: see section 16


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP)

: P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P261 - Avoid breathing fume, vapours
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ethanol, ethyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, ES, ET, FI, FR, GB, GR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE)	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	>= 50	F; R11
propan-2-ol, isopropyl alcohol, isopropanol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	< 30	F; R11 Xi; R36 R67



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol, ethyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, ES, ET, FI, FR, GB, GR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE)	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	>= 50	Flam. Liq. 2, H225
propan-2-ol, isopropyl alcohol, isopropanol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	< 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing fume, vapours.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if substance enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing fume, Vapours.
- Hygiene measures : Wash Skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Flame proof, lighting, electrical equipment and ventilation equipment.
- Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat and ignition sources.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol, ethyl alcohol (64-17-5)		
Austria	Local name	Ethanol
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Local name	Alcool éthylique
Belgium	Limit value (mg/m ³)	1907 mg/m ³
Belgium	Limit value (ppm)	1000 ppm
Bulgaria	Local name	Етилов алкохол
Bulgaria	OEL TWA (mg/m ³)	1000 mg/m ³
Croatia	Local name	Etanol; (Etil-alkohol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	1900 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	1000 ppm
Croatia	Naznake (HR)	F
Czech Republic	Local name	Ethanol
Czech Republic	Expoziční limity (PEL) (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	530 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	3000 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	1600 ppm
Denmark	Local name	Ethanol
Denmark	Grænseværdie (langvarig) (mg/m ³)	1900 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Estonia	Local name	Etanool (etüülalkohol)
Estonia	OEL TWA (mg/m ³)	1000 mg/m ³
Estonia	OEL TWA (ppm)	500 ppm
Estonia	OEL STEL (mg/m ³)	1900 mg/m ³



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethanol, ethyl alcohol (64-17-5)		
Estonia	OEL STEL (ppm)	1000 ppm
Finland	Local name	Etanoli
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1000 ppm
Finland	HTP-arvo (15 min)	2500 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1300 ppm
France	Local name	Alcool éthylique
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	1000 ppm
France	VLE (mg/m ³)	9500 mg/m ³
France	VLE (ppm)	5000 ppm
Germany	Local name	Ethanol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	960 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm
Germany	Remark (TRGS 900)	DFG,Y
Greece	OEL TWA (mg/m ³)	1900 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Hungary	Local name	ETIL-ALKOHOL
Hungary	AK-érték	1900 mg/m ³
Hungary	CK-érték	7600 mg/m ³
Hungary	Megjegyzések (HU)	IV.
Ireland	Local name	Ethanol
Ireland	OEL (15 min ref) (ppm)	1000 ppm
Latvia	Local name	Etilspirts (etanols)
Latvia	OEL TWA (mg/m ³)	1000 mg/m ³
Lithuania	Local name	Etanolis (etilo alkoholis)
Lithuania	IPRV (mg/m ³)	1000 mg/m ³
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m ³)	1900 mg/m ³
Lithuania	TPRV (ppm)	1000 ppm
Netherlands	Local name	Ethanol
Netherlands	Grenswaarde TGG 8H (mg/m ³)	260 mg/m ³
Netherlands	Grenswaarde TGG 8H (ppm)	Ethanol,136 ppm; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	1900 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (ppm)	Ethanol,992 ppm; Netherlands; Short time value; Public occupational exposure limit value
Netherlands	Remark (MAC)	H
Poland	Local name	Etanol (alkohol etylowy)
Poland	NDS (mg/m ³)	1900 mg/m ³
Portugal	Local name	Etanol (Álcool etílico)
Portugal	OEL TWA (ppm)	1000 ppm
Romania	Local name	Alcool etilic
Romania	OEL TWA (mg/m ³)	1900 mg/m ³
Romania	OEL TWA (ppm)	1000 ppm
Romania	OEL STEL (mg/m ³)	9500 mg/m ³
Romania	OEL STEL (ppm)	5000 ppm
Slovenia	Local name	etanol (etilalkohol)
Slovenia	OEL TWA (mg/m ³)	1900 mg/m ³

Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethanol, ethyl alcohol (64-17-5)		
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m ³)	7600 mg/m ³
Slovenia	OEL STEL (ppm)	4000 ppm
Spain	Local name	Alcohol etílico
Spain	VLA-EC (mg/m ³)	1910 mg/m ³
Spain	VLA-EC (ppm)	1000 ppm
Sweden	Local name	Ethanol
Sweden	nivågränsvärde (NVG) (mg/m ³)	1000 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	500 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	1900 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	1000 ppm
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (mg/m ³)	1920 mg/m ³
United Kingdom	WEL TWA (ppm)	1000 ppm
Iceland	Local name	Etanól (etýlalkóhól)
Iceland	OEL (8 hours ref) (mg/m ³)	1900 mg/m ³
Iceland	OEL (8 hours ref) (ppm)	1000 ppm
Norway	Local name	Etanol
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	950 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	500 ppm
Switzerland	Local name	Ethanol
Switzerland	VME (mg/m ³)	960 mg/m ³
Switzerland	VME (ppm)	500 ppm
Switzerland	VLE (mg/m ³)	1920 mg/m ³
Switzerland	VLE (ppm)	1000 ppm
Switzerland	Remark (CH)	4x15
Australia	Local name	Ethyl alcohol
Australia	TWA (mg/m ³)	1880 mg/m ³
Australia	TWA (ppm)	1000 ppm
USA - ACGIH	Local name	Ethanol
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - ACGIH	Remark (ACGIH)	URT irr
USA - OSHA	Local name	Ethyl alcohol (Ethanol)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
Austria	Local name	2-Propanol Kurzzeitwert für Großguss
Austria	MAK (mg/m ³)	500 mg/m ³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m ³)	2000 mg/m ³
Austria	MAK Short time value (ppm)	800 ppm
Belgium	Local name	Alcool isopropylique
Belgium	Limit value (mg/m ³)	500 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m ³)	1000 mg/m ³
Belgium	Short time value (ppm)	400 ppm
Bulgaria	Local name	Изопропилов алкохол
Bulgaria	OEL TWA (mg/m ³)	980 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1225 mg/m ³
Croatia	Local name	Propan-2-ol; (izopropil-alkohol; izopropanol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	999 mg/m ³



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethanol, ethyl alcohol (64-17-5)		
Croatia	GVI (granična vrijednost izloženosti) (ppm)	400 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	1250 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	500 ppm
Croatia	Naznake (HR)	F, Xi
Czech Republic	Local name	iso-Propanol
Czech Republic	Expoziční limity (PEL) (mg/m ³)	500 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	204 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	410 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Isopropylalkohol (2005)
Denmark	Grænseværdie (langvarig) (mg/m ³)	490 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Estonia	Local name	2-propanool (isopropüülalkohol, isopropanool)
Estonia	OEL TWA (mg/m ³)	350 mg/m ³
Estonia	OEL TWA (ppm)	150 ppm
Estonia	OEL STEL (mg/m ³)	600 mg/m ³
Estonia	OEL STEL (ppm)	250 ppm
Finland	Local name	2-Propanoli
Finland	HTP-arvo (8h) (mg/m ³)	500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
France	Local name	Alcool isopropylique
France	VLE (mg/m ³)	980 mg/m ³
France	VLE (ppm)	400 ppm
Germany	Local name	Propan-2-ol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	500 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm
Germany	Remark (TRGS 900)	DFG, Y
Greece	OEL TWA (mg/m ³)	980 mg/m ³
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m ³)	1225 mg/m ³
Greece	OEL STEL (ppm)	500 ppm
Hungary	Local name	IZOPROPIL-ALKOHOL
Hungary	AK-érték	500 mg/m ³
Hungary	CK-érték	2000 mg/m ³
Hungary	Megjegyzések (HU)	b, i; II.1.
Ireland	Local name	Isopropyl alcohol
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	Notes (IE)	Sk
Lithuania	Local name	2-propanolis (izopropanolis, izopropilo alkoholis)
Lithuania	IPRV (mg/m ³)	350 mg/m ³
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m ³)	600 mg/m ³

Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethanol, ethyl alcohol (64-17-5)		
Lithuania	TPRV (ppm)	250 ppm
Poland	Local name	Propan-2-ol (izopropylowy alkohol)
Poland	NDS (mg/m ³)	900 mg/m ³
Poland	NDSch (mg/m ³)	1200 mg/m ³
Portugal	Local name	2-Propanol (isopropanol ou álcool isopropílico)
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	400 ppm
Romania	Local name	Alcool izopropilic
Romania	OEL TWA (mg/m ³)	200 mg/m ³
Romania	OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m ³)	500 mg/m ³
Romania	OEL STEL (ppm)	203 ppm
Slovenia	Local name	propan-2-ol (izopropilalkohol; izopropanol)
Slovenia	OEL TWA (mg/m ³)	500 mg/m ³
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m ³)	2000 mg/m ³
Slovenia	OEL STEL (ppm)	800 ppm
Sweden	Local name	Isopropanol
Sweden	nivågränsvärde (NVG) (mg/m ³)	350 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	600 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
United Kingdom	Local name	Propan-2-ol
United Kingdom	WEL TWA (mg/m ³)	999 mg/m ³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m ³)	1250 mg/m ³
United Kingdom	WEL STEL (ppm)	500 ppm
Norway	Local name	2-Propanol
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	245 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	100 ppm
Switzerland	Local name	2-Propanol
Switzerland	VME (mg/m ³)	500 mg/m ³
Switzerland	VME (ppm)	200 ppm
Switzerland	VLE (mg/m ³)	1000 mg/m ³
Switzerland	VLE (ppm)	400 ppm
Switzerland	Remark (CH)	4x15
Australia	Local name	Isopropyl alcohol
Australia	TWA (mg/m ³)	983 mg/m ³
Australia	TWA (ppm)	400 ppm
Australia	STEL (mg/m ³)	1230 mg/m ³
Australia	STEL (ppm)	500 ppm
USA - ACGIH	Local name	2-Propanol
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	400 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair
USA - OSHA	Local name	Isopropyl alcohol
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls	: Provide adequate general and local exhaust ventilation.
Personal protective equipment	: Protective goggles. Gloves.
Hand protection	: Wear protective gloves
Eye protection	: Chemical goggles or safety glasses
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended



Other information	: Do not eat, drink or smoke during use.
-------------------	--

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Coloured - See Product Specification.
Odour	: characteristic.
Odour threshold	: No data available
pH	: 4 - 12
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 12 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
Based on available data, the classification criteria are not met

ethanol, ethyl alcohol (64-17-5)	
LD50 oral rat	10740 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LD50 oral rat	5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg bodyweight; Rat)
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)

Skin corrosion/irritation : Not classified
Based on available data, the classification criteria are not met
pH: 4 - 12

Serious eye damage/irritation : Causes serious eye irritation.
pH: 4 - 12

Respiratory or skin sensitisation : Not classified
Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified
Based on available data, the classification criteria are not met

Carcinogenicity : Not classified
Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified
Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified
Based on available data, the classification criteria are not met

Aspiration hazard : Not classified
Based on available data, the classification criteria are not met

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

ethanol, ethyl alcohol (64-17-5)	
LC50 fishes 1	14200 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	9300 mg/l (48 h; Daphnia magna)
LC50 fish 2	13000 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)
Threshold limit other aquatic organisms 1	65 mg/l (72 h; Protozoa)
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa; Growth rate)
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda; Growth rate)
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LC50 fishes 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

ethanol, ethyl alcohol (64-17-5)	
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)

12.2. Persistence and degradability

Dry Erase Marker Screamer Ink WB 600 Series	
Persistence and degradability	Not established.
ethanol, ethyl alcohol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in soil. Very mobile in soil.
Biochemical oxygen demand (BOD)	0,8 - 0,967 g O ₂ /g substance
Chemical oxygen demand (COD)	1,70 g O ₂ /g substance
ThOD	2,10 g O ₂ /g substance
BOD (% of ThOD)	0,43 % ThOD
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in soil. Biodegradable in soil in anaerobic condition. No (test)data available on mobility of the substance.
Biochemical oxygen demand (BOD)	1,19 g O ₂ /g substance
Chemical oxygen demand (COD)	2,23 g O ₂ /g substance
ThOD	2,40 g O ₂ /g substance
BOD (% of ThOD)	0,49 % ThOD

12.3. Bioaccumulative potential

Dry Erase Marker Screamer Ink WB 600 Series	
Bioaccumulative potential	Not established.
ethanol, ethyl alcohol (64-17-5)	
BCF fish 1	1 (72 h; Cyprinus carpio)
Log Pow	-0,31 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Log Pow	0,05 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

ethanol, ethyl alcohol (64-17-5)	
Surface tension	0,022 N/m (20 °C)
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Surface tension	0,021 N/m (25 °C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 20 01 27* - paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1993



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

UN-No. (IMDG) : 1993
UN-No.(IATA) : 1993
UN-No.(ADN) : 1993
UN-No. (RID) : 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Flammable liquid, n.o.s.
Proper Shipping Name (ADN) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (RID) : FLAMMABLE LIQUID, N.O.S.
Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS ; ethanol, ethyl alcohol(64-17-5) ; propan-2-ol, isopropyl alcohol, isopropanol(67-63-0)), 3, II, (D/E)
Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3

:



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3

:



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3

:



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3

:

RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

14.6.1. Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640D
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

14.6.2. Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

14.6.3. Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3H

14.6.4. Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 61, 64D
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1
Carriage prohibited (ADN)	: No
Not subject to ADN	: No

14.6.5. Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601, 640D
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33
Carriage prohibited (RID)	: No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Dry Erase Marker Screamer Ink WB 600 Series
3.a. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	ethanol, ethyl alcohol
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Dry Erase Marker Screamer Ink WB 600 Series

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances



Dry Erase Marker Screamer Ink WB 600 Series

Safety Data Sheet

according to Regulation (EC) No. 453/2010

15.1.2. National regulations

Germany

Water hazard class (WGK)

: 1 - low hazard to waters

WGK remark

: Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information

: None.

Full text of R-, H- and EUH-phrases:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
R11	Highly flammable
R36	Irritating to eyes
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
Xi	Irritant

SDS EU_NSC

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.