Wizard Solvent Based Correction Fluid

Version No: 2.1.1.1

Safety Data Sheet (Conforms to Regulations (EC) No 2015/830)

Issue Date: 05/10/2015
Print Date: 06/10/2015
Initial Date: Not

Available

S.REACH.GBR.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1.Product Identifier

Product name	Wizard Solvent Based Correction Fluid
Synonyms	Not Available
Proper shipping name	PAINT or PAINT RELATED MATERIAL
Other means of identification	Not Available
1.2.Relevant identified	uses of the substance or mixture and uses advised against
Relevant identified uses	Correction fluid for paper or fax copies.
Uses advised against	Not Applicable
1.3.Details of the supp	lier of the safety data sheet
Registered company name	HAINENKO LIMITED
Address	284 Chase Road, Southgate, London, N14 6HF
Telephone	+44 (0) 2 08 882 8734
Fax	+44 (0) 2 08 882 7749
Website	Not Available
Email	d.ashpole@hainenko.com
Association / Organisation	Not Available
Emergency telephone numbers	+33 (0) 3 27 23 64 00
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

2.1.Classification of the substance or mixture

Considered a dangerous mixture according to Directive 1999/45/EC, Reg. (EC) No 1272/2008 (if applicable) and their amendments. Classified as Dangerous Goods for transport purposes.

DSD classification	In case of mixtures, classification has been prepared by following DPD (Directive 1999/45/EC) and CLP Regulation (EC) No 1272/2008 regulations				
DPD classification [1]	R65	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. HARMFUL-May cause lung damage if swallowed. Harmful if swallowed. Highly flammable.			

¹.4.Emergency telephone number

Lyreco Solvent Based Correction Fluid Page 2 of 15

Issue Date: 05/10/2015 Print Date: 06/10/2015

Legend:	1.Classification drawn from EC Directive 67/548/EEC - Annex I ; 2. Classification drawn from EC Directive 1272/2008 - Annex VI
Classification according to regulation (EC) No	Flammable Liquid Category 2, Acute Toxicity (Oral) Category 4, Aspiration Hazard Category 1, Chronic Aquatic Hazard Category 2
1272/2008 [CLP] [1]	
Legend:	1.Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

2.2. Label elements

CLP label elements







SIGNAL WORD

DANGER

Hazard statement(s)	
H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	May cause skin irritation
H411	Toxic to aquatic life with long lasting effects

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P241	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P273	Avoid release into the environment.

Precautionary statement(s) Response

recautionary stateme	in(a) reaponae
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P302+P352	If on the skin wash with plenty of soap and water.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
_	

Precautionary statement(s) Storage

Store in a well-ventilated place. Keep cool. P403+P235

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

 $REACh - Art.57-59: The \ mixture \ does \ not \ contain \ Substances \ of \ Very \ High \ Concern \ (SVHC) \ at \ the \ SDS \ print \ date.$

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

Lyreco Solvent Based Correction Fluid Page 3 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to directive 67/548/EEC [DSD]	Classification according to regulation (EC) No 1272/2008 [CLP]
1.64741-84-0 2.265-086-6 3.649-278-00-0 4.01-2119485160-44- XXXX, 01-2119488738-16-XXXX, 01-2119484660-35-XXXX	<45	naphtha petroleum, light solvent-refined	R45, R46, R65 ^[2]	Carc. 1B, Muta. 1B, Asp. Tox. 1; H350, H340
1.13463-67-7 2.215-280-1, 215-282-2, 236-675-5 3.Not Available 4.01-2119954396-27- XXXX, 01-2119489379-17-XXXX	<15	titanium dioxide	R49 ^[1]	Carcinogen Category 1A; H350i [1]
1.471-34-1 2.215-279-6, 207-439-9 3.Not Available 4.01-2119486795-18-XXXX	<35	calcium carbonate	R37/38, R41 ^[1]	Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, STOT - SE (Resp. Irr.) Category 3; H315, H318, H335 [1]
Legend:	Classification drawn from EC Directive 67/548/EEC - Annex I ; 2. Classification drawn from EC Directive 1272/2008 - Anne x VI 4 Classification drawn from C&L			

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

- ▶ If swallowed do **NOT** induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- ▶ Observe the patient carefully.
- ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- ▶ Seek medical advice.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- General

Eye Contact

- ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- ▶ Other measures are usually unnecessary.

If this product comes in contact with the eyes:

- $_{\mbox{\Large \sl h}}$ Wash out immediately with fresh running water.
- ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
- ${\color{red} \blacktriangleright} \ {\sf Removal} \ {\sf of} \ {\sf contact} \ {\sf lenses} \ {\sf after} \ {\sf an} \ {\sf eye} \ {\sf injury} \ {\sf should} \ {\sf only} \ {\sf be} \ {\sf undertaken} \ {\sf by} \ {\sf skilled} \ {\sf personnel}.$

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- ▶ Seek medical attention in event of irritation.

If this product comes in contact with the eyes:

- ▶ Wash out immediately with fresh running water.
 - ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
 - ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Lyreco Solvent Based Correction Fluid Page 4 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

If skin or hair contact occurs:
▶ Flush skin and hair with running water (and soap if available).
▶ Seek medical attention in event of irritation.
▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.
▶ Other measures are usually unnecessary.
▶ If swallowed do NOT induce vomiting.
▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent
aspiration.
▶ Observe the patient carefully.
▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
▶ Seek medical advice.
▶ Avoid giving milk or oils.
▶ Avoid giving alcohol.
nptoms and effects, both acute and delayed
See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours. Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing med	dia
	▶ Foam.
	▶ Dry chemical powder.
	▶BCF (where regulations permit).
	▶ Carbon dioxide.
	▶ Water spray or fog - Large fires only.
5.2. Special hazards ar	rising from the substrate or mixture
Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
5.3. Advice for firefigh	ters
Fire Fighting	 ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Consider evacuation (or protect in place).
Fire/Explosion Hazard	 ▶ Liquid and vapour are highly flammable. ▶ Severe fire hazard when exposed to heat, flame and/or oxidisers. ▶ Vapour may travel a considerable distance to source of ignition. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
SECTION 6 ACCIDENT	TAL RELEASE MEASURES

Lyreco Solvent Based Correction Fluid Page 5 of 15

Issue Date: 05/10/2015 Print Date: 06/10/2015

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

- ▶ Remove all ignition sources
- ▶ Clean up all spills immediately.

Minor Spills

- Avoid breathing vapours and contact with skin and eyes.
- ▶ Control personal contact with the substance, by using protective equipment.
- ▶ Contain and absorb small quantities with vermiculite or other absorbent material.

Major Spills

- ▶ Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

▶ Prevent, by any means available, spillage from entering drains or water course.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safa	handlin	,

- ▶ Containers, even those that have been emptied, may contain explosive vapours.
- ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- ▶ Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.

Fire and explosion protection

See section 5

Other information

- ▶ Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

▶ Use in a well-ventilated area.

▶ Keep containers securely sealed. ▶ Store away from incompatible materials in a cool, dry well ventilated area.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Packing as supplied by manufacturer.
- ▶ Plastic containers may only be used if approved for flammable liquid.
- ▶ Check that containers are clearly labelled and free from leaks.

Storage incompatibility

▶ Avoid reaction with oxidising agents

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Lyreco Solvent Based Correction Fluid Page 6 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

		rage 0 of 13					nt Date: 06/10/2
Source	Ingredient	Material name		TWA	STEL	Peak	Notes
UK Workplace Exposure Limits (WELs)	titanium dioxide				Not Available	Not Available	Not Available
UK Workplace Exposure Limits (WELs)	calcium carbonate	Calcium carbonate inhalable / Calcium carbonate respirable / Limestone total inhalable / Limestone respirable / Marble total inhalable / Marble respiral	mestone total inhalable / Limestone 10 mg/m3 Not			Not Not Available Available	
MERGENCY LIMITS	ı			ı		'	1
Ingredient	Material name		TEEL	-1	TEEL-2	TEEL-	-3
titanium dioxide	Titanium oxide; (Titanium dioxide)	10 mg	g/m3	10 mg/m3 10 mg/m3		
calcium carbonate	Limestone; (Calo	cium carbonate; Dolomite)	27 mg	g/m3	27 mg/m3 1300 mg/m3		
calcium carbonate	Carbonic acid, c	alcium salt	45 mg	g/m3	210 mg/m3 1300 mg/m3		
Ingredient	Original IDLH			Revis	ed IDLH		
naphtha petroleum, light solvent-refined	Not Available			Not A	vailable		
titanium dioxide	N.E. mg/m3 / N.	E. ppm		5,000	mg/m3		
calcium carbonate	Not Available			Not A	vailable		
2. Exposure controls	<u> </u>						
8.2.1. Appropriate engineering controls	Process controls Enclosure and/o	of engineering controls are: s which involve changing the way a job activity or pro r isolation of emission source which keeps a selecte ds" and "removes" air in the work environment. Vent	d hazard	d "physically"	away from the we		
8.2.2. Personal protection		PCO E					
Eye and face protection	 ▶ Safety glasses with side shields ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. 						
Skin protection	See Hand prote	ction below					
Hands/feet protection	▶Wear safety the selection of to manufacturer advance and hathe the exact break when making a term of the exact break when making a term of the safety of t	al protective gloves, e.g. PVC. footwear or safety gumboots, e.g. Rubber suitable gloves does not only depend on the materia. Where the chemical is a preparation of several subs s therefore to be checked prior to the application. through time for substances has to be obtained from final choice. urability of glove type is dependent on usage.	stances,	the resistanc	e of the glove ma	aterial can not b	oe calculated i
Body protection	See Other prote						
Other protection	 ▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit. 						
		is ready access to a safety shower.					
Thermal hazards	Not Available						

Lyreco Solvent Based Correction Fluid Page 7 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

. Information on basic physical and chemical properties Appearance White liquid with a mild odour; does not mix with water.					
Physical state	Liquid	Relative density (Water = 1)	~1.15		
Odour	Not Available	Partition coefficient n- octanol / water			
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	Not Available	Decomposition temperature	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)		Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	Not Available	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Not Available	Oxidising properties	Not Available		
Jpper Explosive Limit (%)	7.0	Surface Tension (dyn/cm or mN/m)	Not Available		
ower Explosive Limit.	Not Available	Volatile Component (%vol)	Not Available		
/apour pressure (kPa)	Not Available	Gas group	Not Available		
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available		
Vapour density (Air =	Not Available	VOC g/L	Not Available		

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2.Chemical stability	 ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2

Lyreco Solvent Based Correction Fluid Page 8 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Eye

Lyreco Solvent Based Correction Fluid

titanium dioxide

TOXICITY

Oral (rat) LD50: >2000 mg/kg [1]

i i.i. iiiioiiiiatioii oii to	Alcological effects
	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified
	by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following
Inhaled	exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and
iiiiaica	that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or

may produce serious damage to the health of the individual.

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)

Skin Contact
The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.

Open cuts, abraded or irritated skin should not be exposed to this material

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

Chronic Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

IRRITATION

	Not Available	Not Available
naphtha petroleum,	TOXICITY	IRRITATION
light solvent-refined	Dermal (rabbit) LD50: >1900 mg/kg [1]	Not Available

TOXICITY	IRRITATION
Inhalation (rat) LC5 0: >2.28 mg/l4 h [1]	Skin (human): 0.3 mg /3D (int)-mild *
Inhalation (rat) LC50: >3.56 mg/l4 h [1]	
Inhalation (rat) LC50: >6.82 mg/l4 h [1]	
Inhalation (rat) LC50: 3.43 mg/l4 h [1]	
Inhalation (rat) LC50: 5.09 mg/l4 h [1]	
Oral (rat) LD50: >2000 mg/kg [1]	

	TOXICITY	IRRITATION
calcium carbonate	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.75 mg/24h - SEVERE
	Oral (rat) LD50: >2000 mg/kg [1]	Skin (rabbit): 500 mg/24h-moderate
	Oral (rat) LD50: 6450 mg/kge [2]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acu	te toxicity 2.* Value obtained from manufacturer's SDS.

Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS.
 Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Lyreco Solvent Based Correction Fluid Page 9 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

	\	
NAPHTHA PETROLEUM, LIGHT SOLVENT-REFINED	No significant acute toxicological data identified in literature search. for petroleum: This product contains benzene which is known to cause acute myeloid leukaemia to compounds which are neuropathic. This product contains toluene. There are indications from animal studies that prolomay lead to hearing loss. This product contains ethyl benzene and naphthalene from which there is evidence Carcinogenicity: Inhalation exposure to mice causes liver tumours, which are not for full-range naphthas	enged exposure to high concentrations of toluene
TITANIUM DIOXIDE	The material may produce moderate eye irritation leading to inflammation. Repeat conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and m production of vesicles, scaling and thickening of the skin. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When in causing dysfunction of the lungs and immune system. * IUCLID	nay produce on contact skin redness, swelling, the
	·	
CALCIUM CARBONATE	Asthma-like symptoms may continue for months or even years after exposure to allergenic condition known as reactive airways dysfunction syndrome (RADS) whice exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthminutes to hours of a documented exposure to the irritant. A reversible airflow patt of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance.	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure
CALCIUM CARBONATE Acute Toxicity	allergenic condition known as reactive airways dysfunction syndrome (RADS) whice exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthrominutes to hours of a documented exposure to the irritant. A reversible airflow patt of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic to Carcinogenicity	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure
Acute Toxicity Skin	allergenic condition known as reactive airways dysfunction syndrome (RADS) whice exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthreminutes to hours of a documented exposure to the irritant. A reversible airflow patt of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic of Carcinogenicity	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure
Acute Toxicity	allergenic condition known as reactive airways dysfunction syndrome (RADS) whice exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthrominutes to hours of a documented exposure to the irritant. A reversible airflow patt of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic to Carcinogenicity	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure
Acute Toxicity Skin	allergenic condition known as reactive airways dysfunction syndrome (RADS) whice exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthreminutes to hours of a documented exposure to the irritant. A reversible airflow patt of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic of Carcinogenicity	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure
Acute Toxicity Skin Irritation/Corrosion Serious Eye	allergenic condition known as reactive airways dysfunction syndrome (RADS) whice exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthrominutes to hours of a documented exposure to the irritant. A reversible airflow patt of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic to Carcinogenicity Reproductivity STOT - Single	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure

Legend:

✓ – Data required to make classification available

X – Data available but does not fill the criteria for classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)

12.4. Mobility in soil

Lyreco Solvent Based Correction Fluid Page 10 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

Ingredient	Mobility
titanium dioxide	LOW (KOC = 23.74)

12. 5.Results of PBT and vPvB assessment

	P	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:
Product / Packaging	▶ Reduction ▶ Reuse
disposal	▶ Recycling
	▶ Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means.
Naste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required		
	FLAMMABLE JOUID	
Marine Pollutant		
HAZCHEM	•3YE	
Land transport (ADR)		
14.1. UN number	1263	
14.2. Packing group	II .	
14.3. UN proper shipping name	PAINT or PAINT RELATED MATERIAL	
14.4. Environmental hazard	No relevant data	
14.5. Transport hazard class(es)	Class 3 Subrisk Not Applicable	
14.6. Special precautions for user	Special provisions 163 640C 640D 650 Limited quantity 5 L	

Lyreco Solvent Based Correction Fluid Page 11 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

Ingredient

Source

14.1. UN number	1263		
14.2. Packing group	П		
14.3. UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)		
14.4. Environmental hazard	No relevant data		
	ICAO/IATA Class 3		
14.5. Transport hazard class(es)	ICAO / IATA Subrisk Not Applicable		
	ERG Code 3L		
	Special provisions	A3 A72 A192	
	Cargo Only Packing Instructions	364	
	Cargo Only Maximum Qty / Pack	60 L	
14.6. Special	Passenger and Cargo Packing Instructions	353	
precautions for user	Passenger and Cargo Maximum Qty / Pack	5 L	
	Passenger and Carg o Limited Quantity Packing Instructions	Y341	
	Passenger and Cargo Limited Maximum Qty / Pack	1 L	
Sea transport (IMDG-C	Code / GGVSee)		
14.1. UN number	1263		
14.1. UN HUMBEI	1203		
14.1. ON number	II		
	II	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group	II PAINT (including paint, lacquer, enamel, stain, shellac, var	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental	II PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound)	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es)	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es)	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E , S-E	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es)	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es)	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L sport (ADN)	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user nland waterways trans 14.1. UN number	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L sport (ADN) 1263 II	nish, polish, liquid filler and liquid lacquer base) or PAINT RELATED	
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user 14.1. UN number 14.2. Packing group 14.3. UN proper	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L sport (ADN) 1263 II PAINT (including paint, lacquer, enamel, stain, shellac, var		
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user 14.1. UN number 14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L Sport (ADN) 1263 II PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning and reducing compound)		
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user 14.1. UN number 14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L sport (ADN) 1263 II PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning and reducing compound) No relevant data		
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user 14.1. UN number 14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es)	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L sport (ADN) 1263 II PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning and reducing compound) No relevant data 3 Not Applicable		
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user 14.1. UN number 14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L sport (ADN) 1263 II PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning and reducing compound) No relevant data 3 Not Applicable Classification code F1		
14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es) 14.6. Special precautions for user 14.1. UN number 14.2. Packing group 14.3. UN proper shipping name 14.4. Environmental hazard 14.5. Transport hazard class(es)	PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning or reducing compound) Not Applicable IMDG Class 3 IMDG Subrisk Not Applicable EMS Number F-E, S-E Special provisions 163 Limited Quantities 5 L Sport (ADN) 1263 II PAINT (including paint, lacquer, enamel, stain, shellac, var MATERIAL (including paint thinning and reducing compound) No relevant data 3 Not Applicable Classification code F1 Limited quantity 5 L		

Pollution Category

Lyreco Solvent Based Correction Fluid Page 12 of 15

7

Issue Date: 05/10/2015
Print Date: 06/10/2015

IMO MARPOL 73/78
(Annex II) - List of
Noxious Liquid
Substances Carried in
Bulk
titanium dioxide

ılk

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

NAPHTHA PETROLEUM, LIGHT SOLVENT-REFINED(64741-84-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

EU REACH Regulation (EC) No 1907/2006 - Annex XVII (Appendix 2) Carcinogens: category 1B (Table 3.1)/category 2 (Table 3.2)

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances - updated by ATP: 31

European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances (updated by ATP: 31) - Carcinogenic Substances

European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances (updated by ATP: 31) - Mutagenic Substances

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances

European Customs Inventory of Chemical Substances ECICS (English) European Trade Union Confederation (ETUC) Priority List for REACH Authorisation European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

CALCIUM CARBONATE(471-34-1) IS FOUND ON THE FOLLOWING

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

UK Workplace Exposure Limits (WELs)

REGULATORY LISTS

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

UK Workplace Exposure Limits (WELs)

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: 67/548/EEC, 1999/45/EC, 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments as well as the following British legislation: - The Control of Substances Hazardous to Health Regulations (COSHH) 2002 - COSHH Essentials - The Management of Health and Safety at Work Regulations 1999

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (naphtha petroleum, light solvent-refined)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (naphtha petroleum, light solvent-refined)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Lyreco Solvent Based Correction Fluid Page 13 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

Full text Risk and Hazard codes

H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H350i	May cause cancer by inhalation.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R45	May cause CANCER.
R46	May cause heritable genetic damage.
R49	May cause CANCER by inhalation.

Other information

DSD / DPD label elements







Relevant risk statements are found in section 2.1

Indication(s) of danger F, N, Xn	
SAFETY ADVICE	
S02 Keep out of	reach of children.
S09 Keep conta	iner in a well ventilated place.
S13 Keep away	from food, drink and animal feeding stuffs.
S16 Keep away	from sources of ignition. No smoking.
S23 Do not brea	the gas/fumes/vapour/spray.
S29 Do not emp	ty into drains.
S33 Take preca	utionary measures against static discharges.
S35 This materia	al and its container must be disposed of in a safe way.
S40 To clean the	e floor and all objects contaminated by this material, use water and detergent.
S41 In case of fi	re and/or explosion, DO NOT BREATHE FUMES.
S43 In case of fi	re use the extinguishing media detailed in section 5 of this SDS.
S46 If swallower	d, seek medical advice immediately and show this container or label.
S51 Use only in	well ventilated areas.
S56 Dispose of	this material and its container at hazardous or special waste collection point.
S57 Use approp	riate container to avoid environmental contamination.
S61 Avoid relea	se to the environment.

Ingredients with multiple cas numbers

Lyreco Solvent Based Correction Fluid Page 14 of 15

Issue Date: **05/10/2015**Print Date: **06/10/2015**

	1 IIIK 54.6. 33/13/2313
titanium dioxide	100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12188-41-9, 12701-76-7, 12767-65-6, 12789-63-8, 1309-63-3, 1317-70-0, 1317-80-2, 1344-29-2, 13463-67-7, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9
calcium carbonate	1317-65-3, 13397-26-7, 146358-95-4, 15634-14-7, 198352-33-9, 459411-10-0, 471-34-1, 63660-97-9, 72608-12-9, 878759-26-3

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review using available literature references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Lyreco Solvent Based Correction Fluid

Print Date: **06/10/2015**

end of SDS