XEROX	Material Safety Data Sheet	MSDS No.: Date:	C49 5/24/02	
	C C	Revision:	7/26/06	
Supplier: Xerox Corporation Rochester, N.Y. 14644	Telephone #'s Transportation En		cy: (585) 422-217	
	Section 1 - Product Identification			
Trade Names/Synonyms:	DocuColor 1632/DocuColor 2240/DocuColor 3535/CopyCentre C32/CopyCentre C40/WorkCentre Pro 32/WorkCentre Pro 40 Print Cartridge	Part No.: 13R579,	13R586	
WHMIS Status:	This is not a WHMIS controlled product.			
	ngredients (% by wt. CAS No.		<u>No.</u>	
	<u>Aluminum substrate (>99%)</u>	7429-9	90-5	
	Polymeric coating (<1%) Polymeric coating Photosensitive materials	Polymeric coating Confidential		
	Section II -Emergency and First Aid			
Primary Route of Entry: Skin	Symptoms of Overexposure: None			
Eyes: N.A. Skin: Wash with soap and water		Medical Conditions Generally Aggravated by Exposure: None when used as described by product literature.		
Inhalation: N.A.	Additional Information: None			

Section III - Toxicology and Health Information

This material has been evaluated by Xerox Corporation.

Oral LD ₅₀ :	N.D.	TLV:	N.A.
Dermal LD ₅₀ :	N.D.	PEL:	N.A.
Inhalation LC ₅₀ :	N.D.	STEL:	N.A.
Eye Irritation:	N.D.	Ceiling:	N.A.
Skin Sensitization:	N.D.	XEL ¹ :	N.A.
Skin Irritation:	N.D.		
Human Patch:	N.D.		
Mutagenicity:	Ingredients negative in Ames test		
Carcinogens:	None Present		
Aquatic LC _{50:} :	N.D.		
Additional Informat	tion: None		

¹XEL - Xerox Exposure Limit

N.A. - Not Applicable N.E. - None Established N.D. - Not Determined

MSDS No: C49

Trade Name: DocuColor 1632/DocuColor 2240/DocuColor 3535/CopyCentre C32/CopyCentre C40/WorkCentre Pro 32/WorkCentre Pro 40 Print Cartridge

Section IV - Physical Data

Appearance/Odor:	Solid cylinder, blue / odorless	Softening Range:	N.D.
Boiling Point:	N.A.	Melting Point:	132 °C (min.)
Solubility in Water:	Insoluble	Specific Gravity (H ₂ O=1)	2.7
Evaporation Rate:	N.A.	Vapor Pressure (mm Hg):	N.A.
Vapor Density (Air=1):	N.A	pH:	N.A.
Volatile:	N.A. % (Wt.) N.A. % (Vol.)		

Section V - Fire and Explosion Data

Flash Point (Method Used):	N.A.
Flammable Limits:	LEL: N.A., UEL: N.A.
NFPA 704:	N.D.
Extinguishing Media:	Water, carbon dioxide, foam
Special Fire Fighting Procedures:	When in a machine, treat as an electrical fire
Fire and Explosion Hazards:	None.

Section VI - Reactivity Data

Stability:	Stable
Hazardous Polymerization:	Will not occur
Hazardous Decomposition Products:	Oxides of carbon and nitrogen.
Incompatibility (Materials to Avoid):	Strong acids and bases.

Xerox

Section VII - Special Protection Information

Respiratory Protection:	None required when used as inten-	ded in Xerox equipment	
Eye Protection:	None required when used as inten-	ded in Xerox equipment	
Protective Gloves:	ves: None required when used as intended in Xerox equipment		
Other:	None required when used as inten-	ded in Xerox equipment	
	Section VIII - S	pecial Precautions	
Handling and Storage:	Do not handle surface. Store at roo	om temperature.	
Conditions to Avoid:	Avoid exposure to high temperatu	res.	
	Section IX - Spill, Leak	, and Disposal Procedures	
For Spills or Leakage:	Particles of coating detached through physical damage may be collected and disposed of casually.		
Waste Disposal Method: Under present EPA Regulations, this photoreceptor is not classified as a hazardous waste and may be disposed of casually. Ensure conformity with federal, state and local regulations.			
Section X - Transportation Information			
DOT Proper Shipping Nat	ne: N.A. (Not Regulated)	ID Number:	N. A.
Hazard Classification:	N. A.	Packing Group:	N. A.