XEROX MATERIAL SAFETY DATA SHEET

Manufacturer: Xerox Corporation, Office Group P. O. Box 1000, Wilsonville, Oregon, 97070-1000

MSDS No.:OPB-6536Date:December 22, 2003Revision Date:March 16, 2005

SECTION 1- PRODUCT IDENTIFICATION

Product Names Black Toner Cartridge Cyan Toner Cartridge Magenta Toner Cartridge Yellow Toner Cartridge Part Numbers 106R00652 106R00653 106R00654 106R00655

Product Use: XEROX Phaser ® 7750 Laser printers

SECTION 2 - INFORMATION ON INGREDIENTS

Ingredients (% by weight) Resin (>60%) Frits (>15%) Wax (>1%) Carbon Black (>3%) Cyan, Magenta, or Yellow dyes (>1%) Amorphous silicas (<5%) CAS number Proprietary 65997-18-4 8002-74-2 1333-86-4 Proprietary Proprietary

SECTION 3 - HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE: Toner powders are encased in a cartridge. Minimal exposure through inhalation or skin contact is expected when used as intended.

POTENTIAL HEALTH EFFECTS: Health effects from this product are expected to be negligible, when product is used as intended. See Section 11, Toxicology Information. Immediate Effects: Inhalation: Minimal irritation to respiratory tract, as for any non-toxic dust Skin: Not expected to cause skin irritation Eye: Not expected to cause eye irritation Ingestion: Not an expected route of exposure Chronic Effects: None known

> Toner cartridge for Phaser ® 7750 Printer Page 1/4 12/22/03

SIGNS AND SYMPTOMS OF EXPOSURE: Minor irritation to respiratory tract. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove person to fresh air. Seek medical attention if symptoms occur. EYES: If particles get into eye, flush thoroughly with water. Seek medical attention if symptoms occur.

SKIN: Wash thoroughly with soap and water. Seek medical attention if symptoms occur. INGESTION: Dilute stomach contents with several glasses of water. Seek medical attention if symptoms occur.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: Not applicable

FIRE & EXPLOSION HAZARDS: Toner is a combustible powder. Like most organic powders, it can form explosive mixtures when dispersed in air.

EXTINGUISHING MEDIA: Water, dry chemical, carbon dioxide, or foam.

FIRE FIGHTING INSTRUCTIONS: Avoid inhalation of smoke. As for any fire, wear protective clothing and self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK: Sweep up or vacuum spilled materials and carefully transfer into sealable waste container. Sweep slowly to minimize generation of dust during clean up. If a vacuum is used, the motor must be rated as dust tight. A conductive hose bonded to the machine should be used to reduce static buildup. Clean up residue if necessary with soap and cold water. Wash or dry clean garments after removing loose toner.

SECTION 7 - HANDLING AND STORAGE

HANDLING: No special precautions, when used as intended. STORAGE: Avoid high temperatures.

SECTION 8 - EXPOSURE CONTROL - PERSONAL PROTECTION

No special personal protection indicated, when used as intended in Xerox Phaser ® laser printers.

THRESHOLD LIMIT VALUE (TLV): 10 mg/m³ (total dust) PERMISSIBLE EXPOSURE LIMIT (PEL): 15 mg/m³ (total dust); 5 mg/m³ (respirable dust) SHORT TERM EXPOSURE LIMIT (STEL): None established CEILING LIMIT: None established XEROX EXPOSURE LIMIT (XEL): 2.5 mg/m³ (total dust); 0.4 mg/m³ (respirable dust)

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/ODOR: Black, magenta, cyan or yellow powder/faint odor BOILING POINT: Not applicable SOLUBILITY IN WATER: Negligible EVAPORATION RATE: Not applicable VAPOR DENSITY (Air = 1): Not applicable VOLATILE: Not applicable MELTING POINT: Not available SPECIFIC GRAVITY (Water = 1): Approximately 1 VAPOR PRESSURE (mm Hg): Not applicable pH: Not applicable

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable. INCOMPATIBILITY WITH OTHER MATERIALS: Strong oxidizers HAZARDOUS POLYMERIZATION: Will not occur HAZARDOUS DECOMPOSITION PRODUCTS: During a fire, toxic gases may be generated by thermal decomposition or combustion. Avoid breathing smoke.

SECTION 11 - TOXICOLOGICAL INFORMATION

This material has been evaluated by Xerox Corporation. The toxicity data noted below is based on test results of similar toners.

Oral LD_{50} : >5 g/kg (rats), practically non-toxic Dermal LD_{50} : > 5 g/kg (rabbits), practically non-toxic Inhalation LC_{50} : > 2 mg/l (rats; 4 hour exposure), practically non-toxic Eye Irritation: Not an irritant Skin sensitization: Not a sensitizer Skin irritation: Not an irritant Human Patch: Non-irritating, non-sensitizing Mutagenicity: No mutagenicity detected in Ames assay Carcinogens: None present

Additional Information: The results obtained from a Xerox sponsored Chronic Toner Inhalation Study demonstrated no lung changes in rats for the lowest (1 mg/m³) exposure level (ie., the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of the animals at the middle (4 mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. The findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with EPA testing protocol. The test toner was ten times more respirable than commercially available Xerox toner and would not be functionally suitable for Xerox equipment.

SECTION 12 - ECOLOGICAL INFORMATION

Aquatic LC₅₀: > 1000 mg/l (fathead minnows); non-toxic

SECTION 13 - DISPOSAL CONSIDERATIONS

This material is not a RCRA hazardous waste as specified in 40 CFR 261. State and local waste disposal requirements, however, may be more restrictive. Dispose in accordance with all federal, state, and local regulations. Incinerate only in a closed container.

SECTION 14 - TRANSPORTATION INFORMATION

DOT: Not regulated.

SECTION 15 - REGULATORY INFORMATION

TSCA: All components of these toners have been manufactured in compliance with TSCA. CANADIAN WHMIS: These toners are not regulated as controlled products under the Workplace Hazardous Material Information System (WHMIS).

SECTION 16 - OTHER INFORMATION

Xerox Corporation Office Group Environmental, Health & Safety P.O. Box 1000 Mail Stop 7063-512 Wilsonville, Oregon 97070 Safety Information: 800-828-6571 Health Emergency: 585-422-2177 Transportation Emergency (Chemtrec): 800-424-9300