HP Business Inkjet 2800 Printer series






The HP Business Inkjet 2800 Printer series is the powerful, cost efficient, A3+ printer series. Experience low running costs with individual high-capacity ink cartridges, exceptional print quality and professional networking for small work teams.



HP Business Inkjet 2800 Printer



HP Business Inkjet 2800dtn Printe



Create fast and vibrant documents from postcard(A6) to poster(A3+)with up to 4800-optimised dpi¹.

Communicate more effectively with printing capabilities from A6 to A3+ on a wide variety of media. Produce vibrant, professional quality documents with up to 4800 x 1200-optimised dpi¹ colour on HP high-capacity printing supplies. Improve productivity with speeds of up to 24 ppm black and up to 21 ppm colour in draft mode. Print speed is enhanced by the printer's 96 MB of on-board memory, upgradeable to 352 MB. Reduce user intervention with a second 250-sheet paper tray².

Enjoy low running cost with four individual high-capacity ink cartridges and long-life printheads.

Four high-capacity individual ink cartridges (69 ml black and 28 ml colour) and long-life printheads reduce running cost and user intervention while increasing productivity. Enjoy greater flexibility and reduce paper cost with optional automatic two-sided printing³ up to A3+ size.

High-volume monthly duty cycle of up to 12,000 pages supports volume printing due to printer robustness. Easily maintain your printer with back-lit LCD and intuitive control panel.

Experience robust connectivity, easy network management and integration into any environment.

The EIO internal print server⁴ enables you to connect swiftly and seamlessly to networks even in the most complex and varied print environments. It prints most sophisticated jobs with industry-standard PCL 5c, PCL 6 and Postscript Level 3 Emulation and provides compatability with PC, Macintosh and major network operating systems. Easy and convenient print and network management through HP Remote Management Software (RMS) and Web Jetadmin helps to increase productivity and save time and money.

 $2_{\mbox{The 250-sheet}}$ second paper tray is available on the HP Business Inkjet 2800dtn

- $^3\mathrm{The}$ automatic two-sided printing accessory is available on the HP Business Inkjet 2800dtn It is an optional feature on the 2800 model; not included, sold separately.
- ⁴The HP Business Inkjet 2800dtn is network-ready

¹Up to 4800 x 1200 optimised dpi colour printing on premium photo papers and 1200 x 1200 input dpi.

It is optional on the 2800 model; not included, sold separately.

Networking capabilities are optional on the 2800 model; not included, sold separately.

Print technology	HP Thermal Inkjet								
Printhead nozzles	304								
Print speed	Document type	Draft	Normal		Best				
	Black text A4	Up to 2			Up to 4 ppm				
	Black text A3		3.5 ppm Up to 4		Up to 3 ppm				
	Mixed text/colour				Up to 4 ppm				
	Mixed text/colour				Up to 2.5 ppm				
		es—exact speed will vary depe	nding on the system contigura	tion, sottware pro	gram, and document complexity				
	media.								
ocessor	Motorola 32-bit ColdFire 4e RISC, 256 MHz								
int quality	Black: Up to 1200 x 600 dpi. Colour: Up to 4800 x 1200 optimised dpi on premium photo paper Resolution Enhancement								
	technology, HP Photoret III								
perating systems compatibility	Microsoft® Windows® 2000, XP Home, XP Professional; Mac OS X v 10.1.5; Mac OS X v 10.2; Mac OS X v 10.3 Optional:								
ALL	UNIX, OS/2, Linux, Latest driver updates available at http://www.hp.com/support/businessinkjet2800								
Network operating system compatibility	Microsoft® Windows® 2000, Windows 2003 Server, Netware (4.2, 5.1, 6.5), Windows 2000 Terminal services, Windows								
	2000 Terminal services with Citrix MetaFrame 1.8, Windows 2000 Terminal services with Citrix MetaFrame XP, Windows 2003 Terminal services with Citrix MetaFrame Proceedings of the Server actional: UNIX®, OS /2, Linux								
	Terminal services, Windows 2003 Terminal services with Citrix MetaFrame Presentation Server, optional: UNIX®, OS/2, Linux								
inimum System Requirements	CD ROM; Microsoft Internet Explorer v. 5 or later; Windows 2000: Pentium 300, 64 MB RAM, 160 MB on hard disk; Windows XP 32: Pentium 233, 64 MB RAM, 160 MB on hard disk; Windows XP 64: Pentium 233, 128 MB RAM, 160 MB on hard disk								
emory	96 MB (upgradeable with two 100-pin SDRAM DIMM), Expandable to 352 MB through 2 industry-standard DIMM slots,								
	maximum: 352 MB								
inter languages		HP PCL 5c, HP PCL 6, HP Postscript Level 3 Emulation							
Typefaces/fonts	HP Jetdirect 620n Fast Ethernet internal print server J7934A, HP Jetdirect 625n Gigabit internal print server J7960A, HP Jetdirect								
	680n 802.11b wireless Ethernet internal print server J6058A, HP Jetdirect ew2400 802.11g wireless & Fast Ethernet external								
	print server (USB 2.0) J7951A, HP Jetdirect 500x TR external print server J3264A, HP Jetdirect 500x 10/100 external print								
	server J3265A, HP Jetdirect 300x 10/100 external print server J3263A, HP Jetdirect 380x 802.11b wireless external print server								
utu avala (manthhr 6.4)	J6061A								
uty cycle (monthly, A4)	Up to 12,000 pag		1						
Media types	Copier, bond, recycled, multipurpose, premium inkjet, premium inkjet heavyweight, premium transparency, premium photo paper,								
	photo paper, professional brochure (matt and glossy), cards, envelopes and banner								
laximum print area	320 x 594.1 mm A4: top: 3 mm, left: 3.4 mm, right: 3.4 mm, bottom: 11.9 mm. A3: top: 3 mm, left: 5 mm, right: 5 mm, bottom: 11.9 mm								
int margins	A4: top: 3 mm, le				5 mm, bottom: 11.9 mm				
Media handling	Input:	Capacity	Weight	Size					
	Tray 1:	150 sheets (plain, inkjet,	60 to 200 g/m² (including		4, A5, A6, B4, B5, B6, C4, C5				
		photo-paper), envelopes, ,	plain paper, photo media d	and C6, DL					
		labels, cards (index, greeting)							
			enables media up to 270 g	/ m²					
			(one sheet at a time)						
	Tray 2:	250 sheets plain paper only	60 to 90 g/m ²	A3+, A3, A					
	Duplex unit:			A3+, A3, A	4, В4				
	Output:	Sheets: Up to 100							
		Envelopes: Up to 22							
		Transparencies: Up to 60							
	Size:	A3+ (305 x 457 mm), A3 (29							
	mm), B4 (250 x 353 mm), B5 (176 x 250 mm), B6 (125 x 176 mm), C4 (229 x 324 mm), C5 (162 x 229								
	mm), C6 (114 x 162 mm), DL (110 x 220 mm), custom: 90 x 146 to 330 x 483 mm								
Power	Requirements: Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 2.2 amp								
	Power supply: Internal: built-in universal power supply								
	Consumption: Standby: 12 watts								
	Powersave: below 30 watts Maximum: 67 watts								
Control panel	Intuitive two-line text-based backlit LCD display, buttons: 1 each (Power, Help, LCD, Cancel, Resume); 2 status LED; 3 LCD Menu								
oniroi panei		5							
-	Navigation	Acrobat Reader 5.05, Config editor, expand utility, INF locator, Scrubber							
oftware included	Acrobat Reader 5		/7/ 500 0/0 /0555	Out of package: 676 x 498 x 199 mm (BIJ 2800) 676 x 588 x 263 mm (2800dtn) Packaged: 788 x 600 x 382 mm (BIJ 2800)					
ftware included	Acrobat Reader 5 Out of package: 6	76 x 498 x 199 mm (BIJ 2800	676 x 588 x 263 mm (2800	atn) Packagea: 78	38 x 600 x 382 mm (BIJ 2800)				
oftware included mensions (w x d x h)	Acrobat Reader 5 Out of package: 6 788 x 600 x 544	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn)							
ftware included mensions (w x d x h) eight	Acrobat Reader 5 Out of package: 6 788 x 600 x 544 Out of package:	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800	dtn) ; Packaged: 17 kg (BIJ 2	800) 23 kg (2800					
oftware included imensions (w x d x h) /eight	Acrobat Reader 5 Out of package: 0 788 x 600 x 544 Out of package: HP Business Inkjet	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn	dtn) ; Packaged: 17 kg (BIJ 2 nin, HP Embedded Web Serve	800) 23 kg (2800 er	Ddtn)				
oftware included imensions (w x d x h) /eight inter management	Acrobat Reader 5 Out of package: 6 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper	76 x 498 x 199 mm (BU 2800 mm (2800dtn) 3.5 kg (BU 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommende	dtn) ; Packaged: 17 kg (BIJ 2 in, HP Embedded Web Serve d operating temperature: 15 t	800) 23 kg (2800 er o 35° C, operatin	Ddtn) g humidity: 15 to 80% RH,				
oftware included imensions (w x d x h) /eight inter management	Acrobat Reader 5 Out of package: c 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating humidit	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommender recommended: 20 to 80% RH	dtn); Packaged: 17 kg (BIJ 2 nin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: -40 to	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu	Ddtn) g humidity: 15 to 80% RH, imidity: 15 to 90% RH, noise				
oftware included imensions (w x d x h) /eight inter management	Acrobat Reader 5 Out of package: 6 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating tumidit level per ISO 929	76 x 498 x 199 mm (BI) 2800 mm (2800dtn) 3.5 kg (BI) 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommended recommended: 20 to 80% RH 5: sound power: LwAd 6.4 B(A)	dtn); Packaged: 17 kg (BU 2 nin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: -40 to (printing in draft mode), 6.2	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu	Ddtn) g humidity: 15 to 80% RH, imidity: 15 to 90% RH, noise				
control panel ioftware included Dimensions (w x d x h) Veight Trinter management Operating environment	Acrobat Reader 5 Out of package: 6 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating tumidit level per ISO 929	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommender recommended: 20 to 80% RH	dtn); Packaged: 17 kg (BU 2 nin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: -40 to (printing in draft mode), 6.2	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu	Ddtn) g humidity: 15 to 80% RH, imidity: 15 to 90% RH, noise				
oftware included limensions (w x d x h) Veight rinter management	Acrobat Reader 5 Out of package: 0 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating humidit level per ISO 929 LpAm 58 dB(A) (p	76 x 498 x 199 mm (BI) 2800 mm (2800dtn) 3.5 kg (BI) 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommended recommended: 20 to 80% RH 5: sound power: LwAd 6.4 B(A)	dtn); Packaged: 17 kg (BU 2 nin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: -40 to (printing in draft mode), 6.2 (printing in default mode)	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu B(A) (printing in D	Ddtn) g humidity: 15 to 80% RH, umidity: 15 to 90% RH, noise Jefault mode), sound pressure:				
oftware included imensions (w x d x h) /eight rinter management perating environment	Acrobat Reader 5 Out of package: 0 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating humidit level per ISO 929 LpAm 58 dB(A) (p EMC certifications	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommende v recommended: 20 to 80% RH 5: sound power: LwAd 6.4 B(A) rinting in draft mode), 53 dB(A : FCC Title 47 CFR Part 15 Cla:	dtn); Packaged: 17 kg (BU 2 in, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: 40 to (printing in draft mode), 6.2 (printing in default mode) as B (USA) CTICK (Australia an	800) 23 kg (280(or o 35° C, operatin 60° C, storage hu B(A) (printing in E ad New Zealand)	Ddtn) g humidity: 15 to 80% RH, umidity: 15 to 90% RH, noise Default mode), sound pressure: , VCCI (Japan), CE (European				
oftware included imensions (w x d x h) /eight rinter management perating environment	Acrobat Reader 5 Out of package: 6 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating tumidit level per ISO 929 LpAm 58 dB(A) (p EMC certifications Union), BSMI (Tai UL Listed (USA), C	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommende recommended: 20 to 80% RH 5: sound power: LwAd 6.4 B(A) initing in draft mode), 53 dB(A : FCC Title 47 CFR Part 15 Cla von), ICES (Canada); CCC S& SA (Canada), GS Certified (Ger	dtn); Packaged: 17 kg (BU 2 sin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: -40 to (printing in draft mode), 6.2 (printing in default mode) is B (USA) CTICK (Australia ar E (China), MIC (Korea) Safety many), CE Marking (Europe),	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu B(A) (printing in E nd New Zealand) • EN 60950/IEC	Ddtn) g humidity: 15 to 80% RH, midity: 15 to 90% RH, noise Default mode), sound pressure: , VCCI (Japan), CE (European 950 Compliance (International),				
oftware included imensions (w x d x h) /eight rinter management perating environment	Acrobat Reader 5 Out of package: 6 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating tumidit level per ISO 929 LpAm 58 dB(A) (p EMC certifications Union), BSMI (Tai UL Listed (USA), C	76 x 498 x 199 mm (BI) 2800 mm (2800dtn) 3.5 kg (BI) 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommended r recommended: 20 to 80% 5: sound power: LwAd 6.4 B(A) 5: sound power: LwAd 6.4 B(A) initing in draft mode), 53 dB(A : FCC Title 47 CFR Part 15 Cla van), ICES (Canada); CCC S&I	dtn); Packaged: 17 kg (BU 2 sin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: -40 to (printing in draft mode), 6.2 (printing in default mode) is B (USA) CTICK (Australia ar E (China), MIC (Korea) Safety many), CE Marking (Europe),	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu B(A) (printing in E nd New Zealand) • EN 60950/IEC	Ddtn) g humidity: 15 to 80% RH, midity: 15 to 90% RH, noise Default mode), sound pressure: , VCCI (Japan), CE (European 950 Compliance (International),				
oftware included imensions (w x d x h) /eight rinter management perating environment	Acrobat Reader 5 Out of package: 0 788 x 600 x 544 Out of package: HP Business Inkjet Operating temper operating humidit level per ISO 929 LpAm 58 dB(A) (p EMC certifications Union), BSMI (Tai UL Listed (USA), C NOM-NYCE (Mex	76 x 498 x 199 mm (BIJ 2800 mm (2800dtn) 3.5 kg (BIJ 2800) 19 kg (2800 2800 Toolbox, HP Web Jetadn ature: 5 to 40° C, recommende recommended: 20 to 80% RH 5: sound power: LwAd 6.4 B(A) initing in draft mode), 53 dB(A : FCC Title 47 CFR Part 15 Cla von), ICES (Canada); CCC S& SA (Canada), GS Certified (Ger	dtn); Packaged: 17 kg (BIJ 2 sin, HP Embedded Web Serve d operating temperature: 15 t , storage temperature: 40 to (printing in default mode) is B (USA) CTICK (Australia ar E (China), MIC (Korea) Safety many), CE Marking (Europe), ingapore)	800) 23 kg (2800 er o 35° C, operatin 60° C, storage hu B(A) (printing in E ad New Zealand) E EN 60950/IEC B (Poland),eK (Ko	Ddtn) g humidity: 15 to 80% RH, midity: 15 to 90% RH, noise Default mode), sound pressure: , VCCI (Japan), CE (European 950 Compliance (International),				



© Copyright 2009 Hewlett-Packard Development Company, L.P.The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Published in EMEA 07/09 5982-9928EEE

rina information

174A	HP Business Inkjet 2800		
	Printer, setup roadmap, 4 ink		
	cartridges [black (26 ml),		
	colour (28 ml)], 4 print heads,		
	getting started guide, power		
	cord, driver CD		
164A	HP Business Inkjet 2800dtn		
	Printer, setup roadmap, 4		
	ink cartridges [black (26		
	ml), colour (28 ml)], 4 print		
	heads, getting started		
	guide, power cord, driver		
	CD, duplexer, 250-sheet		
	tray, HP Jetdirect EIO		
	Internal Network Print		
	Server (installed)		
	Accessories		

HP letdirect 620n Fast Ethernet Print Server HP Jetdirect 625n Gigabit Ethernet Print Server HP Inkjet Automatic Two-sided Printing Accessory HP Inkjet 250-sheet Paper Ťray HP Jetdirect 680n 802.11b Wireless Print Server HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server HP Jetdirect 500x External Print Server (3 port parallel-10/100Base-TX/10 Base2) HP Jetdirect 300x External Print Server (parallel/10/100TX) HP Jetdirect 380x Wireless External Print Server (USB compatible with USB 2.0 specifications, 802.11b) HP Jetdirect en3700 Fast Ethernet Print Server Supplies HP 10 Black Ink Cartridge HP 11 Cyan Ink Cartridge HP 11 Magenta Ink F

	Cartridge
C4838AE	HP 11 Yellow Ink Cartridge
C4810A	HP 11 Black Printhead
C4811A	HP 11 Cyan Printhead
C4812A	HP 11 Magenta Printhead
C4813A	HP 11 Yellow Printhead

Service & Support

/E HP Care Pack, next business ite, 3 years **PA/PE** HP Care Pack, post y next business day on-site, 1

a complete list of supplies, media and ries, please refer to the HP website at http://www.hp.com

