

HP Color LaserJet CM6030/CM6040 Multifunction Printer series



See productivity soar with this high performing Color LaserJet MFP. Create A3 colour documents with excellent line and image quality. Enjoy fast print speeds; print, copy, scan, fax¹ and digital sending functionality plus exceptional ease of use.

Ideal for workgroups (of 6 to 15 users) and departmental environments (up to 20 users) within large and medium enterprise managed office environments who need print, copy, scan, fax and digital sending functionality, up to A3 format as well as high quality colour capabilities to produce a range of internal and external business communications.

Boost workgroup productivity with fast print speeds, more functionality and outstanding performance.

Increase output with speeds of up to 31 ppm² and 41 ppm³ in colour and black (A4), and a first printed page in around 12 seconds. Handle complex jobs fast with an 835 MHz microprocessor and 512 MB memory expandable up to 768 MB. Speed up workflow with scan-to e-mail, scan-to network folder, scan-to printer, and fax⁴. Get peace of mind with security solutions like job authentication, encryption and network protection. Paper handling options include a booklet maker and stapler/stacker.

Exceptionally easy to use and manage with an intuitive design and touch screen control panel.

Find applications quickly and experience consistency with the Easy Select⁵ control panel's intuitive display. Feature and device management compatibility across your MFP fleet ensures ease of use. Cut costs and save time with HP Web Jetadmin fleet management software: install, configure and manage remotely, automate routine tasks and track supplies usage. Extend your MFP's capabilities: streamline workflows with advanced solutions like integrated capture, job accounting and security.

Achieve outstanding results with superior colour accuracy and excellent output quality.

Create high quality colour documents up to A3⁶ that make a big impact with HP ImageREt 4800. Get exceptional line acuity with up to 1200x600 dpi operating mode, ideal for detailed plans and architectural drawings. Ensure superior colour accuracy with support for colour matching standards and Pantone certification. Produce reliable, consistent, high gloss, colour print quality with improved HP ColorSphere toner. Advanced paper handling options include a booklet maker and a stapler/stacker.

¹ Optional accessory
Please purchase separately
Available as standard with HP Color LaserJet CM6030f and CM6040f MFP.

² With CM6030 MFP series

³ With CM6040 MFP series

⁴ Optional accessory
Please purchase separately
Available as standard with HP Color LaserJet CM6030f and CM6040f MFP

⁵ Buyer's Lab gave HP a "Pick of the Year" award in December 2006 for Outstanding Achievement for the User Interface Design of its Multifunction Printers

⁶ Up to SRA3.



HP Color LaserJet
CM6030 Multifunction
Printer



HP Color LaserJet
CM6030f Multifunction
Printer



HP Color LaserJet
CM6040 Multifunction
Printer



HP Color LaserJet
CM6040f Multifunction
Printer

Series at a glance



HP Color LaserJet CM6030 Multifunction Printer

- Print and copy speed up to 31ppm A4 and 17ppm A3
- Effective output quality with ImageREt4800 and up to 1200x600 dpi
- 600x600 dpi scan resolution
- 512MB RAM expandable to 768MB RAM
- 80GB Hard Disk drive capacity
- 835MHz processor
- Automatic two-sided printing
- 50-sheet Automatic Document Feeder (ADF)
- Input capacity of 1100-sheet (from 100-sheet MP tray and 2 x 500-sheet trays)
- Standard 500-sheet output capacity
- Colour Access Controls



HP Color LaserJet CM6030f Multifunction Printer

- HP Color LaserJet CM6030f MFP: as base model plus fax and 2 additional 500-sheet input trays making a total of 2100-sheet input capacity.



HP Color LaserJet CM6040 Multifunction Printer

- Print and copy speed up to 41ppm A4 and 23ppm A3
- Effective output quality with ImageREt4800 and up to 1200x600 dpi
- 600x600 dpi scan resolution
- 512MB RAM expandable to 768MB RAM
- 80GB Hard Disk drive capacity
- 835MHz processor
- Automatic two-sided printing
- 50-sheet Automatic Document Feeder (ADF)
- Input capacity of 1100-sheet (from 100-sheet MP tray and 2 x 500-sheet trays)
- Standard 500-sheet output capacity
- Colour Access Controls
- Blue Angel certified



HP Color LaserJet CM6040f Multifunction Printer

- HP Color LaserJet CM6040 plus:
- Analog fax
- 2 additional 500-sheet trays (bringing the total input capacity to 2100-sheet)
- Energy Star certified

Recommended accessories



CC517A
HP 3-bin Stapler/Stacker
with Output



CC516A
HP Booklet Maker/Finisher
with Output



C8091A
HP Staple Cartridge Refill



Q3701A
HP LaserJet MFP Analog Fax
Accessory 300



CC383A
HP 2-pack 2000-staple
Cartridge



T1936AA
HP MFP Digital Sending
Software 4.0



J7961G
HP Jetdirect 635n IPv6/IPsec Print Server



J8007G
HP Jetdirect 690n IPv6/IPsec 802.11g Wireless Print Server



J8018A
HP Secure High Performance Hard Disk Drive

Operating and warranty specifications

Operating environment	Operating temperature: 15 to 27° C. Recommended operating temperature: 15 to 27° C. Operating humidity: 10 to 80% RH. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0 to 35° C. Storage humidity: 35 to 85% RH. Noise level per ISO 9296: sound power: LwAd6.8 B(A) (active/printing), 6.9 B(A) (active/copy or scan), 5.8 B(A) (ready). Sound pressure: LpAm56.8 dB(A) (active/printing), 57.1 B(A) (active/copy or scan), 40.3 dB(A) (ready)
Certifications	CISPR 22: 2005/EN 55022: 2006 Class B, EN 61000-3-2: 2000 +A2, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1 +A2, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries. Regulatory standards: IEC 60950-1 (International), EN 60950-1 +A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 Class 1, 21 CFR Ch. 1/SubCh. J and Laser Notice#50 (July 26th 2001)(Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe). Other safety approvals as required by individual countries. ENERGY STAR: Yes
Warranty	1 year Next Business Day On-Site standard. Warranty and support options vary by product, country and local legal requirements.

Ordering information



HP Color LaserJet CM6030 Multifunction Printer (CE664A)
HP Color LaserJet CM6030 MFP unit, CD Assembly (Driver/User Guide), Digital Sending Software (DSS) Trial Version CD, Getting Started Guide, Wall Poster with Helpful Tips, Telephone Support Flyer, Power Cords, Control Panel Overlays, and the Cyan, Magenta, Yellow and Black Toner Cartridges already installed within the device.



HP Color LaserJet CM6030f Multifunction Printer (CE665A)
Same as the CM6030, except: HP Color LaserJet CM6030f MFP unit, and fax cable



HP Color LaserJet CM6040 Multifunction Printer (Q3938A)
Same as the CM6030, except: HP Color LaserJet CM6040 MFP unit



HP Color LaserJet CM6040f Multifunction Printer (Q3939A)
Same as the CM6030, except: HP Color LaserJet CM6040f MFP unit, and fax cable

Accessories, Supplies and Support

Accessories

CC517A	HP 3-bin Stapler/Stacker with Output
CC516A	HP Booklet Maker/Finisher with Output
C8091A	HP Staple Cartridge Refill
Q3701A	HP LaserJet MFP Analog Fax Accessory 300
CC383A	HP 2-pack 2000-staple Cartridge
T1936AA	HP MFP Digital Sending Software 4.0
J8019A	HP Secure High Performance EIO Hard Disk
J8018A	HP Secure High Performance Hard Disk Drive

Supplies

CE487A	HP Color LaserJet CE487A ADF Roller Kit
CB390A	HP Color LaserJet CB390A Black Print Cartridge Average continuous Black Cartridge yield 19,500 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CB381A	HP Color LaserJet CB381A Cyan Print Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 21,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CB382A	HP Color LaserJet CB382A Yellow Print Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 21,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CB383A	HP Color LaserJet CB383A Magenta Print Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 21,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*

CB384A	HP Color LaserJet CB384A Black Image Drum 35,000 pages*
CB385A	HP Color LaserJet CB385A Cyan Image Drum 35,000 pages*
CB386A	HP Color LaserJet CB386A Yellow Image Drum 35,000 pages*
CB387A	HP Color LaserJet CB387A Magenta Image Drum 35,000 pages*
CB458A	HP Color LaserJet CB458A 220V Fuser Kit
CB459A	HP Color LaserJet CB459A Roller Kit
CB463A	HP Color LaserJet CB463A Transfer Kit

Connectivity

J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
J8007G	HP Jetdirect 690n IPv6/IPsec 802.11g Wireless Print Server
C6518A	HP USB Cable, 2m

Service & support

UJ165A/E	HP Care Pack, Next Business Day On site Response, 3 years
UJ169E	HP Care Pack, Same Business Day On site Response, 4-Hour, 13x5, 3 years
UJ166E	HP Care Pack, Next Business Day On site Response, 4 years
UJ167E	HP Care Pack, Next Business Day On site Response, 5 years
UJ174PE	HP Care Pack, Post Warranty, Next Business Day On site Response, 1 year
UJ176PE	HP Care Pack, Post Warranty Same Business Day On site Response, 4-Hour, 13x5, 1 year

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>
For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

* Declared yield value in accordance with ISO/IEC 19798



Technical specifications

Print technology	Laser		
Print speed	A4:black:CM6030:Up to 31 ppm; CM6030f:Up to 31 ppm; CM6040:Up to 41 ppm; CM6040f:Up to 41 ppm, color:CM6030:Up to 31 ppm; CM6030f:Up to 31 ppm; CM6040:Up to 41 ppm; CM6040f:Up to 41 ppm. A3:CM6030:Up to 17 ppm; CM6030f:Up to 17 ppm; CM6040:Up to 23.5 ppm; CM6040f:Up to 23.5 ppm. First page out black,CM6030:< 15.5 sec (from ready); CM6030f:< 15.5 sec (from ready); CM6040:< 11.5 sec (from ready); CM6040f:< 11.5 sec (from ready), colour:CM6030:< 15.8 sec (from ready); CM6030f:< 15.8 sec (from ready); CM6040:< 11.5 sec (from ready); CM6040f:< 11.5 sec (from ready); . Warm-up time:less thanCM6030:124.3 sec; CM6030f:124.3 sec; CM6040:112 sec; CM6040f:112 sec Exact speed varies depending on the system configuration, software program and document complexity.		
Processor	835 MHz. PMC-Sierra RM7965 64-bit Microprocessor		
Memory	512 MB. Hard Disk Capacity:Standard, 80 GB		
Print	Quality	HP ImageREt 4800	
	Resolution	Black:Up to 1200 x 600 dpi, Color:Up to 1200 x 600 dpi	
	Printer languages	HP PCL 5, HP PCL 6, HP Postscript level 2 emulation (default), HP Postscript level 3 emulation is supported	
	Economical printing	Two-sided printing and N-up printing/copying (saves paper), Colour Access Control (printing/copying in black saves toner)	
	Typefaces/fonts	Set of 80 HP fonts (plus Greek, Hebrew, Cyrillic, Arabic)	
	Duty cycle (monthly, A4)	Up to 200000 pages	
	Recommended monthly page volume	CM6030:5000 to 10000; CM6030f:5000 to 10000; CM6040:8000 to 15000; CM6040f:8000 to 15000	
	Print margins (mm)	Top:4.2 mm. Left:4.2 mm. Right:4.2 mm. Bottom:4.2 mm	
	Maximum print area	316 x 453.2 mm	
Fax	Modem speed	13 sec per page	
	Telecom compliance	CM6030f:ES 203 021, R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe), FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703, GB3382 (China) other Telecom approvals as required by individual countries; CM6040f:ES 203 021, R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe), FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703, GB3382 (China), other Telecom approvals as required by individual countries	
	Fax memory	Up to 60,000 pages (depending on available free disk space)	
	Fax resolution	Standard:100 x 100 dpi. Fine:200 x 200 dpi. Superfine:300 x 300 dpi	
	Quick dialing	Up to 100 (each can contain 100 numbers)	
Digital sending	File formats	PDF, JPEG, TIFF, or MTIFF. (OCR supports PDF, TEXT, RTF (Microsoft® Word® Compatible), XML, HTML; send to workflow (DSS) supported file types include XML, searchable PDF, TXT, RTF (Microsoft® Word® Compatible), HTML, PDF, JPEG, TIFF, and MTIFF	
	Installation	Fast Ethernet, Gigabit Ethernet, 802.11b wireless	
	Features	Standard:Scan to folder (includes shared address book for fax), scan direct to e-mail server, send to e-mail, analog fax, LDAP e-mail addressing; authentication: Windows® negotiated (Kerberos and NTLM), group 1 and group 2 PIN, LDAP, authentication manager	
Scan	Type	Flatbed, ADF. Colour scanning:Yes	
	Scan resolution	Optical:Up to 600 dpi	
	Grey scale levels	256	
	Scannable area	Minimum media size:12.7 x 12.7 cm. Maximum media size:29.7 x 43.2 cm	
	Margins for scanned items	Left:4.2. Top:4.2. Right:4.2. Bottom:4.2	
Copy	Copy speed	CM6030:Up to 31 cpm; CM6030f:Up to 31 cpm; CM6040:Up to 41 cpm; CM6040f:Up to 41 cpm	
	Copy resolution	Up to 600 x 600 dpi	
	Multiple copies	Up to 999	
	Reduce/enlarge	25 to 400%	
Media handling	Input:	Capacity	Weight
	Tray 1		60 to 220 g/m ²
	Tray 2		60 to 220 g/m ²
	Tray 3		60 to 220 g/m ² (same for Tray 4 and Tray 5)
	ADF		60 to 220 g/m ²
	Output:	Sheets: Up to 500-sheet without finisher	
	Duplex printing:Automatic (standard)		
Media types	Paper (bond, recycled, glossy, mid-weight, heavy, heavy glossy, extra heavy, extra heavy glossy, tough, rough), transparencies, labels, envelopes, cardstock		
Interface and connectivity	Hi-Speed USB 2.0 device port, one open EIO slot, HP Jetdirect Gigabit Ethernet embedded print server, fax port, Foreign Interface Harness (FIH) port, PCI express. Optional:HP Jetdirect EIO internal print servers, HP Jetdirect external print servers, wireless print server, printer adapter		
Network operating systems compatibility	Microsoft® Windows® Server 2003, XP, 2003 64-bit, XP 64-bit; Windows Vista®, 64-bit (For Microsoft® IPv6 compatible with Microsoft® Windows® 2003, XP, and Windows Vista®); Novell® 5.1 or higher, Mac OS X v10.2, v10.3, v10.4 or higher; RED HAT Linux 7.x or higher; SUSE Linux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris® 2.5 or higher (SPARC® systems only); IBM® AIX 3.2.5 or higher; MPE-iX; Citrix® MetaFrame Server; Windows® Terminal Services		
Minimum system requirements	Microsoft® Windows® XP: 333 MHz processor with 128 MB RAM; Microsoft® Windows® Server 2003: 550 MHz processor with 128 MB RAM; Windows Vista®: 800 MHz processor with 512 MB RAM; CD-ROM/DVD drive, Internet connection, USB or network port connection. Mac OS X v10.2.8, v10.3, v10.4 and higher with 128 MB RAM, CD-ROM, 160 MB of free hard disk space (For Mac OS v10.4 and higher, PowerPC and Intel® Core Processor Macs are supported)		
Standard software	Print drivers and installation software on CD-ROM: HP common installer, HP Internet installer, HP common drivers, HP Installation Wizard, Postscript Printer Description (PPD) files, Printer Dialog Extensions (PDEs), HP Printer Utility for use with Macintosh computers		
Control panel	5 LED indicator lights, 10-key numeric pad, graphical touch screen display (192 x 72 mm) 640 x 240 resolution with adjustable contrast		
Power	Requirements:Input voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 10.5 amp; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 5.5 amp. *115 VAC unit tested. Data from colour simplex printing and copying.		
Dimensions (w x d x h)	Out of package:704 x 673 x 988 mm. Packaged:935 x 800 x 1210 mm		
Weight	Out of package:CM6030:139.87 kg; CM6030f:144.91 kg; CM6040:139.87 kg ; CM6040f:144.91 kg. Packaged:CM6030:154.92 kg; CM6030f:159.96 kg; CM6040:154.92 kg; CM6040f:159.96 kg		
Printer management	HP Web Jetadmin, HP Embedded Web Server		

<http://www.hp.com/uk>



© Copyright 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 11/09 4AA1-3943EEE

